NORTHSTAR RANGE FEATURES AND SPECIFICATIONS							
(SUBJECT TO CHANGE WITHOUT	1947	1954	1954Z	1955	1955Z	1956	1956Z
NOTICE)	36" DUAL	30"	30"	30" DUAL	30" DUAL	30"	30"
	FUEL	ELECTRIC	ELECTRIC	FUEL	FUEL	GAS	GAS
DIMENSIONS:				_			
Width	36"	30"	30"	30"	30"	30"	30"
Height	49"	49"	43-1/4"	49"	43-1/4"	49"	43-1/4"
<u> </u>		36"	36"	38"	36"	38"	36"
Height to Cooking Surface	37-1/4"						
Depth (plus 2" handles)	28-1/2"	28-1/2"	28-1/2"	28-1/2"	28-1/2"	28-1/2"	28-1/2"
OVEN:							
Fuel	Electric	Electric	Electric	Electric	Electric	LP or Natural Gas	LP or Natura Gas
Capacity (Cubic Feet)	5.0	4.3 (4.0 Convection)	4.3	4.3 (4.0 Convection)	4.3	4.0	4.0
Width	31"	25"	25"	25"	25"	25"	25"
Height	15-1/2"	16"	16"	16"	16"	15-1/2"	15-1/2"
Depth (Standard / Convection)	18"	17-1/2" / 16-1/2"	17-1/2"	17-1/2" / 16-1/2"	17-1/2"	17-1/2"	17-1/2"
Delayed Start Baking / Cleaning	•	•		•		•	
Variable Temperature Broil	•	•		•		•	
Oven Lights	Halogen	Halogen	Halogen	Halogen	Halogen	Incandescent	Incandescer
Commercial-Grade Plated Racks	•	•	•	•	•	•	•
True Convection	Standard	Optional	N/A	Optional	N/A	N/A	N/A
Self Clean	Standard	Standard	N/A	Standard	N/A	Standard	N/A
RANGE TOP:							
Electric High-Speed Radiant Elements		•	•				
1,500 Watt Radiant (Rear)		2	2				
2,000 Watt Radiant (Front Left)		1	1				
2,500 Watt Radiant (Front Right)		1	1				
Gas Sealed Burners / Cast Grates	•			•	•	•	•
8,000* BTU Gas Burners (Rear)	3			2	2	2	2
15,000* BTU Gas Burner (Front L)	1			1	1	1	1
15,000* BTU Gas Burner (Front R)	1						
12,000* BTU Gas Burners (Front R)				1	1	1	1
12,000* BTU Gas Burner (Front C)	1						
Electronic Spark with Re-Ignition	•			•	•	•	•
* Ratings are for Natural Gas; Liquid Pro	opane is approx	imately 10% lov	ver				
Power Rating - Natural Gas (BTUs)	66,000			43,000	43,000	58,000	58,000
Power Rating – LP (BTUs)	59,400			38,700	38,700	52,000	52,000
Power – Oven Burner NG (BTUs)						16,000	16,000
Power Rating – Oven LP (BTUs)						14,400	14,400
Electrical Source (208 – 250V)	220V – 40A	220V – 40A	220V – 40A	220V – 25A	220V – 25A	110V – 15A	110V - 15A
STAINLESS STEEL WARMER (ST	ORAGE WHE	NOT IN USI	≣):				
Located in Lower Drawer	N/A	Optional	N/A	Optional	N/A	N/A	N/A
	·		· · · · · · · · · · · · · · · · · · ·			<u> </u>	, , , , , , , , , , , , , , , , , , ,
Dimensions 26-3/4"W x 22-1/2"D x 5-3	/8 H						

All 220V ranges come with a standard four-wire range cord attached. NOTE: The January 1998 electrical standard requires that a four-wire range cord be used in all new construction. Please advise us if a three-wire range cord is required (used only in existing construction). Electrical receptacle and gas piping should be installed approximately in the center of the opening, as close to the floor as practical.

N/A = Not Available