

PFD 101 U Built-under dishwasher for large loads of dishware in households, offices and utility areas.



- Wash performance: 13 place settings in just 52 min.*
- Everything completely dry AutoOpen assisted drying
- Intuitive to operate thanks to clear fascia panel design
- Flexible loading of wash items for the best cleaning results

EAN: 4002516366850 / Material number: 11605420 / Old Material Number: 61010102USA

Number of levels Front Stainless steel Galvanised Fascia color Application Suitable for retirement and care homes Suitable for Ped & Breakfast Suitable for o'ffices Suitable for o'ffices Suitable for offices Suitable for offices Suitable for offices Suitable for ormali businesses Suitable for ormali businesses Suitable for ormali businesses Suitable for sports clubs Performance data Tested virucidal efficacy Controls Program selection Program selection Program sequence indicator Standard electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Length of power cord in ft (m) NEMA plug: 5-15 Possible voltage variant 1 Electrical connection and plus in kW Fuse rating in kW Suitable for power cord in ft (m) Fuse rating in A Suitable for some some some some some some some some	EAN. 40023103000307 Material number. 110034207 Old N	
Front Side walls Galvanised Cleansteel Side walls Galvanised Cleansteel Application Suitable for retirement and care homes Suitable for retirement and care homes Suitable for Bed & Breakfast Suitable for child care facilities Suitable for child care facilities Suitable for or child care facilities Suitable for or child care facilities Suitable for or miversities and schools Suitable for offices Suitable for sports cluse Suitable for small businesses Suitable for deal of scale Suitable for deal ficacy Service life in wash cycles Controls Performance data Tested virucidal efficacy Standard electrical connection Program sequence indicator Standard electrical connection Electrical connected load in kW 1.30 1.40 1.5 1.40 1.5 1.6 1.7 1.40 1.5 1.7 1.40 1.5 1.7 1.40 1.5 1.7 1.40 1.5 1.7 1.7 1.40 1.5 1.7 1.7 1.7 1.7 1.7 1.7 1.7 1.7 1.7 1.7	Model and design	
Side walls		
Fascia color Application Suitable for retirement and care homes Suitable for hospitals Suitable for Sed & Breakfast Suitable for offices Suitable for small businesses Suitable for small businesses Suitable for sports clubs Performance data Tested virucidal efficacy Circulation pump, Omax in gal/min (l/min) Service life in wash cycles Controls Program selection Program selection Program sequence indicator Standard electrical connection Electrical connection Electrical connection Fuse rating in kW 1.30 Total connected load in kW 1.40 Fuse rating in A Length of power cord in ft (m) NEMA plug: 5-15 Possible voltage variant 1 Electrical connection Electrical connection Supplication Program selection Solution Solu		
Application Suitable for retirement and care homes Suitable for Bed & Breakfast Suitable for Child care facilities Suitable for offices Suitable for offices Suitable for ofmestic use Suitable for small businesses Suitable for sports clubs Performance data Tested virucidal efficacy Circulation pump, Omax in gal/min (/min) Service life in wash cycles Circulation pump, Omax in gal/min (/min) Service life in wash cycles Circulation pump, Omax in gal/min (/min) Service life in wash cycles Controls Program selection Program selection Program selector Buttons Program sequence indicator Standard electrical connection Electrical connection AC 120V 60HZ Heater rating in kW 1.30 Total connected load in kW 1.40 Fuse rating in A Length of power cord in ft (m) NEMA plug: 5-15 Possible voltage variant 1 Electrical connection 2N AC 120/208-240V, 60HZ Heater rating in kW 3.50-3.80 Total connected load in kW Fuse rating in A 30 Water connection/drainage Required flow pressure in bar Dorain hose [DN] Maximum delivery head for drain pump in inches (cm) Water protection system Dimensions and weight External dimensions, gross height in inches External dimensions, gross depth in inches (cm) Usable space in wash cabinet, width in inches (cm) Usable space in wash cabinet, depth of lower basket in inches (cm) Usable space in wash cabinet, depth of lower basket in inches (cm) Usable space in wash cabinet, depth of lower basket in inches (cm)		
Suitable for retirement and care homes Suitable for hospitals Suitable for hospitals Suitable for child care facilities Suitable for child care facilities Suitable for universities and schools Suitable for offices Suitable for small businesses Suitable for small businesses Suitable for sports clubs Performance data Tested virucidal efficacy Circulation pump, Omax in gal/min (l/min) Service life in wash cycles Controls Program selection Program selection Program selection Program sequence indicator Standard electrical connection Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Length of power cord in ft (m) NEMA plug: 5-15 Possible voltage variant 1 Electrical connection Heater rating in kW Total connected load in kW Total connected load in kW 7 total connection Prossible voltage variant 1 Electrical connection Beater rating in kW Total connected load in kW Total connected load in kW Total connected load in kW 3.50-3.80 Water connection/drainage Required flow pressure in bar Drain hose [DN] Maximum delivery head for drain pump in inches (cm) Water protection system Dimensions and weight External dimensions, gross height in inches External dimensions, gross depth in inches Lable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm)		Cleansteel
Suitable for hospitals Suitable for Bed & Breakfast Suitable for child care facilities Suitable for universities and schools Suitable for offices Suitable for offices Suitable for domestic use Suitable for small businesses Suitable for small businesses Suitable for small businesses Suitable for sports clubs Performance data Tested virucidal efficacy Circulation pump, Omax in gal/min (l/min) Service life in wash cycles Controls Program selection Program selection Program selection Program sequence indicator Standard electrical connection Electrical connection Heater rating in kW Total connected load in kW Tuse rating in A Length of power cord in ft (m) NEMA plug: 5-15 Possible voltage variant 1 Electrical connection Fuse rating in kW Total connected load in kW Total connected load in kW Total connection Reater rating in kW 3.50-3.80 Total connection Program in A Sun AC 120/208-240V, 60HZ Heater rating in kW 3.50-3.80 Total connection GOHZ Heater rating in kW 3.50-3.80 Total connection/drainage Required flow pressure in bar Drain hose [DN] Maximum delivery head for drain pump in inches (cm) Water protection system Water protection system Water protection system Dimensions and weight External dimensions, gross height in inches External dimensions, gross width in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm)	Application	
Suitable for Bed & Breakfast Suitable for child care facilities Suitable for child care facilities Suitable for offices Suitable for offices Suitable for domestic use Suitable for small businesses Suitable for sports clubs Performance data Tested virucidal efficacy Circulation pump, Qmax in gal/min (l/min) Service life in wash cycles Program selection Program selection Program sequence indicator Standard electrical connection Electrical connected load in kW Tuser arting in A Length of power cord in ft (m) NEMA plug: 5-15 Possible voltage variant 1 Electrical connected load in kW Total connected load in kW Total connected load in kW Total connection Beater rating in KW 1.30 Total connection Sum AC 120/208-240V, 60HZ Heater rating in W 3.50-3.80 Total connection Program selection Prossible voltage variant 1 Electrical connection Beater rating in A Water connection Vater promotion/drainage Required flow pressure in bar Drain hose [DN] Water protection system Water protection system Dimensions and weight External dimensions, gross height in inches External dimensions, gross width in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) 17 3/4 (450)		•
Suitable for child care facilities Suitable for universities and schools Suitable for offices Suitable for small businesses Suitable for small businesses Suitable for sports clubs Performance data Tested virucidal efficacy Circulation pump, Omax in gal/min (l/min) Service life in wash cycles Controls Program selection Program selection Program selection Program selection Standard electrical connection Electrical connection AC 120V 60HZ Heater rating in kW 1.30 Total connected load in kW Fuse rating in A Length of power cord in ft (m) NEMA plug: 5-15 Possible voltage variant 1 Electrical connection Heater rating in kW 3.50-3.80 3.70-4.00 Fuse rating in A Water connected load in kW Susar ating in A Water connection/drainage Required flow pressure in bar Drain hose [DN] Aximum delivery head for drain pump in inches (cm) Water protection system Dimensions and weight External dimensions, gross height in inches External dimensions, gross depth in inches External dimensions, gross depth in inches Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm)	Suitable for hospitals	•
Suitable for universities and schools Suitable for offices Suitable for offices Suitable for domestic use Suitable for sports clubs Performance data Tested virucidal efficacy Circulation pump, Omax in gal/min (l/min) Service life in wash cycles Controls Program selection Program selection Program sequence indicator Standard electrical connection Electrical connected load in kW Total connected load in kW Fuse rating in A Length of power cord in ft (m) NEMA plug: 5-15 Possible voltage variant 1 Electrical connection Electrical connection Pleater rating in kW 3.50-3.80 Total connected load in kW Fuse rating in N AC 120/208-240V, 60HZ Heater rating in N AC 30 Water connection 2N AC 120/208-240V, 60HZ Heater rating in N May a 3.50-3.80 Total connected load in kW Fuse rating in N Subject to the service of	Suitable for Bed & Breakfast	•
Suitable for offices Suitable for small businesses Suitable for small businesses Performance data Tested virucidal efficacy Circulation pump, Qmax in gal/min (l/min) Service life in wash cycles Program selection Program selection Program sequence indicator Standard electrical connection Electrical connection Fleater rating in kW Total connected load in kW Fuse rating in A Length of power cord in ft (m) NEMA plug: 5-15 Possible voltage variant 1 Electrical connection Heater rating in kW 3.50-3.80 Total connected load in kW Fuse rating in A Solution Read to 120/208-240V, 60HZ Heater rating in W 3.50-3.80 Total connected load in kW Fuse rating in N Water connection AC 120/208-240V, 60HZ Beater rating in load in l	Suitable for child care facilities	•
Suitable for domestic use Suitable for small businesses Suitable for sports clubs Performance data Tested virucidal efficacy Circulation pump, Omax in gal/min (l/min) Service life in wash cycles Controls Program selection Program selection Program sequence indicator Standard electrical connection Electrical connection Electrical connection AC 120V 60HZ Heater rating in kW 1.30 Total connected load in kW Fuse rating in A Length of power cord in ft (m) NEMA plug: 5-15 Possible voltage variant 1 Electrical connection Heater rating in kW 3.50-3.80 Total connected load in kW 7 total connected load in kW Total connected sod in kW Total connected rating in which in chese [DN] Water protection yessure in bar Drain hose [DN] Maximum delivery head for drain pump in inches (cm) Syad (12 (670) External dimensions, gross height in inches External dimensions, gross depth in inches External dimensions, gross depth in inches External dimensions, gross depth in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm)	Suitable for universities and schools	•
Suitable for small businesses Suitable for sports clubs Performance data Tested virucidal efficacy Circulation pump, Cmax in gal/min (l/min) Service life in wash cycles Controls Program selection Program selection Program selection Program sequence indicator Standard electrical connection Electrical connection AC 120V 60HZ Heater rating in kW 1.30 Total connected load in kW 1.40 Fuse rating in A 15 Length of power cord in ft (m) NEMA plug: 5-15 Possible voltage variant 1 Electrical connection Heater rating in kW 3.50-3.80 Total connected load in kW 7 total connection 30 Water connected load in kW 3.70-4.00 Fuse rating in A 30 Water connection/drainage Required flow pressure in bar Drain hose [DN] Maximum delivery head for drain pump in inches (cm) Simple space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm)	Suitable for offices	•
Suitable for sports clubs Performance data Tested virucidal efficacy Circulation pump, Qmax in gal/min (l/min) Service life in wash cycles Program selection Program selection Program sequence indicator Standard electrical connection Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Length of power cord in ft (m) NEMA plug: 5-15 Possible voltage variant 1 Electrical connection Heater rating in kW Total connected load in kW Total connected load in kW Fuse rating in A South Collective variant 1 Electrical connection Relater rating in kW Total connected load in kW Total connected load in kW Total connection South Collective variant 1 Electrical connection Consider variant 1 Electrical connection South Collective variant 1 Electrical connected load in kW Total connected load in kW Tot	Suitable for domestic use	•
Performance data Tested virucidal efficacy Circulation pump, Omax in gal/min (l/min) Service life in wash cycles Controls Program selection Program selection Program sequence indicator Standard electrical connection Electrical connection Heater rating in kW 1.30 Total connected load in kW 1.40 Fuse rating in A Length of power cord in ft (m) NEMA plug: 5-15 Possible voltage variant 1 Electrical connection Electrical connection AC 120V 60HZ 1.40 Fuse rating in A 15 Length of power cord in ft (m) NEMA plug: 5-15 Possible voltage variant 1 Electrical connection 2N AC 120/208-240V, 60HZ Heater rating in kW 3.50-3.80 Total connected load in kW 3.70-4.00 Fuse rating in A 30 Water connection/drainage Required flow pressure in bar Drain hose [DN] 22 Maximum delivery head for drain pump in inches (cm) Water protection system Dimensions and weight External dimensions, gross height in inches External dimensions, gross width in inches External dimensions, gross depth in inches External dimensions, gross depth in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm)	Suitable for small businesses	•
Tested virucidal efficacy Circulation pump, Qmax in gal/min (l/min) Service life in wash cycles Controls Program selection Program selector Buttons Program sequence indicator Standard electrical connection Electrical connection AC 120V 60HZ Heater rating in kW 1.30 Total connected load in kW 1.40 Fuse rating in A Length of power cord in ft (m) Sessible voltage variant 1 Electrical connection Heater rating in kW 3.50-3.80 Total connected load in kW 7 total connection Prossible voltage variant 1 Electrical connection 2N AC 120/208-240V, 60HZ Heater rating in kW 3.50-3.80 Total connected load in kW 3.70-4.00 Fuse rating in A Water connection/drainage Required flow pressure in bar Dirain hose [DN] Maximum delivery head for drain pump in inches (cm) Water protection system Dimensions and weight External dimensions, gross height in inches External dimensions, gross depth in inches (27 5/8 (700) Lsable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm)	Suitable for sports clubs	•
Circulation pump, Qmax in gal/min (l/min) Service life in wash cycles Controls Program selection Program selector Buttons Program selector Buttons Standard electrical connection Electrical connection Heater rating in kW 1.30 Total connected load in kW Fuse rating in A Length of power cord in ft (m) NEMA plug: 5-15 Possible voltage variant 1 Electrical connection Heater rating in kW 3.50-3.80 Total connected load in kW Total connection Program Selector Buttons AC 120V 60HZ Hado 1.40 1.40 Fuse rating in A Length of power cord in ft (m) NEMA plug: 5-15 Possible voltage variant 1 Electrical connection 2N AC 120/208-240V, 60HZ Heater rating in kW 3.50-3.80 3.70-4.00 Fuse rating in A Water connection/drainage Required flow pressure in bar Drain hose [DN] 22 Maximum delivery head for drain pump in inches (cm) Water protection system Dimensions and weight External dimensions, gross height in inches External dimensions, gross width in inches External dimensions, gross depth in inches External dimensions, gross depth in inches External dimensions, gross depth in inches (mm) Usable space in wash cabinet, height in inches (mm) Usable space in wash cabinet, depth of upper basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm)	Performance data	
Service life in wash cycles Controls Program selection Program sequence indicator Standard electrical connection Electrical connection Electrical connection Heater rating in kW 1.30 Total connected load in kW 1.40 Fuse rating in A Length of power cord in ft (m) NEMA plug: 5-15 Possible voltage variant 1 Electrical connection Electrical connection Beater rating in kW 3.50-3.80 Total connected load in kW 3.70-4.00 Fuse rating in A 30 Water ronnection load in kW 3.70-4.00 Fuse rating in A Water connection/drainage Required flow pressure in bar Drain hose [DN] External dimensions, gross height in inches (cm) Dimensions and weight External dimensions, gross width in inches External dimensions, gross width in inches External dimensions, gross depth in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm)	Tested virucidal efficacy	•
Service life in wash cycles Controls Program selection Program sequence indicator Standard electrical connection Electrical connection Electrical connection Heater rating in kW 1.30 Total connected load in kW 1.40 Fuse rating in A Length of power cord in ft (m) NEMA plug: 5-15 Possible voltage variant 1 Electrical connection Electrical connection Beater rating in kW 3.50-3.80 Total connected load in kW 3.70-4.00 Fuse rating in A 30 Water ronnection load in kW 3.70-4.00 Fuse rating in A Water connection/drainage Required flow pressure in bar Drain hose [DN] External dimensions, gross height in inches (cm) Dimensions and weight External dimensions, gross width in inches External dimensions, gross width in inches External dimensions, gross depth in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm)	Circulation pump, Qmax in gal/min (l/min)	283.9 (75)
Controls Program selection Program Selector Buttons Program sequence indicator • Standard electrical connection AC 120V 60HZ Beater rating in kW 1.30 Total connected load in kW 1.40 Fuse rating in A 15 Length of power cord in ft (m) 5 (1.70) NEMA plug: 5-15 • Possible voltage variant 1 Electrical connection Electrical connection 2N AC 120/208-240V, 60HZ Heater rating in kW 3.50-3.80 Total connected load in kW 3.70-4.00 Fuse rating in A 30 Water connection/drainage Pequired flow pressure in bar Required flow pressure in bar 0.30-10.00 Drain hose [DN] 22 Maximum delivery head for drain pump in inches (cm) 39 3/8 (100) Water protection system Waterproof system Dimensions and weight External dimensions, gross height in inches 26 1/2 (670) External dimensions, gross depth in inches 27 5/8 (700) Usable space in wash cabinet, width in inches (mm) 20 1/8 (540) Usable space in wash cabinet, depth of upper basket in inches (mm)		
Program selection Program sequence indicator Standard electrical connection Electrical connection AC 120V 60HZ Heater rating in kW 1.30 Total connected load in kW 1.40 Fuse rating in A Length of power cord in ft (m) NEMA plug: 5-15 Possible voltage variant 1 Electrical connected load in kW 3.50-3.80 Total connected load in kW 3.70-4.00 Fuse rating in kW 3.70-4.00 Fuse rating in A Water connected load in kW 3.70-4.00 Fuse rating in A Water connected load in kW 3.70-4.00 Fuse rating in A Water connection/drainage Required flow pressure in bar Drain hose [DN] Water protection system Dimensions and weight External dimensions, gross height in inches External dimensions, gross depth in inches External dimensions, gross depth in inches Usable space in wash cabinet, depth of upper basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm)		
Program sequence indicator Standard electrical connection Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Length of power cord in ft (m) NEMA plug: 5-15 Possible voltage variant 1 Electrical connection Heater rating in kW Total connection 2N AC 120/208-240V, 60HZ Heater rating in kW 3.50-3.80 Total connected load in kW 7otal connected load in kW 3.70-4.00 Fuse rating in A Water connection/drainage Required flow pressure in bar Drain hose [DN] Maximum delivery head for drain pump in inches (cm) Water protection system Water protection system Dimensions and weight External dimensions, gross height in inches External dimensions, gross depth in inches External dimensions, gross depth in inches Usable space in wash cabinet, width in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm)		Program Selector Buttons
Standard electrical connection Electrical connection AC 120V 60HZ Heater rating in kW 1.30 Total connected load in kW 1.40 Fuse rating in A 15 Length of power cord in ft (m) 5 (1.70) NEMA plug: 5-15 • Possible voltage variant 1 • Electrical connection 2N AC 120/208-240V, 60HZ Heater rating in kW 3.50-3.80 Total connected load in kW 3.70-4.00 Fuse rating in A 30 Water connection/drainage ** Required flow pressure in bar 0.30-10.00 Drain hose [DN] 22 Maximum delivery head for drain pump in inches (cm) 39 3/8 (100) Water protection system Waterproof system Dimensions and weight ** External dimensions, gross height in inches 37 7/8 (960) External dimensions, gross width in inches 26 1/2 (670) External dimensions, gross depth in inches 27 5/8 (700) Usable space in wash cabinet, width in inches (mm) 20 1/8 (510) Usable space in wash cabinet, depth of upper basket in inches (mm) 17 3/4 (450)	· ·	•
Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Length of power cord in ft (m) NEMA plug: 5-15 Possible voltage variant 1 Electrical connection Electrical connection Beater rating in kW Total connected load in kW Total connection Electrical connection Beater rating in kW Total connected load in kW Total connected load in kW Total connected load in kW Total connection/drainage Required flow pressure in bar Drain hose [DN] Water protection system Dimensions and weight External dimensions, gross height in inches External dimensions, gross width in inches External dimensions, gross depth in inches External dimensions External dimensions, gross depth in inches External dimensions Externa		
Heater rating in kW Total connected load in kW Fuse rating in A Length of power cord in ft (m) NEMA plug: 5-15 Possible voltage variant 1 Electrical connection Electrical connection Beater rating in kW Total connected load in kW Total connection/drainage Required flow pressure in bar Drain hose [DN] Maximum delivery head for drain pump in inches (cm) Water protection system Dimensions and weight External dimensions, gross height in inches External dimensions, gross depth in inches External dimensions External dimensions, gross depth in inches External dimensions External dimensions External dimensions External dimensions External dimensions External dim		AC 120V 60H7
Total connected load in kW Fuse rating in A Length of power cord in ft (m) NEMA plug: 5-15 Possible voltage variant 1 Electrical connection Electrical connection Connected load in kW Total connection/drainage Required flow pressure in bar Drain hose [DN] Water protection system Dimensions and weight External dimensions, gross height in inches External dimensions, gross depth in inches External dimensions, gross depth in inches Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm)		
Fuse rating in A Length of power cord in ft (m) NEMA plug: 5-15 Possible voltage variant 1 Electrical connection Electrical connection 2N AC 120/208-240V, 60HZ Heater rating in kW 3.50-3.80 Total connected load in kW 3.70-4.00 Fuse rating in A 30 Water connection/drainage Required flow pressure in bar Drain hose [DN] External divery head for drain pump in inches (cm) Dimensions and weight External dimensions, gross height in inches External dimensions, gross width in inches External dimensions, gross depth in inches Dusable space in wash cabinet, width in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm)		
Length of power cord in ft (m) NEMA plug: 5-15 Possible voltage variant 1 Electrical connection Another a traing in kW Total connected load in kW Fuse rating in A Water connection/drainage Required flow pressure in bar Drain hose [DN] Water protection system Dimensions and weight External dimensions, gross height in inches External dimensions, gross depth in inches External dimensions, gross depth in inches Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm)		
NEMA plug: 5-15 Possible voltage variant 1 Electrical connection		
Electrical connection Electrical connection in kW Electrical connected load in kW Electrical connected load in kW Electrical connected load in kW Electrical connection/drainage Required flow pressure in bar Electrical connection/drainage Electrical connection/drainage Required flow pressure in bar Electrical connection/drainage Electrical connection/drainage Electrical connection Electrical connec		3 (1.70)
Electrical connection 2N AC 120/208-240V, 60HZ Heater rating in kW 3.50-3.80 Total connected load in kW 3.70-4.00 Fuse rating in A 30 Water connection/drainage Required flow pressure in bar Drain hose [DN] External dimensions, gross height in inches External dimensions, gross depth in inches External dimensions, gro		
Heater rating in kW 3.50-3.80 Total connected load in kW 3.70-4.00 Fuse rating in A 30 Water connection/drainage Required flow pressure in bar 0.30-10.00 Drain hose [DN] 22 Maximum delivery head for drain pump in inches (cm) 39 3/8 (100) Water protection system Waterproof system Dimensions and weight External dimensions, gross height in inches 26 1/2 (670) External dimensions, gross depth in inches 27 5/8 (700) Usable space in wash cabinet, width in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm)	•	ON AC 100/000 040V
Total connected load in kW 3.70-4.00 Fuse rating in A 30 Water connection/drainage Required flow pressure in bar 0.30-10.00 Drain hose [DN] 22 Maximum delivery head for drain pump in inches (cm) 39 3/8 (100) Water protection system Waterproof system Dimensions and weight External dimensions, gross height in inches 37 7/8 (960) External dimensions, gross width in inches 26 1/2 (670) External dimensions, gross depth in inches 27 5/8 (700) Usable space in wash cabinet, width in inches (mm) 21 3/8 (540) Usable space in wash cabinet, depth of upper basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm)		60HZ
Fuse rating in A Water connection/drainage Required flow pressure in bar Drain hose [DN] Maximum delivery head for drain pump in inches (cm) Water protection system Dimensions and weight External dimensions, gross height in inches External dimensions, gross width in inches External dimensions, gross depth in inches External dimensions, gross depth in inches 26 1/2 (670) External dimensions, gross depth in inches 27 5/8 (700) Usable space in wash cabinet, width in inches (mm) Usable space in wash cabinet, height in inches (mm) Usable space in wash cabinet, depth of upper basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm)		_
Water connection/drainageRequired flow pressure in bar0.30-10.00Drain hose [DN]22Maximum delivery head for drain pump in inches (cm)39 3/8 (100)Water protection systemWaterproof systemDimensions and weight37 7/8 (960)External dimensions, gross height in inches26 1/2 (670)External dimensions, gross width in inches26 1/2 (670)External dimensions, gross depth in inches27 5/8 (700)Usable space in wash cabinet, width in inches (mm)21 3/8 (540)Usable space in wash cabinet, height in inches (mm)20 1/8 (510)Usable space in wash cabinet, depth of upper basket in inches (mm)17 3/4 (450)Usable space in wash cabinet, depth of lower basket in inches (mm)17 3/4 (450)		3.70-4.00
Required flow pressure in bar Drain hose [DN] Maximum delivery head for drain pump in inches (cm) Water protection system Waterproof system Dimensions and weight External dimensions, gross height in inches External dimensions, gross width in inches External dimensions, gross depth in inches 27 5/8 (700) Usable space in wash cabinet, width in inches (mm) Usable space in wash cabinet, height in inches (mm) Usable space in wash cabinet, depth of upper basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm)	Fuse rating in A	30
Drain hose [DN] Maximum delivery head for drain pump in inches (cm) Water protection system Waterproof system Dimensions and weight External dimensions, gross height in inches External dimensions, gross width in inches External dimensions, gross depth in inches External dimensions, gross width in inches External dimensions, gross depth in inches External dimensi	Water connection/drainage	
Maximum delivery head for drain pump in inches (cm) Water protection system Waterproof system Dimensions and weight External dimensions, gross height in inches External dimensions, gross width in inches External dimensions, gross width in inches External dimensions, gross depth	Required flow pressure in bar	0.30-10.00
Water protection system Dimensions and weight External dimensions, gross height in inches External dimensions, gross width in inches External dimensions, gross width in inches External dimensions, gross depth in inches External dimensions, gross depth in inches External dimensions, gross depth in inches Usable space in wash cabinet, width in inches (mm) Usable space in wash cabinet, height in inches (mm) Usable space in wash cabinet, depth of upper basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm)	Drain hose [DN]	22
Dimensions and weight External dimensions, gross height in inches 27 7/8 (960) External dimensions, gross width in inches External dimensions, gross depth in inches 27 5/8 (700) Usable space in wash cabinet, width in inches (mm) Usable space in wash cabinet, height in inches (mm) Usable space in wash cabinet, depth of upper basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm)	Maximum delivery head for drain pump in inches (cm)	39 3/8 (100)
External dimensions, gross height in inches 37 7/8 (960) External dimensions, gross width in inches 26 1/2 (670) External dimensions, gross depth in inches 27 5/8 (700) Usable space in wash cabinet, width in inches (mm) 21 3/8 (540) Usable space in wash cabinet, height in inches (mm) 20 1/8 (510) Usable space in wash cabinet, depth of upper basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm)	Water protection system	Waterproof system
External dimensions, gross width in inches External dimensions, gross depth in inches External dimensions, gross depth in inches Usable space in wash cabinet, width in inches (mm) Usable space in wash cabinet, height in inches (mm) Usable space in wash cabinet, depth of upper basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm)	Dimensions and weight	
External dimensions, gross depth in inches 27 5/8 (700) Usable space in wash cabinet, width in inches (mm) 21 3/8 (540) Usable space in wash cabinet, height in inches (mm) 20 1/8 (510) Usable space in wash cabinet, depth of upper basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) 17 3/4 (450)	External dimensions, gross height in inches	37 7/8 (960)
Usable space in wash cabinet, width in inches (mm) Usable space in wash cabinet, height in inches (mm) Usable space in wash cabinet, depth of upper basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) 17 3/4 (450)	External dimensions, gross width in inches	26 1/2 (670)
Usable space in wash cabinet, width in inches (mm) Usable space in wash cabinet, height in inches (mm) Usable space in wash cabinet, depth of upper basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) 17 3/4 (450)	External dimensions, gross depth in inches	
Usable space in wash cabinet, height in inches (mm) Usable space in wash cabinet, depth of upper basket in inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) 17 3/4 (450) 17 3/4 (450)		
Usable space in wash cabinet, depth of upper basket in inches (mm) 17 3/4 (450) 18 3/4 (450) 19 3/4 (450) 19 3/4 (450)		
inches (mm) Usable space in wash cabinet, depth of lower basket in inches (mm) 17 3/4 (450)	· · · · · · · · · · · · · · · · · · ·	
inches (mm)	inches (mm)	
In-feed height above floor in inches (mm) 8 3/8 (210)	· · · · · · · · · · · · · · · · · · ·	17 3/4 (400)
	In-feed height above floor in inches (mm)	8 3/8 (210)

Depending on site conditions (temperature of incoming water / power connection) values given may vary.



PFD 101 U Built-under dishwasher for large loads of dishware in households, offices and utility areas.



EAN: 4002516366850 / Material number: 11605420 / Old Material Number: 61010102USA

Gross weight in lbs.	113 (51)
Maximum floor loading in N	1000
Emissions data	
Sound power (LwA) in dB(A) re 1 pW	48.0
Programs	
Universal	•
Short	•
SaniWash	•
Cold/Pre-wash	•
Glasses	•
Plastic	•
Intensive	•
Basket design	
ExtraComfort baskets	•
Flexible FlexLine basket design	•
FlexCare glass holder [number]	2
FlexCare cup rack [number]	1
Cutlery basket	•
Height-adjustable upper basket	•
Features	
Commercial-grade electrical connection	•
Wash cabinet made from high-quality stainless steel	•
AutoOpen assisted drying	•
AutoClose	•
EcoFeedback	•
Brilliant GlassCare	•
Child lock	•
Adjustable final rinse temperature	•
Optical interface	•
SmartStart	•
Test certificate	
UL	•