



**BO450611**  
**400 series single oven**  
**Stainless steel-backed full glass door**  
**Width 24" (60 cm)**  
**Right-hinged**  
**controls on top**

**Handleless door / automatic door opening**  
**Pyrolytic self-cleaning**  
**Universal heating system with 13 heating modes, with meat probe and baking stone operation**  
**TFT touch display**  
**Panel-free appliance with surface control module**  
**Electronic precision temperature control from 85° F - 550° F**  
**3.2 cu.ft. net volume**  
**Star-K certified**

**Cooking modes**  
 Convection.  
 Economy convection.  
 Top + bottom heat.  
 Top heat.  
 Bottom heat.  
 Convection+ bottom heat.  
 Convection broiling.  
 Broiling.  
 Economy broiling.  
 Baking stone operation.  
 Roaster operation.  
 Dough proofing.  
 Defrosting.

**Operation**  
 Automatic door opening to the left.  
 Rotary knobs and TFT touch display operation.  
 Clear text display in 25 languages.  
 Option to save individual recipes (incl. meat probe)  
 Information key with use indicators.  
 Side-opening door opens up to 180° angle.

**Features**  
 Meat probe with automatic shut-off.  
 Baking stone outlet.  
 Actual temperature display.  
 Super-quick preheating.  
 Timer functions: cooking time, switch-off time, short-term timer, stopwatch, Sabbath mode.  
 60 W halogen light on top.  
 10 W halogen light on the side.  
 Enamel wire racks on the side with 5 rack levels, pyrolytic-safe.

**Safety**  
 Thermally insulated door with quadruple glazing.  
 Child lock.  
 Safety shut-off.  
 Cooled door housing with temperature protection.

**Cleaning**  
 Pyrolytic self-cleaning.  
 Gaggenau Clean-Enamel.  
 Heated air cleaning catalyst.

**Planning notes**  
 Door hinge not reversible.  
 The front of the appliance extends 1 7/8" from the cabinet front.  
 When handle (optional accessory) is installed, the outer edge of the door handle extends 3 11/16" (94 mm) from the cabinet front.  
 Consider the overhang, incl. the door handle where applicable, when planning to open drawers next to the appliance. Plan a gap of at least 3/16" between the appliance and adjacent cabinets.  
 When planning a corner solution, pay attention to the 90° door opening angle.

**Product Features**  
**Cooking mode**  
 Baking stone function, Bottom heat, Conventional heat, Defrost, Dough proving setting, Full width broil, Half width broil, Hot Air, Hot air and 1/1 bottom heating, Hot air broiling, Hot Air-Eco, Roasting function, Top heat  
**Integrated Cleaning system**  
 Self Clean  
**Interior Lights - primary cavity**  
 2  
**Pull-out system**  
 Accessory  
**Timer settings**  
 Alarm, Off, On, timer  
**Included accessories**  
 1 x enamel baking tray, suit. pyrolytic clean, 1 x grill shelf, 1 x grill tub with grid, 1 x pluggable meat probe  
**Bake Element Wattages primary cavity (W)**  
 1300  
**Broil Element Wattages primary cavity (W)**  
 3000  
**Convection Element Wattages primary cavity (W)**  
 2100  
**Microwave Wattages (W)**  
**Drawer wattage (W)**

**Consumption and connection features**  
**UPC code**  
 825225911180  
**Product color**  
 Stainless steel  
**Alternative colors available**  
**Energy source**  
 Electric  
**Watts (W)**  
 4030  
**Current (A)**  
 17  
**Volts (V)**  
 208/220-240  
**Frequency (Hz)**  
 60  
**Approval certificates**  
 ETL  
**Power Cord Length**  
 39 3/8  
**Plug type**  
 fixed connection  
**Required cutout size (HxWxD) (in)**  
 23 1/4 " x 22 1/16 x 21 11/16 "  
**Product packaging dimensions (HxWxD) (in)**  
 30 11/16 x 26 3/4 x 29 15/16  
**Net weight (lbs)**  
 126  
**Gross weight (lbs)**  
 135  
**2017-09-19**  
 Page 1

To achieve the 21 5/8" installation depth, the connecting cable needs to follow the slanted edge on the lower right hand corner of the housing. The electrical outlet needs to be planned outside the cut-out niche.

**Rating**  
 Total rating 4.0 kW.  
 Total Amps: 17 A.  
 208 / 220 - 240 V / 60 Hz.  
 Connecting cable 39 3/8 without plug (hardwire required).

**Color Variants**  
**BO450611**  
**Stainless steel-backed full glass door**  
**Width 24" (60 cm)**

**Included accessories**  
 1 x enamel baking tray, suit. pyrolytic clean.  
 1 x grill shelf.  
 1 x grill tub with grid.  
 1 x pluggable meat probe.

**Optional accessories**  
**BA026115**  
**Baking tray, enameled**  
**BA056115**  
**Heating element for baking stone and cast-iron roaster**  
**BA056133**  
**Baking stone**  
**BA226105**  
**Broil pan, enameled**  
**BS020002**  
**Pizza peel, additional set of 2**  
**GN340230**  
**Non-stick aluminum cast-iron roaster**

**Installation Accessories**  
**BA476110**  
**Handle bar, stainless steel**

**Product Variants**  
**BO451611**  
**400 series single oven**  
**Stainless steel-backed full glass door**  
**Width 24" (60 cm)**  
**Left-hinged**  
**controls on top**

BO450611  
400 series single oven  
Stainless steel-backed full glass door  
Width 24" (60 cm)  
Right-hinged  
controls on top  
2017-09-19  
Page 2

