SIENA ES

WALL

The Siena ES, certified ENERGY STAR® hood is packed with power. With a 400-CFM blower and ACT™ technology this hood has a versatile range of features perfect for any kitchen. With energy-efficient, warm white

fluorescent lights, an extension duct cover option and Zephyr's new ICON Touch® controls, clearing the air is as simple as the touch of a button.







INTERNAL BLOWER STANDARD		INTERNAL BLOWER with ACT™ AIRFLOW CONTROL TECHNOLOGY™*				
Min Max. CFM	200 - 400	200 - 290				
Min Max. Sones	1.4 - 6	1.4 - 3				


*AIRFLOW CONTROL TECHNOLOGY™ (ACT™) is an exclusive feature built into specific Zephyr hoods which can limit the maximum blower CFM to meet local code requirements.





FRONT





WALL



Stainless Steel Size BLOWER PERFORMANCE Blower CFM (Min Max.) Sones (Min Max.) ACT 290 CFM (Min Max.) FEATURES ENERGY STAR® Certified ACT™ Technology Controls Speed Levels Auto Delay-Off Lighting Dual-Level Lighting Filters Recirculating Option Extension Duct Cover Option DUCT SPECIFICATIONS Vertical Internal Blower AC POWER ZSI-E30AS-ES 30" Z00 - 400 1.4 - 6 200 - 290 FEATURES FICON Touch® Yes ICON Touch® 3* Flourescent, 13\ No Filters Hybrid Baffle x2 No Extension Duct Cover Option 8" Round 8" Round 8" Round or 3-1. 120V, 60Hz at M OPTIONAL ACCESSORIES	36" 200 1.4 - 200 Yes 290 ICO 3* Yes Yes Flou N) - 400 - 6) - 290
Blower CFM (Min Max.) Sones (Min Max.) ACT 290 CFM (Min Max.) FEATURES ENERGY STAR® Certified ACT™ Technology Controls Speed Levels Auto Delay-Off Lighting Dual-Level Lighting Filters Recirculating Option Extension Duct Cover Option DUCT SPECIFICATIONS Vertical Internal Blower Horizontal Internal Blower AC POWER 1.4 - 6 200 - 400 1.4 - 6 200 - 400 1.4 - 6 200 - 400 1.4 - 6 200 - 400 1.4 - 6 200 - 400 1.4 - 6 200 - 400 1.4 - 6 200 - 400 1.4 - 6 200 - 400 1.4 - 6 Yes FILH TO TOUCH® FILIP TOUCH® Flourescent, 130 No Filters Recirculating Option No Extension Duct Cover Option Pes, Up to 12° Company of the properties of the	1.4 - 200 Yes 290 ICO 3* Yes W x2 Flou N	- 6 0 - 290 ON Touch® urescent, 13W x2
Blower CFM (Min Max.) Sones (Min Max.) ACT 290 CFM (Min Max.) FEATURES ENERGY STAR® Certified ACT™ Technology Controls Speed Levels Auto Delay-Off Lighting Dual-Level Lighting Filters Recirculating Option Extension Duct Cover Option DUCT SPECIFICATIONS Vertical Internal Blower Horizontal Internal Blower AC POWER 1.4 - 6 200 - 400 1.4 - 6 200 - 400 1.4 - 6 200 - 400 1.4 - 6 200 - 400 1.4 - 6 200 - 400 1.4 - 6 200 - 400 1.4 - 6 200 - 400 1.4 - 6 200 - 400 1.4 - 6 Yes FILH TO TOUCH® FILIP TOUCH® Flourescent, 130 No Filters Recirculating Option No Extension Duct Cover Option Pes, Up to 12° Company of the properties of the	1.4 - 200 Yes 290 ICO 3* Yes W x2 Flou N	- 6 0 - 290 ON Touch® urescent, 13W x2
Sones (Min Max.) ACT 290 CFM (Min Max.) FEATURES ENERGY STAR® Certified ACT™ Technology Controls Speed Levels Auto Delay-Off Lighting Dual-Level Lighting Filters Recirculating Option Extension Duct Cover Option DUCT SPECIFICATIONS Vertical Internal Blower Horizontal Internal Blower AC POWER 1.4 - 6 200 - 290 1.4 - 6 200 - 290 Yes Yes ICON Touch® Yes Flourescent, 13V No Hybrid Baffle x2 Recirculating Option No Extension Duct Cover Option 8° Round 8° Round 8° Round or 3-1. AC POWER	1.4 - 200 Yes 290 ICO 3* Yes W x2 Flou N	- 6 0 - 290 ON Touch® urescent, 13W x2
ACT 290 CFM (Min Max.) FEATURES ENERGY STAR® Certified ACT™ Technology Controls Speed Levels Auto Delay-Off Lighting Dual-Level Lighting Filters Recirculating Option Extension Duct Cover Option DUCT SPECIFICATIONS Vertical Internal Blower Horizontal Internal Blower AC POWER ACTM (Min Max.) 200 - 290 Yes Hyes AVE APPONT (APPONT APPONT AP	200 Yes 290 ICOI 3* Yes W x2 Flou N	DN Touch® urescent, 13W x2
FEATURES ENERGY STAR® Certified Yes ACT™ Technology 290 Controls ICON Touch® Speed Levels 3* Auto Delay-Off Yes Lighting Flourescent, 13\text{Dual-Level Lighting} No Filters Hybrid Baffle x2\text{Recirculating Option} No Extension Duct Cover Option Yes, Up to 12' Co DUCT SPECIFICATIONS Vertical Internal Blower Horizontal Internal Blower AC POWER 120V, 60Hz at M	Yes 290 ICOI 3* Yes W x2 Flou N	DN Touch® urescent, 13W x2
ENERGY STAR® Certified ACT™ Technology Controls Speed Levels Auto Delay-Off Lighting Dual-Level Lighting Filters Recirculating Option Extension Duct Cover Option DUCT SPECIFICATIONS Vertical Internal Blower Horizontal Internal Blower AC POWER ICON Touch® 9** Horizontal Internal Blower AC POWER Pool Touch® No Filters Flourescent, 13\to No Filters Hybrid Baffle x2 No Yes, Up to 12' Co Section Secti	290 ICOI 3* Yes W x2 Flou N	ON Touch® urescent, 13W x2
ACT™ Technology Controls Speed Levels 3* Auto Delay-Off Lighting Dual-Level Lighting Filters Recirculating Option Extension Duct Cover Option DUCT SPECIFICATIONS Vertical Internal Blower Horizontal Internal Blower AC POWER ICON Touch® 3* No Flourescent, 13\to No Hybrid Baffle x2 No Yes, Up to 12' Co Section Sectio	290 ICOI 3* Yes W x2 Flou N	ON Touch® urescent, 13W x2
Controls ICON Touch® Speed Levels 3* Auto Delay-Off Yes Lighting Flourescent, 13V Dual-Level Lighting No Filters Hybrid Baffle x2 Recirculating Option No Extension Duct Cover Option Yes, Up to 12' Co DUCT SPECIFICATIONS Vertical Internal Blower 8" Round Horizontal Internal Blower 8" Round or 3-1 AC POWER 120V, 60Hz at M	ICO 3* Yes W x2 Flou N	ON Touch® urescent, 13W x2
Controls ICON Touch® Speed Levels 3* Auto Delay-Off Yes Lighting Flourescent, 13V Dual-Level Lighting No Filters Hybrid Baffle x2 Recirculating Option No Extension Duct Cover Option Yes, Up to 12' Co DUCT SPECIFICATIONS Vertical Internal Blower 8" Round Horizontal Internal Blower 8" Round or 3-1 AC POWER 120V, 60Hz at M	3* Yes W x2 Flou N	urescent, 13W x2
Auto Delay-Off Lighting Dual-Level Lighting Filters Recirculating Option Extension Duct Cover Option DUCT SPECIFICATIONS Vertical Internal Blower Horizontal Internal Blower AC POWER Flourescent, 13V No Hybrid Baffle x2 Hybrid Baffle x2 Hybrid Baffle x2 For Hy	Yes N x2 Flou N	
Lighting Flourescent, 13V Dual-Level Lighting No Filters Hybrid Baffle x2 Recirculating Option No Extension Duct Cover Option Yes, Up to 12' Co DUCT SPECIFICATIONS Vertical Internal Blower 8" Round Horizontal Internal Blower 8" Round or 3-1 AC POWER 120V, 60Hz at M	N x2 Flou N	
Dual-Level Lighting Filters Recirculating Option Extension Duct Cover Option DUCT SPECIFICATIONS Vertical Internal Blower Horizontal Internal Blower AC POWER No Hybrid Baffle x2 No Yes, Up to 12' Co 8" Round 8" Round 8" Round or 3-1 120V, 60Hz at M	N	
Filters Hybrid Baffle x2 Recirculating Option No Extension Duct Cover Option Yes, Up to 12' Co DUCT SPECIFICATIONS Vertical Internal Blower 8" Round Horizontal Internal Blower 8" Round or 3-1 AC POWER 120V, 60Hz at M		orid Baffle x2
Recirculating Option Extension Duct Cover Option DUCT SPECIFICATIONS Vertical Internal Blower Horizontal Internal Blower AC POWER No Yes, Up to 12' Co	? Hyb	orid Baffle x2
Extension Duct Cover Option Yes, Up to 12' Co DUCT SPECIFICATIONS Vertical Internal Blower Horizontal Internal Blower AC POWER Yes, Up to 12' Co 8" Round 8" Round 120V, 60Hz at M		
DUCT SPECIFICATIONS Vertical Internal Blower 8" Round Horizontal Internal Blower 8" Round or 3-1. AC POWER 120V, 60Hz at M	No	
Vertical Internal Blower 8" Round Horizontal Internal Blower 8" Round or 3-1. AC POWER 120V, 60Hz at M	eiling Yes,	Up to 12' Ceiling
Horizontal Internal Blower 8" Round or 3-1. AC POWER 120V, 60Hz at M		
AC POWER 120V, 60Hz at M	8" R	Round
	/4" x 10" 8" R	Round or 3-1/4" x 10"
ODTIONAL ACCESSODIES	lax. 1.2A 120V	V, 60Hz at Max. 1.2A
OPTIONAL ACCESSORIES		
Extension Duct Cover Z1C-00SI	Z1C-	:-00SI
Stainless Steel Telescopic Backsplash AK1710	AK17	716
MOUNTING HEIGHT RANGE** 26" - 34"		- 34"
WARRANTY 3 years parts, 1	26"	

CEILING HEIGHT		8'	8.5'	9'	9.5'	10'	10.5'	11'	12'
STANDARD DUCT COVER	Ducted Mounting Height**	26" - 32.5"	26" - 34"	30" - 34"	NA	NA	NA	NA	NA
EXTENSION DUCT COVER	Ducted Mounting Height**	NA	NA	NA	26" - 31.5"	26" - 34"	26" - 34"	26" - 34"	28" - 34"

^{*}When ACT™ is enabled the maximum speed levels will change 3 to 2 speeds.

**Mounting height refers to distance between top of a 36" tall cooking surface and bottom of hood.



Airflow Control Technology™ (ACT™)
is an exclusive feature built into specific Zephyr hoods which can limit the maximum blower CFM to meet local code requirements.

