

Size & Weight

Dimensions (W x H x D)	18.13" x 8.28" x 20.34"
Weight	Approx. 31 lb (14 kg)

Interface

Input and Output Terminals	HDMI (TWO INPUTS)* - Digital RGB/Y Pb/Cb Pr/Cr, IR IN - Minijack, LAN - RJ45, 10Base-T/100BASE-TX, REMOTE - RS-232C, D-sub 9-pin (male), TRIGGER - Minijack, DC 12 V Max. 100 mA, 3D SYNC OUT - Minijack, USB - Type A, DC 5 V, Max. 500 mA *Both HDMI inputs are compatible with HDCP 2.3.
----------------------------	---

Power

Power Consumption	350 W
Power Requirement	AC 100 V to 240 V, 50/60 Hz
Acoustic noise	26 dB *The value depends on the environment or how the projectors are used.

Eco and energy saving

Power Consumption (Standby Mode)	0.3 W (When "Remote Start" is set to "Off")
Power Consumption (Networked Standby Mode)	0.5 W (LAN) (when "Remote Start" is set to "On") When a LAN terminal is not connected, it becomes a low power consumption mode (0.5 W)
Standby Mode Activated	After about 10 Minutes

Accessibility

Screen Reader	Yes
---------------	-----

Display

Display Resolution	720 x 576/50p, 720 x 480/60p, 1280 x 720/50p, 1280 x 720/60p, 1920
--------------------	--

x 1080/50i, 1920 x 1080/60i, 1920 x 1080/24p, 1920 x 1080/50p, 1920 x 1080/60p, 1920 x 1080/120p, 3840 x 2160/24p, 3840 x 2160/25p, 3840 x 2160/30p, 3840 x 2160/50p, 3840 x 2160/60p, 4096 x 2160/24p, 4096 x 2160/25p, 4096 x 2160/30p, 4096 x 2160/50p, 4096 x 2160/60p

Display System 4K SXRD™ panel, projection system

Light source Laser diode

Picture processor X1™ Ultimate for projector

Hardware

Projection lens zoom / focus Powered (Approx. x2.1) / Powered

Operating Conditions

Operating temperature / humidity 41 °F to 95 °F (5 °C to 35 °C) / 20% to 80% (no condensation)

Storage temperature / humidity 14 °F to +140 °F (-10 °C to +60 °C) / 20% to 80% (no condensation)

Video Features

Light Output 2,500 lm

Color Light Output 2,500 lm

General Features

Contrast Ratio ∞: 1 (Dynamic Contrast)

Effective Imager Size 0.61 in x 3

Effective pixels 24,883,200 (3840 x 2160 x 3) pixels

Projection lens shift Powered, Vertical +/- 85%, Horizontal +/- 36%

Throw ratio 1.35:1 to 2.84:1* *Display size: 16:9