

PURESOURCE 3™ ICE AND WATER FILTER SYSTEM
SYSTEM SPECIFICATION AND DATA SHEET

APPLICATION GUIDELINES / CONDITIONS OF USE

Water Supply:	Municipal or Well applications
Water Temp.:	Maximum 100° F (38° C), Minimum 33° F (0.6° C); for cold water use only.
Water Pressure:	100 psi Maximum. Recommended Minimum: 30 psi, as measured at the valve inlet.
<ul style="list-style-type: none"> Timely cartridge replacement is essential for the product to perform as advertised. Please refer to the Use & Care Guide for general operation and maintenance requirements. Your refrigerator will have an electronic light on the freezer door dispenser that lights up yellow or displays "ORDER" when the filter is almost ready for replacement and lights up red or displays "REPLACE" when the filter must be replaced. The indicator button is pressed for approximately 3-10 seconds to reset after replacing the filter cartridge. Please refer to the Use & Care Guide for complete instructions. Flush new cartridge for 4 minutes. PureSource 3™ Ice & Water Filter System should not be used on water that is microbiologically unsafe or with water of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used on disinfected waters that may contain filterable cysts. While testing was performed under standard laboratory conditions, actual performance may vary based on local water conditions and/or pressure. High sediment areas may require more frequent filter cartridge replacement. Spent adsorption media will not be regenerated or used. 	


SYSTEM SPECIFICATIONS

Flow Rate:	Ice Maker - 3.4 to 4.3 oz (99 - 125 cc) per 6.3 seconds at 60 psi (as measured at valve inlet) Dispenser - 60 oz per minute (.5 gpm or 1.9 liters per minute) at 60 psi (as measured at valve inlet)
Capacity:	200 Gallons (757 Liters)
System Construction:	Filter Housing Assembly - Polycarbonate Plastic Water Storage Tank - Polyethylene Plastic Tubing - Polyethylene Plastic Filter Media - Extruded Carbon block

REPLACEMENT CARTRIDGE INFORMATION

Replacement WF3CB cartridges are available through your local Frigidaire dealer or by calling the Customer Assistance Center at 1-800-944-9044. Please reference installation instructions in the Use & Care Guide for replacing the cartridge and warranty information. Estimated cost for the replacement filter cartridge kit: Less than \$40.00.

PERFORMANCE DATA SHEET

MODEL: PureSource 3™	Use the replacement cartridge listed below.
	The PureSource 3™ system with the WF3CB cartridge has been tested according to NSF/ANSI Standard 42/53/401 for the reduction of substances listed below. The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system, as specified in NSF/ANSI Standard 42/53/401.
General test water parameters; pH = 7.5 +/- 0.5 Temp. 20°C +/- 3°C (68°F +/- 5°F) Pressure = 60 psi	

Substance Reduction	NSF Standard	NSF Reduction Requirements	Influent Challenge Concentration	Max. Permissible Product Water Concentration	Average % Reduction
Chlorine taste & odor	42	>/= 50%	2.0 ± 10% mg/L	NA	97.40%
Chlorobenzene	53	N/A	2.0 ± 10% mg/L	0.1 mg/L	99.90%
Cyst	53	99.95%	Min 50,000/L	N/A	99.95%
2,4-D	53	N/A	0.210 ± 10% mg/L	0.07 mg/L	94.50%
Alachlor	53	N/A	0.04 ± 10% mg/L	0.002 mg/L	97.50%
Atrazine	53	N/A	0.009 ± 10% mg/L	0.003 mg/L	94.00%
Lead	53	N/A	0.15 ± 10% mg/L	0.005 mg/L	99.10%
Mercury	53	N/A	0.006 ± 10% mg/L	0.002 mg/L	80.40%
Lindane	53	N/A	0.002 ± 10% mg/L	0.0002 mg/L	99.00%
O-dichlorobenzene	53	N/A	1.8 ± 10% mg/L	0.6 mg/L	99.90%
Toxaphene	53	N/A	0.015 ± 10% mg/L	0.003 mg/L	93.50%
Particulate class I	42	>/= 85%	Min 10,000 particles/ml	>/= 85%	99.90%
Turbidity	53	N/A	11 ± NTU	0.5 NTU	98.50%
Styrene	53	N/A	2.0 ± 10%	0.1 mg/L	99.90%
Tetrachloroethylene	53	N/A	0.015 ± 10%	0.005 mg/L	99.60%



P.O. Box 212378
Augusta, GA 30907
2009 ELECTROLUX HOME PRODUCTS, INC.

State of California
Department of Public Health
Water Treatment Device
Certificate Number
09 - 2025

Date Issued: December 15, 2009

Trademark/Model Designation

PureSource 3

Replacement Elements

WF3CB

Manufacturer: Electrolux

The water treatment device(s) listed on this certificate have met the testing requirements pursuant to Section 116830 of the Health and Safety Code for the following health related contaminants:

Microbiological Contaminants and Turbidity

Cysts
Turbidity

Organic Contaminants

Atrazine
Chlorobenzene
Lindane
o-Dichlorobenzene
Styrene
Tetrachloroethylene
Toxaphene
2,4 D

Inorganic/Radiological Contaminants

Lead
Mercury

Rated Service Capacity: 200 gal

Rated Service Flow: 0.5 gpm

Conditions of Certification:

Do not use where water is microbiologically unsafe or with water of unknown quality, except that systems certified for cyst reduction may be used on disinfected waters that may contain filterable cysts.



This filter is certified by the Water Quality Association to WQA/ASPE/ANSI-803 for sustainability.

Ce filtre est certifié par la Water Quality Association conformément à la norme WQA/ASPE/ANSI-803 pour la durabilité.

Este filtro está certificado por la Water Quality Association según WQA/ASPE/ANSI-803 por sostenibilidad.