

Friedrich ZoneAire® Series
Portable Air Conditioners

SMART. QUIET. COOL.



THE EXPERTS IN ROOM AIR CONDITIONING



SMART HOME READY

SET/ADJUST
SCHEDULES

ADJUST
TEMPS

CONTROL
BY VOICE

ZoneAire® | Smart Portable Air Conditioners

HOME OR AWAY, YOU'RE IN CONTROL WITH THE FRIEDRICHGO™ APP.

Integrated Wi-Fi control from your smartphone. Also compatible with Amazon Alexa or Google Home.

Connect in minutes

It's easy with our simplified set up process

Easily set your home, away, and night time preferences

Create a custom cooling schedule that fits your lifestyle

You're in control anytime, anywhere

Power your unit on and off, change temperature, system mode, and adjust fan speeds no matter where you are

Why FriedrichGo™?

By maintaining even temperatures with centralized controls, you reduce wasted energy and lower utility and maintenance costs while extending the life of your equipment.



CONTROL W/APP
SAVE ENERGY

ZCP08SA, ZCP10SA, ZCP12SA



CONTROL W/APP
SAVE ENERGY

ZCP12DB, ZHP14DB

Dual Hose Portables

Intake & exhaust hoses provide up to 40% faster cooling.

Control Features

- ✔ Built-in Wi-Fi control on the go with the FriedrichGo app
- ✔ Smart home / voice command device compatibility (Amazon Alexa and Google Home)

Comfort & Convenience

- 3-IN-1 SYSTEM: Air conditioner, dehumidifier and fan
- 4-IN-1 SYSTEM: Air conditioner, heater (heat pump), dehumidifier and fan (ZHP14DB)
- Auto swing air louvers for even air distribution
- Self-evaporative condensate system - no bucket to empty
- Condensate overflow protection- the unit will automatically shut off if tank should become full
- LCD remote control
- 3-speed fan
- Easy-access, washable antimicrobial filters
- Auto restart after power outage
- Built-in drain pump to remove condensate in heat pump mode (ZHP14DB)
- Removes up to 72 pts./day when used as a dehumidifier
- ✔ R-32 refrigerant with low Global Warming Potential

ZoneAire® Installation Features

- Quick installation - Snap-in hoses and 115v operation mean quick start-up and cooling
- Easy-roll casters for portability
- Small footprint - only 17" wide
- All installation accessories included
- 6 ft. long power cord



Single Hose Portables

Small and compact for fast setup and easy storage.

Control Features

- ✔ Built-in Wi-Fi control on the go with the FriedrichGo app
- ✔ Smart home / voice command device compatibility (Amazon Alexa and Google Home)

Comfort & Convenience

- 3-in-1 system: Air conditioner, dehumidifier and fan
- Auto-swing louvers for even air distribution
- Easy-access, washable antimicrobial filters
- 3-speed fan with Auto setting that maintains your ideal temperature
- Auto restart after power outage
- LCD remote control
- ✔ Sleep setting increases temperature 2 degrees every 4 hours
- ✔ R-32 refrigerant with low Global Warming Potential

ZoneAire® Compact Installation Features

- Quick installation - Snap-in hoses and 115v operation mean quick start-up and cooling
- Easy-roll casters for portability
- All installation accessories included
- Window kit fits vertical and horizontal standard windows up to 50 inches
- Window kit extension to allow installation in sliding patio doors up to 87 inches
- Includes gravity drain hose for continuous drainage option during dehumidification mode
- Small footprint takes up minimal space- only 16 1/2" wide
- 5 ft. long power cord





A perfect way to cool that new home office space

Quickly set up supplemental or emergency cooling in computer rooms and server rooms

Fast and Easy Setup In These Applications

- Supplemental or emergency cooling or heating anywhere
- Home offices
- Computer rooms
- Guard buildings
- Construction trailers/RVs
- Workshops and garages
- Dorm rooms
- Bedrooms, attics and basements
- Sunrooms/ enclosed patios



Friedrich Air Conditioning Co. | 10001 Reunion Place, Suite 500 | San Antonio, TX 78216 | 877.599.5665 | www.friedrich.com



Friedrich ZoneAire® Series Portable Air Conditioners



ZCP08SA, ZCP10SA, ZCP12SA



ZCP12DB, ZHP14DB

COOL ONLY

Single Hose
8,500, 10,000 and 13,000 Btu

Dual Hose
11,000 and 12,000 Btu

EFFICIENCY: EERs up to 10.4

HEAT PUMP

115 volt

Dual Hose
13,000 Btu COOLING
9,500 Btu HEATING

EFFICIENCY: EERs up to 10.6

FEATURES

- Built-in Wi-Fi control on the go with the *FriedrichGo™* app
- Smart home / voice command device compatibility (Amazon Alexa and Google Home)
- 3-IN-1 SYSTEM: Air conditioner, dehumidifier and fan
- 4-IN-1 SYSTEM: Air conditioner, heater (heat pump), dehumidifier and fan (ZHP14DB)
- Auto swing air louvers for even air distribution
- Self-evaporative condensate system - no bucket to empty
- Condensate overflow protection- the unit will automatically shut off if tank should become full
- LCD remote control
- 3-speed fan
- Easy-access, washable antimicrobial filters
- Auto restart after power outage
- Built-in drain pump to remove condensate in heat pump mode (ZHP14DB)
- Removes up to 72 pts./day when used as a dehumidifier
- Quick installation - Snap-in hoses and 115v operation mean quick start-up and cooling
- Easy-roll casters for portability
- Small footprint: Dual hose - 17" wide
Single hose - 16.5" wide
- All installation accessories included
- Power cord: Dual hose - 6 ft. Single hose - 5 ft.



SPECIFICATIONS

| Model | | SINGLE HOSE | | | | | | DUAL HOSE | | | |
|---------------------|----------|--------------------------|------------|--------------|------------|--------------------------|------------|--------------------------|------------|--------------|------------|
| | | ZCP08SA | | ZCP10SA | | ZCP12SA | | ZCP12DB | | ZHP14DB | |
| UPC | | 724587440164 | | 724587440171 | | 724587440188 | | 724587440034 | | 724587440041 | |
| | | SACC | ASHRAE 128 | SACC | ASHRAE 128 | SACC | ASHRAE 128 | SACC | ASHRAE 128 | SACC | ASHRAE 128 |
| Cooling | BTUh | 5000 | 8500 | 6000 | 10000 | 8000 | 13000 | 7500 | 11000 | 8300 | 12000 |
| Heating | BTUh | — | | — | | — | | — | | 9500 | 9500 |
| Volts Rated | | 115v | | 115v | | 115v | | 115v | | 115v | |
| Cooling | Amps | 6.6 | | 7.9 | | 9.2 | | 10.5 | | 10.5 | |
| Cooling | Watts | 760 | | 890 | | 1060 | | 1160 | | 1160 | |
| Cooling | EER | 9.5 | | 10.2 | | 10.4 | | 9.6 | | 10.6 | |
| Cooling | CEER | 6.1 | | 6.51 | | 7.22 | | 7.1 | | 7.4 | |
| Heating | COP | — | | — | | — | | — | | 9.3 | |
| Moisture Removal | Pts./Hr. | 2.11 | | 2.63 | | 3.46 | | 3.5 | | 3.8 | |
| Model | CFM | 188/171/153 | | 188/171/153 | | 212/184/165 | | 252 | 240 | 252 | 260 |
| Model Dim W x H x D | | 16 1/2 x 27 5/8 x 12 5/8 | | | | 17 1/8 x 28 1/3 x 14 1/4 | | 17 1/8 x 28 3/8 x 14 1/4 | | | |
| Net Wt | Lbs. | 52.8 | | 53.9 | | 65.48 | | 64.2 | 64.2 | 64.2 | 64.2 |
| Ship Wt | Lbs. | 64.24 | | 65.34 | | 75.24 | | 72 | 72 | 88 | 88 |
| Coverage | Sq. Ft. | Up to 200 | | Up to 300 | | Up to 400 | | Up to 400 | | Up to 500 | |
| Carton W x H x D | | 19 x 35 x 14 1/8 | | | | 19 x 35 x 14 1/8 | | 19 x 35 x 17 | | | |
| Hose Length | | 5 ft. | | 5 ft. | | 5 ft. | | 5 ft. | | 5 ft. | |
| Hose Diameter | | 6 in. | | 6 in. | | 6 in. | | 6 in. | | 6 in. | |
| Cord Length | | 5 ft. | | 5 ft. | | 5 ft. | | 6 ft. | | 6 ft. | |

BTU calculations for ASHRAE 128 and SACC capacities are based on different test procedures where the BTU ratings are calculated differently. While the BTU's may be lower on the SACC rating, the actual cooling capacity of the air conditioners are the same.

NOTE: Air conditioners will provide cooling at outdoor temperatures down to 41°F and heat pump will provide heating at outdoor temperatures down to 14°F with single hose installation


NOTE: Air conditioners will provide cooling at outdoor temperatures down to 41°F and ZHP14DB heat pump will provide heating at outdoor temperatures down to 14°F with single hose installation.

*SACC is the Seasonally Adjusted Cooling Capacity measured in BTU/Hr. The Department of Energy requires portable air conditioners to be tested in accordance with title 10 Code of Federal Regulations (CFR) 430, subpart B, appendix CC and applicable sampling plans.

*ASHRAE 128 was the federal testing requirement for manufactures prior to 2017.

Due to continuing research in new energy-saving technology, specifications are subject to change without notice

CIRCUIT RATING / BREAKER / PLUG FACE

| Model | Circuit Rating Breaker or T-D Fuse | Plug Face (NEMA#) | Wall Outlet Appearance |
|---------------------------|--|----------------------|---|
| ZCP08SA, ZCP10SA, ZCP12SA | 125V - 15A | 5 - 15P |  |
| ZCP12DB, ZHP14DB | 125V - 15A | 5 - 15P | |



Friedrich Air Conditioning Co. | www.friedrich.com