

3-speed high performance blower featuring 550 CFM, HVI certified*, offering 1.5 sones level at minimum speed.

Two ultra efficient hybrid baffle filters, easy to clean, for optimal grease removal.

Two built-in LED modules provide an even lighting over the cookton

Telescopic chimney for 8' to 9'

Optional flue extension available for 10' ceiling.

Model Numbers:

WCP3I30SB WCP3I36S



Hybrid baffle filters provide ultra-efficient grease removal with superior air flow.



Tap-touch control features easy-to-clean surface.



Two-level LED modules evenly illuminate cooktop.

Hood Sizes

Width	30", 36"	
Depth	20"	
Finish		
Stocked	Brushed Stainless Steel	
Special Order	NA	
Features		
Lighting Type	LED Modules (450 Lumens each, 4.5 watts per module, color temp 3000K)	
Number of Modules	2	
Lighting Levels	2	
Lighting Modules Included	Yes	
Control Type	3-speed Tap Touch	

Hood Blower Included

Non-ducted Capability

Internal		
Blower CFM Low/High	200/550	
Sones Low/High	1.5/11.0	

Yes

Heat Sentry™, Filter Clean Reminder

Hybrid Baffle Filter

Accessories

Control Features

Remote Control

Filter Type

10' Flue Extension (Ducted)

Recirculation Kit

Non-Duct Filter

CFM Reducer Kit

AEWCP3SB

HRKBSS

HRKBSS

FILTERECB


ARP6, ARP310

Installation Requirements

Amps @ 120V: Internal Blower 3.9 Electrical Connection Plug In

 $\begin{array}{ll} \mbox{Duct Size: Internal Blower} & \mbox{6" round, 3-1/4"} \times \mbox{10"} \\ \mbox{Duct Direction} & \mbox{6" V, 3-1/4"} \times \mbox{14" V and H} \end{array}$

Backdraft Damper Included



Install hood so that the bottom of the unit is 24" to 30" above the cooking surface. Mounting height may be affected by ceiling height.

Ducted telescopic flue accommodates celling heights from 8' to 9'. Flue extension for higher ceilings is also available.

*299 CFM max with ARP6 or ARP10 reducer plate option

For more details see the product specifications sheet found at www.BESTRangeHoods.com



