



763 Station



	US Units	Metric Units
Style Number	5M208	
Construction	Light Commercial Luxury Vinyl Tile	
Profile	Direct Glue	
Size	6" x 48"	15.24 cm x 121.92 cm
Overall Thickness	0.079"	2 mm
Wear Layer Thickness	12 mil (0.012")	0.3 mm
Finish	Opticlean Urethane	
Edge Description	Square	
Area per Carton	53.93 sq ft	5.01 sq m
Area per Pallet	2588.64 sq ft	240.49 sq m
Installation	Glue	
Installation Grade	Above, On, Below	
Ortho-Phthalates Free	Yes	
FloorScore Certified	Yes	
Residential Warranty	<a href="#">Residential Resilient Limited Warranty - Defects, Wear</a> 25 Years <a href="#">Residential Resilient LVP/LVT Products Limited Warranty</a>	
Commercial Warranty	7 Year Commercial	
Smoke Density (ASTM E662, Flaming Mode)	<a href="#">Passes, &lt;450</a>	
Radiant Panel (ASTM E648)	<a href="#">Passes, Class I</a>	

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Features

Metropolis makes a fabulous first impression with the desirable look of rustic, reclaimed barnwood. Its styling reflects 10 gorgeous wood species in current colors, creating design choices that range from contemporary to traditional.


Colors



Suggested Adhesive

Style Name	Style Number
SHAW 200 1 GAL	052VS
KWIKFLASH 4 GAL	080VS
KWIKFLASH LV 1	081VS
S150 SPRAY ADHS	069VS
SHAW 200 TPS 4G	026VS

Coordinating Trim



Multi-Purpose Reducer  
VSUN1 | 94"




Quarter Round  
VSQT1 | 94"



Flush Stairnose  
VSSN1 | 94"

Coordinating Metal Trim



Finish	Reducer	T-Mold	Stair Cap
Satin Silver	152SA	155SA	149SA
Satin Nickel	153SA	156SA	150SA
Dark Bronze	154SA	157SA	151SA

Installation Range

Profile Size	Installation Range
3.5mm	1.5mm to 3.5mm heights
5.5mm	3.6mm to 5.5mm heights
8mm	6mm to 8mm heights

