

**APPEARANCE**

|                         |      |
|-------------------------|------|
| <b>Color Appearance</b> | Gray |
|-------------------------|------|

**CAPACITY**

|                      |            |
|----------------------|------------|
| <b>Unit Capacity</b> | 18 Gallons |
|----------------------|------------|

**FEATURES**

|                                      |                                |
|--------------------------------------|--------------------------------|
| <b>Anode Rod</b>                     | Aluminum                       |
| <b>Configuration</b>                 | Lowboy                         |
| <b>Control Type</b>                  | Thermostat                     |
| <b>Controls</b>                      | Mechanical Temperature Control |
| <b>Drain Valve Type</b>              | Plastic                        |
| <b>Family Size</b>                   | 1-2 People                     |
| <b>Foam Insulation</b>               | Yes                            |
| <b>Fuel Type</b>                     | Electric                       |
| <b>GPH Recovery @ 90 Degrees F</b>   | 25.1                           |
| <b>Heating Element</b>               | Stainless steel                |
| <b>Height Description</b>            | Low Boy with Side Port         |
| <b>Installation Location</b>         | Indoor                         |
| <b>Max. operating pressure (psi)</b> | 150                            |
| <b>Max: operating pressure (psi)</b> | 150                            |
| <b>Mobile Home</b>                   | No                             |

|  |                     |
|--|---------------------|
| <b>Compatible</b>                          |                     |
| <b>Operating Modes</b>                     | Standard Electric   |
| <b>Point of Use</b>                        | No                  |
| <b>Product Type</b>                        | Electric Thermostat |
| <b>Rated Capacity</b>                      | 18.0 gal            |
| <b>Rated Storage Capacity</b>              | 18                  |
| <b>Temp &amp; Pressure Relief Valve</b>    | Yes                 |
| <b>Temperature Setting</b>                 | 90-150° F Range     |
| <b>Temperature Setting Factory Default</b> | 120° F              |
| <b>Water Connection Location</b>           | Side                |

## POWER / RATINGS

|  |                                       |
|--|---------------------------------------|
| <b>Electrical Circuit Required</b>       | 208V/240V 60 Hz Dedicated 30 Amp Min. |
| <b>Electrical Connection</b>             | Direct-Wire                           |
| <b>Heating - Electric - Heater Watts</b> | 3800                                  |
| <b>Operating Water Pressure</b>          | 20-125 PSI                            |
| <b>Voltage (MAX)</b>                     | 240 V                                 |
| <b>Volts/Hertz</b>                       | 240V; 60Hz                            |

## WARRANTY

|                       |                |
|-----------------------|----------------|
| <b>Labor Warranty</b> | 1-year limited |
|-----------------------|----------------|

|                       |                                       |
|-----------------------|---------------------------------------|
| <b>Parts Warranty</b> | 8-year limited                        |
| <b>Warranty Notes</b> | See written warranty for full details |

## WEIGHTS & DIMENSIONS

|  |                   |
|--|-------------------|
| <b>Approximate Shipping Weight</b>                               | 62 lb             |
| <b>Connection Sizes - Hot Water Outlet (MNPT)</b>                | 3/4"              |
| <b>Connection Sizes - Water Inlet (MNPT)</b>                     | 3/4"              |
| <b>Net Weight</b>  | 54.2 lb           |
| <b>Overall Depth</b>   | 19 1/4 in         |
| <b>Overall Height</b>  | 25 3/4 in         |
| <b>Overall Width</b>   | 19 1/4 in         |
| <b>Product Diameter</b>  | 19 1/4 in         |
| <b>Product Height (to top of unit)</b>                           | 25 3/4 in         |
| <b>Product Height (to top of water inlet/outlet connections)</b> | 8 7/8 : 17 1/8 in |