

APPEARANCE

Color Appearance	Diamond Gray
Installation	Wall Mounted

FEATURES

Activation Flowrate (GPM)	≤ 0.5
Cold/hot water connections (inches)	3/4" Cold Water Inlet; 3/4" Hot Water Outlet
Configuration	Space Saver
Controls	Adjust degree Fahrenheit/Celsius Adjustable Temperature Digital Electronic Control
Flowrate (GPM) @ 37 F inlet	3
Flowrate (GPM) @ 42 F inlet	3.29
Flowrate (GPM) @ 47 F inlet	3.4
Flowrate (GPM) @ 52 F inlet	3.79
Flowrate (GPM) @ 57 F inlet	4.19
Flowrate (GPM) @ 62 F inlet	4.4
Flowrate (GPM) @ 67 F inlet	5.09
Flowrate (GPM) @ 72 F inlet	5.4
Flowrate (GPM) @ 77 F inlet	6.19

Fuel Type	Electric
Installation Location	Indoor
Integrated Safety Devices	Flow sensor¶High limit thermostat (on each heating element)¶Inlet Temperature Sensor¶Material Rated for Ignition Containment¶Outlet Temperature Sensor
Max. operating pressure (psi)	150
Max: operating pressure (psi)	150
Maximum Outlet Temperature (F)	140
Min. operating pressure (psi)	25
Point of Use	Whole Home
Product Type	Electric Tankless
Temperature adjustment amount (degree)	1
Temperature Setting	86-140° F Range
Temperature Setting Factory Default	105° F
Uniform Energy Factor (UEF)	>0.91
Water Connection Location	Bottom

POWER / RATINGS

Amps	112.5
Electrical Circuit Required	40 Amp (x3)
Power Rating-kW	27

Voltage (MAX)	240 V
----------------------	-------

WARRANTY

Parts Warranty	5-year Limited Replacement Warranty
-----------------------	-------------------------------------

WEIGHTS & DIMENSIONS

Approximate Shipping Weight	15.2 lb
Net Weight	14.09 lb
Overall Depth	3.70 in
Overall Height	15.20 in
Overall Width	10.20 in
Product Diameter	10.200 in
Product Height (to top of unit)	15.200 in