

## CVA 6401

## Built-in coffee machine with bean-to cup system and OneTouch for Two prep. for perfect coffee enjoyment.



- Perfect results and intense coffee flavor AromaticSystem
- Fully automatic perfection -OneTouch for Two
- Innovative and convenient milk system EasyClick milk system
- Convenient cleaning for care and mainten. Cleaning programs
- Patented door system with fully opening front - ComfortDoor

EAN: 4002515464052 / material number: 09869070

Construction type and design	
Built-in bean-to-cup coffee machine	•
PureLine	•
Color	Brilliant white
ContourLine	•
Consumer benefits	
AromaticSystem	•
OneTouch preparation	•
One Touch and OneTouch for Two	•
Programmable user profile	10
Grinding grade selectable	•
Additional coffee types in ground coffee form possible	•
Ground quantity programmable	•
Water quantity programmable	•
Water temperature programmable	•
Amount of milk can be programmed	•
Amount of milk froth can be programmed	•
Pre-brewing programmable	•
Beverage specialities	
Espresso, single	•
Espresso, double	•
Coffee, single	•
Coffee, double	•
Long coffee, single	•
Long coffee, double	•
Cappuccino, single	•
Cappuccino, double	•
Latte macchiato, single	•
Latte macchiato, double	•
Hot milk, single	•
Hot milk, double	•
Milk froth, single	•
Milk froth, double	•
Caffè latte, single	•
Caffè latte, double	•
Hot water, single	•
Coffee pot	•

More information at www.MieleUSA.com



## CVA 6401

Built-in coffee machine

with bean-to cup system and OneTouch for Two prep. for perfect coffee enjoyment.



Control panel	
Control panel	DirectSensor
Height adjustment of infinitely adjustable central spout in	3 3/8 (8)
_in.(cm) ComfortDoor	•
Hidden door handle	
MultiLingua	
	17.64 (500)
Bean container capacity, total in oz (g)	17.64 (500)
Capacity of water container in fl oz (l)	<u>77.77 (2.3)</u> 15
Capacity of waste container in capsules	•
Easily accessible containers	-
Time-of-day display	
Date display	
Programmable switch-on time	•
Programmable switch-off time	•
Programmable stand-by time	•
Clock battery backup in h	150
Efficiency and sustainability	
Energy-saving Eco mode option	•
Cleaning convenience Automatic rinsing of the milk pipework from the water	
container	•
Convenient cleaning programs	•
Auto-Off function	•
ComfortClean	•
Removable milk pipework	•
Removable brew unit	•
Adjustable water hardness	•
Safety	
System lock	•
Technical data	
Appliance width in in.(mm)	23 1/2 (595)
Applicance height in in.(mm)	17 7/8 (452)
Appliance depth in in.(mm)	19 (480)
Depth with door open in in.(cm)	41 3/4 (106.0)
Total connected load in kW	1.5
Voltage in V	120
Voltage in V Fuse rating in A	
	120
Fuse rating in A	120 15
Fuse rating in A Number of phases	120 15 1
Fuse rating in A Number of phases Length of electrical wire in ft (m)	120 15 1
Fuse rating in A Number of phases Length of electrical wire in ft (m) Standard accessories	120 15 1
Fuse rating in A   Number of phases   Length of electrical wire in ft (m)   Standard accessories   Glass milk container	120 15 1
Fuse rating in A   Number of phases   Length of electrical wire in ft (m)   Standard accessories   Glass milk container   Descaling tablets	120   15   1   5 (1.8)   •   •
Fuse rating in A   Number of phases   Length of electrical wire in ft (m)   Standard accessories   Glass milk container   Descaling tablets   Cleaning tablets	120   15   1   5 (1.8)   •   •
Fuse rating in A   Number of phases   Length of electrical wire in ft (m)   Standard accessories   Glass milk container   Descaling tablets   Cleaning tablets   Milk pipework cleaner	120   15   1   5 (1.8)   •   •