Custom Installation CCM662




See nothing, hear everything

The CCM662 is a true high performance ceiling-mount speaker. The tweeter has a 25mm(1in) aluminium dome tweeter and its housing pivots for adjustable off-axis treble response. The die-cast chassis of the bass/ midrange driver provides extra rigidity which results in a cleaner, faster bass and a three-position EQ switch offers a better off-axis response. With superior cross-over components along with gold plated terminals the CCM662 has an impressive maximum amp power of 150W. Its blue Kevlar[®] cone means that the unit is well hidden behind the grille but still produces a remarkably clear and dynamic sound. Incorporating QuickDogs™ and plug-and-play functionality it is quick and easy to install.

Technical Specifications

Description	2-way in-ceiling system
Drive Units	1x ø25mm (1in) Nautilus™ swirl loaded aluminium dome tweeter 1x ø150mm (6in) blue Kevlar® cone bass/midrange
Frequency Range (-6dB)	45Hz – 50kHz
Recommended Amp Power	25 – 150w
Sensitivity SPL (2.83V, 1m)	88dB
Impedance Nominal (min)	8Ω (4.5Ω)
Frame diameter	240mm (9.5in)
Cut-out diameter	202mm (8in)
Depth behind surface	133mm (5.2in)
Protrusion	4mm (0.2in)
Pre-mount Kit	C6
Back Box	6C





Bowers & Wilkins

www.bowers-wilkins.com

Nautilus and QuickDogs are trademarks of B&W Group Ltd. Kevlar is a registered trademark of DuPont. Copyright © B&W Group Ltd. E&OE

