

Monitor Section

Picture size	6.75 inches(diagonal) wide
W x H	151.8 mm x 79.68 mm, 5-31/32 x 3-1/8 inch
Display system	TN LCD panel
Drive system	TFT active matrix system
Number of pixels	1,152,000 800H x 480V x RGB
Effective pixels	99.99%
Pixel arrangement	RGB striped arrangement
Back lighting	LED

USB I/F Section

USB Standard	USB2.0 High Speed	
File System	FAT 16/32, exFAT, NTFS	
Maximum Power Supply Current	DC5V=1.5A	
D/A Converter	24/32Bit	
Audio Decoder	MP3 / WMA / AAC / WAV / FLAC / Vorbis	
Video Decoder	MPEG1/2,MPEG4 / WMV / H.264 / MKV	
Frequency response	192k Sampling	20 - 88,000 Hz
	96k Sampling	20 - 44,000 Hz
	48k Sampling	20 - 22,000 Hz
	44.1k Sampling	20 - 20,000 Hz
Total harmonic distortion 1kHz	0.0001%	
Signal to Noise ratio	98.5dB	
Dynamic range	89dB	

SD Section

SD Standard	SD / SDHC / SDXC
Compatible File System	FAT 16/32, exFAT, NTFS
Capacity	Maximum 2T Byte
Data Transfer Rate	Maximum 25MB/sec
Audio Decoder	MP3 / WMA / AAC / WAV / FLAC / Vorbis
Video Decoder	MPEG1/2,MPEG4 / WMV / H.264 / MKV

Bluetooth Section

Technology	Bluetooth Ver5.0
Frequency	2.402 – 2.480 GHz
RF Output Power (E.I.R.P.)	+4dBm (MAX), Power Class 2

Monitor Section

Picture size	6.75 inches(diagonal) wide
W x H	151.8 mm x 79.68 mm, 5-31/32 x 3-1/8 inch
Display system	TN LCD panel
Drive system	TFT active matrix system
Number of pixels	1,152,000 800H x 480V x RGB
Effective pixels	99.99%
Pixel arrangement	RGB striped arrangement
Back lighting	LED

USB I/F Section

USB Standard	USB2.0 High Speed	
File System	FAT 16/32, exFAT, NTFS	
Maximum Power Supply Current	DC5V=1.5A	
D/A Converter	24/32Bit	
Audio Decoder	MP3 / WMA / AAC / WAV / FLAC / Vorbis	
Video Decoder	MPEG1/2,MPEG4 / WMV / H.264 / MKV	
Frequency response	192k Sampling	20 - 88,000 Hz
	96k Sampling	20 - 44,000 Hz
	48k Sampling	20 - 22,000 Hz
	44.1k Sampling	20 - 20,000 Hz
Total harmonic distortion 1kHz	0.0001%	
Signal to Noise ratio	98.5dB	
Dynamic range	89dB	

SD Section

SD Standard	SD / SDHC / SDXC
Compatible File System	FAT 16/32, exFAT, NTFS
Capacity	Maximum 2T Byte
Data Transfer Rate	Maximum 25MB/sec
Audio Decoder	MP3 / WMA / AAC / WAV / FLAC / Vorbis
Video Decoder	MPEG1/2,MPEG4 / WMV / H.264 / MKV

Bluetooth Section

Technology	Bluetooth Ver5.0
Frequency	2.402 – 2.480 GHz
RF Output Power (E.I.R.P.)	+4dBm (MAX), Power Class 2

Monitor Section

Picture size	6.75 inches(diagonal) wide
W x H	151.8 mm x 79.68 mm, 5-31/32 x 3-1/8 inch
Display system	TN LCD panel
Drive system	TFT active matrix system
Number of pixels	1,152,000 800H x 480V x RGB
Effective pixels	99.99%
Pixel arrangement	RGB striped arrangement
Back lighting	LED

USB I/F Section

USB Standard	USB2.0 High Speed	
File System	FAT 16/32, exFAT, NTFS	
Maximum Power Supply Current	DC5V=1.5A	
D/A Converter	24/32Bit	
Audio Decoder	MP3 / WMA / AAC / WAV / FLAC / Vorbis	
Video Decoder	MPEG1/2,MPEG4 / WMV / H.264 / MKV	
Frequency response	192k Sampling	20 - 88,000 Hz
	96k Sampling	20 - 44,000 Hz
	48k Sampling	20 - 22,000 Hz
	44.1k Sampling	20 - 20,000 Hz
Total harmonic distortion 1kHz	0.0001%	
Signal to Noise ratio	98.5dB	
Dynamic range	89dB	

SD Section

SD Standard	SD / SDHC / SDXC
Compatible File System	FAT 16/32, exFAT, NTFS
Capacity	Maximum 2T Byte
Data Transfer Rate	Maximum 25MB/sec
Audio Decoder	MP3 / WMA / AAC / WAV / FLAC / Vorbis
Video Decoder	MPEG1/2,MPEG4 / WMV / H.264 / MKV

Bluetooth Section

Technology	Bluetooth Ver5.0
Frequency	2.402 – 2.480 GHz
RF Output Power (E.I.R.P.)	+4dBm (MAX), Power Class 2

Monitor Section

Picture size	6.75 inches(diagonal) wide
W x H	151.8 mm x 79.68 mm, 5-31/32 x 3-1/8 inch
Display system	TN LCD panel
Drive system	TFT active matrix system
Number of pixels	1,152,000 800H x 480V x RGB
Effective pixels	99.99%
Pixel arrangement	RGB striped arrangement
Back lighting	LED

USB I/F Section

USB Standard	USB2.0 High Speed	
File System	FAT 16/32, exFAT, NTFS	
Maximum Power Supply Current	DC5V=1.5A	
D/A Converter	24/32Bit	
Audio Decoder	MP3 / WMA / AAC / WAV / FLAC / Vorbis	
Video Decoder	MPEG1/2,MPEG4 / WMV / H.264 / MKV	
Frequency response	192k Sampling	20 - 88,000 Hz
	96k Sampling	20 - 44,000 Hz
	48k Sampling	20 - 22,000 Hz
	44.1k Sampling	20 - 20,000 Hz
Total harmonic distortion 1kHz	0.0001%	
Signal to Noise ratio	98.5dB	
Dynamic range	89dB	

SD Section

SD Standard	SD / SDHC / SDXC
Compatible File System	FAT 16/32, exFAT, NTFS
Capacity	Maximum 2T Byte
Data Transfer Rate	Maximum 25MB/sec
Audio Decoder	MP3 / WMA / AAC / WAV / FLAC / Vorbis
Video Decoder	MPEG1/2,MPEG4 / WMV / H.264 / MKV

Bluetooth Section

Technology	Bluetooth Ver5.0
Frequency	2.402 – 2.480 GHz
RF Output Power (E.I.R.P.)	+4dBm (MAX), Power Class 2

Monitor Section

Picture size	6.75 inches(diagonal) wide
W x H	151.8 mm x 79.68 mm, 5-31/32 x 3-1/8 inch
Display system	TN LCD panel
Drive system	TFT active matrix system
Number of pixels	1,152,000 800H x 480V x RGB
Effective pixels	99.99%
Pixel arrangement	RGB striped arrangement
Back lighting	LED

USB I/F Section

USB Standard	USB2.0 High Speed	
File System	FAT 16/32, exFAT, NTFS	
Maximum Power Supply Current	DC5V=1.5A	
D/A Converter	24/32Bit	
Audio Decoder	MP3 / WMA / AAC / WAV / FLAC / Vorbis	
Video Decoder	MPEG1/2,MPEG4 / WMV / H.264 / MKV	
Frequency response	192k Sampling	20 - 88,000 Hz
	96k Sampling	20 - 44,000 Hz
	48k Sampling	20 - 22,000 Hz
	44.1k Sampling	20 - 20,000 Hz
Total harmonic distortion 1kHz	0.0001%	
Signal to Noise ratio	98.5dB	
Dynamic range	89dB	

SD Section

SD Standard	SD / SDHC / SDXC
Compatible File System	FAT 16/32, exFAT, NTFS
Capacity	Maximum 2T Byte
Data Transfer Rate	Maximum 25MB/sec
Audio Decoder	MP3 / WMA / AAC / WAV / FLAC / Vorbis
Video Decoder	MPEG1/2,MPEG4 / WMV / H.264 / MKV

Bluetooth Section

Technology	Bluetooth Ver5.0
Frequency	2.402 – 2.480 GHz
RF Output Power (E.I.R.P.)	+4dBm (MAX), Power Class 2

Monitor Section

Picture size	6.75 inches(diagonal) wide
W x H	151.8 mm x 79.68 mm, 5-31/32 x 3-1/8 inch
Display system	TN LCD panel
Drive system	TFT active matrix system
Number of pixels	1,152,000 800H x 480V x RGB
Effective pixels	99.99%
Pixel arrangement	RGB striped arrangement
Back lighting	LED

USB I/F Section

USB Standard	USB2.0 High Speed	
File System	FAT 16/32, exFAT, NTFS	
Maximum Power Supply Current	DC5V=1.5A	
D/A Converter	24/32Bit	
Audio Decoder	MP3 / WMA / AAC / WAV / FLAC / Vorbis	
Video Decoder	MPEG1/2,MPEG4 / WMV / H.264 / MKV	
Frequency response	192k Sampling	20 - 88,000 Hz
	96k Sampling	20 - 44,000 Hz
	48k Sampling	20 - 22,000 Hz
	44.1k Sampling	20 - 20,000 Hz
Total harmonic distortion 1kHz	0.0001%	
Signal to Noise ratio	98.5dB	
Dynamic range	89dB	

SD Section

SD Standard	SD / SDHC / SDXC
Compatible File System	FAT 16/32, exFAT, NTFS
Capacity	Maximum 2T Byte
Data Transfer Rate	Maximum 25MB/sec
Audio Decoder	MP3 / WMA / AAC / WAV / FLAC / Vorbis
Video Decoder	MPEG1/2,MPEG4 / WMV / H.264 / MKV

Bluetooth Section

Technology	Bluetooth Ver5.0
Frequency	2.402 – 2.480 GHz
RF Output Power (E.I.R.P.)	+4dBm (MAX), Power Class 2