

KDC-BT572U

FM	Frequency Range (Frequency step)	87.9MHz – 107.9MHz (200kHz)
	Usable Sensitivity S/N:26dB	8.2dBf (0.71 μ V/75 Ω)
	Quieting Sensitivity DIN S/N 46dB	17.2dBf (2.0 μ V/75 Ω)
	Frequency Response (\pm 3.0dB)	30Hz–15kHz
	S/N	64dB(MONO)
	Stereo Separation	40dB(1 kHz)
AM	Frequency Range (Frequency step)	530kHz – 1700kHz (10kHz)
	Usable Sensitivity S/N:20dB	29dB μ (28.2 μ v)
CD	Laser Diode	GaAlAs
	Digital Filter(D/A)	8 Times OverSampling
	Spindle Speed	500~200rpm(CLV)
	Wow & Flutter	Below Measurable Limit
	Frequency Response	20–20kHz(\pm 1dB)
	Total Harmonic Distortion	0.01%(1 kHz)
	S/N Ratio (dB)	105dB(1 kHz)
	Dynamic Range	90dB
	Channel Separation	85dB

	MP3 Decode	Compliant with MPEG-1/2 Audio Layer-3
	WMA Decode	Compliant with WINDOWS MEDIA AUDIO
	AAC Decode	AAC-LC ".aac" files
	WAV Decode	-
USB I/F	USB	USB 1.1 / 2.0 full speed
	File System	FAT12 / 16 / 32
	Maximum Supply current	DC5V(DC logo) 1.5A
	MP3 decode	Compliant with MPEG-1/2 Audio Layer-3
	WMA decode	Compliant with Windows Media Audio
	AAC Decode	AAC-LC ".aac", ".m4a" files
	WAV Decode	Linear-PCM
	FLAC Decode	FLAC file (Up to 96kHz/24bit)
Preout Level(mV)/Load-Unbalanced		2500mV/10kΩ(CD)
Preout Impedance(Ω)		≤600Ω
Speaker Impedance(Ω)		4-8Ω
AUX Input	Frequency Response	20Hz~20KHz ±3dB
	Input Maximum Voltage	1000mV
	Input Impedance	30KΩ
AMP	Maximum Power	50wx4
	Full Bandwidth Power (at less than 1%THD)	22wx4
TONE	Band1	62.5Hz ±9dB
	Band2	100Hz ±9dB
	Band3	160Hz ±9dB
	Band4	250Hz ±9dB
	Band5	400Hz ±9dB
	Band6	630Hz ±9dB

	Band7	1kHz ±9dB
	Band8	1.6kHz ±9dB
	Band9	2.5kHz ±9dB
	Band10	4kHz ±9dB
	Band11	6.3kHz ±9dB
	Band12	10kHz ±9dB
	Band13	16kHz ±9dB
Bluetooth	Version	Bluetooth 3.0
	Frequency Range	2.402-2.480GHz
	Output Power	+4dBm(MAX)、0dBm (AVE) Power Class 2
	Maximum Communication range	Line of sight approx.10m(32.8ft)
	Profile	HFP 1.6 (Hands Free Profile) SPP(Serial Port Profile) PBAP(Phonebook Access Profile) A2DP(Advanced Audio Distribution Profile) AVRCP 1.5 (Audio/Video Remote Control Profile)
GENE	Operating voltage (10.5~16v allowable)	14.4v
	Maximum Current Consumption	10A
	Operational Temperature Range	-10°C to +60°C
	Dimensions (W) (H) (D)	182(mm) 7-3/16(in) 53(mm) 2-1/16(in) 158(mm) 6-1/4(in)
	Net Weight (Trim plate and Mounting sleeve: Included)	1.3(kg) 2.9(lbs)

Marine

1 DIN CDR

Digital Media Receivers

Amplifiers

Speakers

Accessories

Amplifiers

Amplifiers

Compact Amplifiers

Support