

CTA-2006 Primary Ratings	Power Output	50 Watts RMS x 4 at 4 Ohms and $\leq 1\%$ THD+N
	Signal-to-Noise Ratio	80dBA (Reference: 1Watt into 4Ohms)
Maximum Power Output	MAX POWER	600W
Rated Power Output at 14.4V	A/B (4 Ohms)	50Watts RMS x 4 (4 Ohms, 20-20kHz, $\leq 1.0\%$ THD)
	A/B (2 Ohms)	75Watts RMS x 4 (2 Ohms, 1kHz, $\leq 1.0\%$ THD)
	A/B (Bridged 4Ohms)	150Watts RMS x 2 (Bridged 4 Ohms, 1kHz, $\leq 1.0\%$ THD)
Specifications	Signal to Noise Ratio	100dB (Reference: Rated Power into 4Ohms at 14.4V)
	Frequency Response	20Hz-50kHz (+0dB, -3dB)
	Input Impedance	10k ohm
	Speaker Impedance	4 $\Omega$ (2 $\Omega$ to 8 $\Omega$ allowable)
	Bridged Connection	4 $\Omega$ to 8 $\Omega$ allowable
Audio Section	Low-Pass Filter	50Hz-200Hz, -12dB/oct (A/B)
	High-Pass Filter	50Hz-200Hz, -12dB/oct (A/B)
	Bass Boost	40Hz, 0dB - +18dB (Bch)
	RCA Input Sensitivity	0.2[V] - 5.0 [V]
	Speaker Level Input Sensitivity	4.0[V] - 12.0 [V]
Terminals	Battery & Ground	M6 Screw Type Terminal Block
	Speaker Output	M4 Screw Type Terminal Block
General	Dimensions(WxHxD)	6-11/16 x 2-3/16 x 7-3/8 [inch]
	Operating Voltage	14.4V (11-16V allowable)
	Current Consumption	25[A]
Key Features	CTA-2006 Compliant 2 Ohms Load Capability Speaker Level Input with Signal Sensing Turn-on Power MOS-FET Switching Power Supply Extruded Aluminum Heat Sink Design	

CTA-2006 Primary Ratings	Power Output	50 Watts RMS x 4 at 4 Ohms and $\leq 1\%$ THD+N
	Signal-to-Noise Ratio	80dBA (Reference: 1Watt into 4Ohms)
Maximum Power Output	MAX POWER	600W
Rated Power Output at 14.4V	A/B (4 Ohms)	50Watts RMS x 4 (4 Ohms, 20-20kHz, $\leq 1.0\%$ THD)
	A/B (2 Ohms)	75Watts RMS x 4 (2 Ohms, 1kHz, $\leq 1.0\%$ THD)
	A/B (Bridged 4Ohms)	150Watts RMS x 2 (Bridged 4 Ohms, 1kHz, $\leq 1.0\%$ THD)
Specifications	Signal to Noise Ratio	100dB (Reference: Rated Power into 40hms at 14.4V)
	Frequency Response	20Hz-50kHz (+0dB, -3dB)
	Input Impedance	10k ohm
	Speaker Impedance	4 $\Omega$ (2 $\Omega$ to 8 $\Omega$ allowable)
	Bridged Connection	4 $\Omega$ to 8 $\Omega$ allowable
Audio Section	Low-Pass Filter	50Hz-200Hz, -12dB/oct (A/B)
	High-Pass Filter	50Hz-200Hz, -12dB/oct (A/B)
	Bass Boost	40Hz, 0dB - +18dB (Bch)
	RCA Input Sensitivity	0.2[V] - 5.0 [V]
	Speaker Level Input Sensitivity	4.0[V] - 12.0 [V]
Terminals	Battery & Ground	M6 Screw Type Terminal Block
	Speaker Output	M4 Screw Type Terminal Block
General	Dimensions(WxHxD)	6-11/16 x 2-3/16 x 7-3/8 [inch]
	Operating Voltage	14.4V (11-16V allowable)
	Current Consumption	25[A]
Key Features	CTA-2006 Compliant 2 Ohms Load Capability Speaker Level Input with Signal Sensing Turn-on Power MOS-FET Switching Power Supply Extruded Aluminum Heat Sink Design	

CTA-2006 Primary Ratings	Power Output	50 Watts RMS x 4 at 4 Ohms and $\leq 1\%$ THD+N
	Signal-to-Noise Ratio	80dBA (Reference: 1Watt into 4Ohms)
Maximum Power Output	MAX POWER	600W
Rated Power Output at 14.4V	A/B (4 Ohms)	50Watts RMS x 4 (4 Ohms, 20-20kHz, $\leq 1.0\%$ THD)
	A/B (2 Ohms)	75Watts RMS x 4 (2 Ohms, 1kHz, $\leq 1.0\%$ THD)
	A/B (Bridged 4Ohms)	150Watts RMS x 2 (Bridged 4 Ohms, 1kHz, $\leq 1.0\%$ THD)
Specifications	Signal to Noise Ratio	100dB (Reference: Rated Power into 40hms at 14.4V)
	Frequency Response	20Hz-50kHz (+0dB, -3dB)
	Input Impedance	10k ohm
	Speaker Impedance	4 $\Omega$ (2 $\Omega$ to 8 $\Omega$ allowable)
	Bridged Connection	4 $\Omega$ to 8 $\Omega$ allowable
Audio Section	Low-Pass Filter	50Hz-200Hz, -12dB/oct (A/B)
	High-Pass Filter	50Hz-200Hz, -12dB/oct (A/B)
	Bass Boost	40Hz, 0dB - +18dB (Bch)
	RCA Input Sensitivity	0.2[V] - 5.0 [V]
	Speaker Level Input Sensitivity	4.0[V] - 12.0 [V]
Terminals	Battery & Ground	M6 Screw Type Terminal Block
	Speaker Output	M4 Screw Type Terminal Block
General	Dimensions(WxHxD)	6-11/16 x 2-3/16 x 7-3/8 [inch]
	Operating Voltage	14.4V (11-16V allowable)
	Current Consumption	25[A]
Key Features	CTA-2006 Compliant 2 Ohms Load Capability Speaker Level Input with Signal Sensing Turn-on Power MOS-FET Switching Power Supply Extruded Aluminum Heat Sink Design	

CTA-2006 Primary Ratings	Power Output	50 Watts RMS x 4 at 4 Ohms and $\leq 1\%$ THD+N
	Signal-to-Noise Ratio	80dBA (Reference: 1Watt into 4Ohms)
Maximum Power Output	MAX POWER	600W
Rated Power Output at 14.4V	A/B (4 Ohms)	50Watts RMS x 4 (4 Ohms, 20-20kHz, $\leq 1.0\%$ THD)
	A/B (2 Ohms)	75Watts RMS x 4 (2 Ohms, 1kHz, $\leq 1.0\%$ THD)
	A/B (Bridged 4Ohms)	150Watts RMS x 2 (Bridged 4 Ohms, 1kHz, $\leq 1.0\%$ THD)
Specifications	Signal to Noise Ratio	100dB (Reference: Rated Power into 4Ohms at 14.4V)
	Frequency Response	20Hz-50kHz (+0dB, -3dB)
	Input Impedance	10k ohm
	Speaker Impedance	4 $\Omega$ (2 $\Omega$ to 8 $\Omega$ allowable)
	Bridged Connection	4 $\Omega$ to 8 $\Omega$ allowable
Audio Section	Low-Pass Filter	50Hz-200Hz, -12dB/oct (A/B)
	High-Pass Filter	50Hz-200Hz, -12dB/oct (A/B)
	Bass Boost	40Hz, 0dB - +18dB (Bch)
	RCA Input Sensitivity	0.2[V] - 5.0 [V]
	Speaker Level Input Sensitivity	4.0[V] - 12.0 [V]
Terminals	Battery & Ground	M6 Screw Type Terminal Block
	Speaker Output	M4 Screw Type Terminal Block
General	Dimensions(WxHxD)	6-11/16 x 2-3/16 x 7-3/8 [inch]
	Operating Voltage	14.4V (11-16V allowable)
	Current Consumption	25[A]
Key Features	CTA-2006 Compliant 2 Ohms Load Capability Speaker Level Input with Signal Sensing Turn-on Power MOS-FET Switching Power Supply Extruded Aluminum Heat Sink Design	