

|                         |              |                           |
|-------------------------|--------------|---------------------------|
| ELECTRICAL              |              |                           |
| Impedance ( $\Omega$ )  | 4            |                           |
| Peak Input Power (W)    | 1300         |                           |
| RMS Power (W)           | 300          |                           |
| Sensitivity (dB at 1m)  | 84           |                           |
| Frequency Response (Hz) | 33 ~ 300     |                           |
| MOUNTED SPEAKER         |              |                           |
| Size                    | 250mm        | 10 inch                   |
| Diaphragm               | Paper        |                           |
| Cap                     | Injection PP |                           |
| Surround                | Urethane     |                           |
| Basket                  | Steel        |                           |
| Gasket                  | ABS          |                           |
| Magnet                  | Ferrite      | $\phi$ 134- $\phi$ 70-t30 |
| DIMENSION               |              |                           |
| Width                   | 275mm        | 10 - 13/16 inch           |
| Height                  | 275mm        | 10 - 13/16 inch           |
| Cut-out Diameter        | 230mm        | 9 - 1/16 inch             |
| Depth                   | 142.2mm      | 5 - 5/8 inch              |
| Mounting Depth          | 124mm        | 4 - 7/8 inch              |
| WEIGHT                  |              |                           |
| Woofer without Gasket   | 4.0 kg       | 8.8 lb                    |
| Gross Weight            | 4.6 kg       | 10.1 lb                   |
| Weight of Magnet        | 1560 g       | 54.9 oz                   |

|                         |              |                           |
|-------------------------|--------------|---------------------------|
| ELECTRICAL              |              |                           |
| Impedance ( $\Omega$ )  | 4            |                           |
| Peak Input Power (W)    | 1300         |                           |
| RMS Power (W)           | 300          |                           |
| Sensitivity (dB at 1m)  | 84           |                           |
| Frequency Response (Hz) | 33 ~ 300     |                           |
| MOUNTED SPEAKER         |              |                           |
| Size                    | 250mm        | 10 inch                   |
| Diaphragm               | Paper        |                           |
| Cap                     | Injection PP |                           |
| Surround                | Urethane     |                           |
| Basket                  | Steel        |                           |
| Gasket                  | ABS          |                           |
| Magnet                  | Ferrite      | $\phi$ 134- $\phi$ 70-t30 |
| DIMENSION               |              |                           |
| Width                   | 275mm        | 10 - 13/16 inch           |
| Height                  | 275mm        | 10 - 13/16 inch           |
| Cut-out Diameter        | 230mm        | 9 - 1/16 inch             |
| Depth                   | 142.2mm      | 5 - 5/8 inch              |
| Mounting Depth          | 124mm        | 4 - 7/8 inch              |
| WEIGHT                  |              |                           |
| Woofer without Gasket   | 4.0 kg       | 8.8 lb                    |
| Gross Weight            | 4.6 kg       | 10.1 lb                   |
| Weight of Magnet        | 1560 g       | 54.9 oz                   |

|                         |              |                           |
|-------------------------|--------------|---------------------------|
| ELECTRICAL              |              |                           |
| Impedance ( $\Omega$ )  | 4            |                           |
| Peak Input Power (W)    | 1300         |                           |
| RMS Power (W)           | 300          |                           |
| Sensitivity (dB at 1m)  | 84           |                           |
| Frequency Response (Hz) | 33 ~ 300     |                           |
| MOUNTED SPEAKER         |              |                           |
| Size                    | 250mm        | 10 inch                   |
| Diaphragm               | Paper        |                           |
| Cap                     | Injection PP |                           |
| Surround                | Urethane     |                           |
| Basket                  | Steel        |                           |
| Gasket                  | ABS          |                           |
| Magnet                  | Ferrite      | $\phi$ 134- $\phi$ 70-t30 |
| DIMENSION               |              |                           |
| Width                   | 275mm        | 10 - 13/16 inch           |
| Height                  | 275mm        | 10 - 13/16 inch           |
| Cut-out Diameter        | 230mm        | 9 - 1/16 inch             |
| Depth                   | 142.2mm      | 5 - 5/8 inch              |
| Mounting Depth          | 124mm        | 4 - 7/8 inch              |
| WEIGHT                  |              |                           |
| Woofer without Gasket   | 4.0 kg       | 8.8 lb                    |
| Gross Weight            | 4.6 kg       | 10.1 lb                   |
| Weight of Magnet        | 1560 g       | 54.9 oz                   |

| ELECTRICAL              |              |                           |
|-------------------------|--------------|---------------------------|
| Impedance ( $\Omega$ )  | 4            |                           |
| Peak Input Power (W)    | 1300         |                           |
| RMS Power (W)           | 300          |                           |
| Sensitivity (dB at 1m)  | 84           |                           |
| Frequency Response (Hz) | 33 ~ 300     |                           |
| MOUNTED SPEAKER         |              |                           |
| Size                    | 250mm        | 10 inch                   |
| Diaphragm               | Paper        |                           |
| Cap                     | Injection PP |                           |
| Surround                | Urethane     |                           |
| Basket                  | Steel        |                           |
| Gasket                  | ABS          |                           |
| Magnet                  | Ferrite      | $\phi$ 134- $\phi$ 70-t30 |
| DIMENSION               |              |                           |
| Width                   | 275mm        | 10 - 13/16 inch           |
| Height                  | 275mm        | 10 - 13/16 inch           |
| Cut-out Diameter        | 230mm        | 9 - 1/16 inch             |
| Depth                   | 142.2mm      | 5 - 5/8 inch              |
| Mounting Depth          | 124mm        | 4 - 7/8 inch              |
| WEIGHT                  |              |                           |
| Woofer without Gasket   | 4.0 kg       | 8.8 lb                    |
| Gross Weight            | 4.6 kg       | 10.1 lb                   |
| Weight of Magnet        | 1560 g       | 54.9 oz                   |

| ELECTRICAL              |              |                           |
|-------------------------|--------------|---------------------------|
| Impedance ( $\Omega$ )  | 4            |                           |
| Peak Input Power (W)    | 1300         |                           |
| RMS Power (W)           | 300          |                           |
| Sensitivity (dB at 1m)  | 84           |                           |
| Frequency Response (Hz) | 33 ~ 300     |                           |
| MOUNTED SPEAKER         |              |                           |
| Size                    | 250mm        | 10 inch                   |
| Diaphragm               | Paper        |                           |
| Cap                     | Injection PP |                           |
| Surround                | Urethane     |                           |
| Basket                  | Steel        |                           |
| Gasket                  | ABS          |                           |
| Magnet                  | Ferrite      | $\phi$ 134- $\phi$ 70-t30 |
| DIMENSION               |              |                           |
| Width                   | 275mm        | 10 - 13/16 inch           |
| Height                  | 275mm        | 10 - 13/16 inch           |
| Cut-out Diameter        | 230mm        | 9 - 1/16 inch             |
| Depth                   | 142.2mm      | 5 - 5/8 inch              |
| Mounting Depth          | 124mm        | 4 - 7/8 inch              |
| WEIGHT                  |              |                           |
| Woofer without Gasket   | 4.0 kg       | 8.8 lb                    |
| Gross Weight            | 4.6 kg       | 10.1 lb                   |
| Weight of Magnet        | 1560 g       | 54.9 oz                   |

|                         |              |                           |
|-------------------------|--------------|---------------------------|
| ELECTRICAL              |              |                           |
| Impedance ( $\Omega$ )  | 4            |                           |
| Peak Input Power (W)    | 1300         |                           |
| RMS Power (W)           | 300          |                           |
| Sensitivity (dB at 1m)  | 84           |                           |
| Frequency Response (Hz) | 33 ~ 300     |                           |
| MOUNTED SPEAKER         |              |                           |
| Size                    | 250mm        | 10 inch                   |
| Diaphragm               | Paper        |                           |
| Cap                     | Injection PP |                           |
| Surround                | Urethane     |                           |
| Basket                  | Steel        |                           |
| Gasket                  | ABS          |                           |
| Magnet                  | Ferrite      | $\phi$ 134- $\phi$ 70-t30 |
| DIMENSION               |              |                           |
| Width                   | 275mm        | 10 - 13/16 inch           |
| Height                  | 275mm        | 10 - 13/16 inch           |
| Cut-out Diameter        | 230mm        | 9 - 1/16 inch             |
| Depth                   | 142.2mm      | 5 - 5/8 inch              |
| Mounting Depth          | 124mm        | 4 - 7/8 inch              |
| WEIGHT                  |              |                           |
| Woofer without Gasket   | 4.0 kg       | 8.8 lb                    |
| Gross Weight            | 4.6 kg       | 10.1 lb                   |
| Weight of Magnet        | 1560 g       | 54.9 oz                   |