

FM	Frequency Range	87.9MHz to 107.9MHz
	(Frequency step)	(200kHz)
	Channel Space Selection	
	Usable Sensitivity	8.2dBf
	S/N 30dB	(0.71 μ V/75 Ω)
	Quieting Sensitivity	17.2dBf
	DIN S/N:46dB	(2.0 μ V/75 Ω)
	Frequency Response(\pm 3.0dB)	30Hz to 15kHz
	S/N	64.0dB(MONO)
	Stereo Separation	40dB(1kHz)
AM	Frequency Range	530kHz to 1700kHz
	(Frequency step)	(10kHz)
	Channel Space Selection	-
	Usable Sensitivity	29dB μ (28.2 μ V)
	S/N:20dB	-
CD	Laser Diode	GaAlAs
	Digital Filter(D/A)	8 Times OverSampling
	Spindle Speed	500 to 200rpm (CLV)
	Wow & Flutter	Below Measurable Limit
	Frequency Response	20Hz to 20kHz(\pm 1dB)
	Total Harmonic Distortion	0.02%(1kHz)
	S/N Ratio (dB)	99dB(1kHz)
	Dynamic Range	92dB
	Channel Separation	90dB

FM	Frequency Range	87.9MHz to 107.9MHz
	(Frequency step)	(200kHz)
	Channel Space Selection	
	Usable Sensitivity	8.2dBf
	S/N 30dB	(0.71μV/75Ω)
	Quieting Sensitivity	17.2dBf
	DIN S/N:46dB	(2.0μV/75Ω)
	Frequency Response(±3.0dB)	30Hz to 15kHz
	S/N	64.0dB(MONO)
	Stereo Separation	40dB(1kHz)
AM	Frequency Range	530kHz to 1700kHz
	(Frequency step)	(10kHz)
	Channel Space Selection	-
	Usable Sensitivity	29dBμ (28.2μV)
	S/N:20dB	-
CD	Laser Diode	GaAlAs
	Digital Filter(D/A)	8 Times OverSampling
	Spindle Speed	500 to 200rpm (CLV)
	Wow & Flutter	Below Measurable Limit
	Frequency Response	20Hz to 20kHz(±1dB)
	Total Harmonic Distortion	0.02%(1kHz)
	S/N Ratio (dB)	99dB(1kHz)
	Dynamic Range	92dB
	Channel Separation	90dB

FM	Frequency Range	87.9MHz to 107.9MHz
	(Frequency step)	(200kHz)
	Channel Space Selection	
	Usable Sensitivity	8.2dBf
	S/N 30dB	(0.71 μ V/75 Ω)
	Quieting Sensitivity	17.2dBf
	DIN S/N:46dB	(2.0 μ V/75 Ω)
	Frequency Response(\pm 3.0dB)	30Hz to 15kHz
	S/N	64.0dB(MONO)
	Stereo Separation	40dB(1kHz)
AM	Frequency Range	530kHz to 1700kHz
	(Frequency step)	(10kHz)
	Channel Space Selection	-
	Usable Sensitivity	29dB μ (28.2 μ V)
	S/N:20dB	-
CD	Laser Diode	GaAlAs
	Digital Filter(D/A)	8 Times OverSampling
	Spindle Speed	500 to 200rpm (CLV)
	Wow & Flutter	Below Measurable Limit
	Frequency Response	20Hz to 20kHz(\pm 1dB)
	Total Harmonic Distortion	0.02%(1kHz)
	S/N Ratio (dB)	99dB(1kHz)
	Dynamic Range	92dB
	Channel Separation	90dB

FM	Frequency Range	87.9MHz to 107.9MHz
	(Frequency step)	(200kHz)
	Channel Space Selection	
	Usable Sensitivity	8.2dBf
	S/N 30dB	(0.71 μ V/75 Ω)
	Quieting Sensitivity	17.2dBf
	DIN S/N:46dB	(2.0 μ V/75 Ω)
	Frequency Response(\pm 3.0dB)	30Hz to 15kHz
	S/N	64.0dB(MONO)
	Stereo Separation	40dB(1kHz)
AM	Frequency Range	530kHz to 1700kHz
	(Frequency step)	(10kHz)
	Channel Space Selection	-
	Usable Sensitivity	29dB μ (28.2 μ V)
	S/N:20dB	-
CD	Laser Diode	GaAlAs
	Digital Filter(D/A)	8 Times OverSampling
	Spindle Speed	500 to 200rpm (CLV)
	Wow & Flutter	Below Measurable Limit
	Frequency Response	20Hz to 20kHz(\pm 1dB)
	Total Harmonic Distortion	0.02%(1kHz)
	S/N Ratio (dB)	99dB(1kHz)
	Dynamic Range	92dB
	Channel Separation	90dB