LG REFRIGERATION

LRMDS3006_

4-Door French Door Refrigerator

Door-in-Door® with Adjustable Bin Full-Convert™ Drawer Dual Ice Maker with Craft Ice™ Smart Cooling Plus™ System PrintProof™ Micro Surface LED Door Cooling + Cool Guard Metal Back Wall Measured Fill LG ThinQ® App Compatible SmartDiagnosis™ **ENERGY STAR® Qualified**



Enjoy new ways to control your home with LG smart appliances

- Get an alert when kids forget to close the doorMake more ice while you're at work
- Works with the LG ThinQ® app



works with the Google Assistant



| CAPACITY | |
|---------------------------------|--|
| Refrigerator (cu.ft.) | 17.00 |
| Full-Convert™ Drawer | 3.60 |
| Freezer (cu.ft.) | 8.90 |
| Total Capacity (cu.ft.) | 29.50 |
| ENERGY | 25.50 |
| Energy Consumption (kWh/Year) | 799 |
| ENERGY STAR® Qualified | Yes |
| WATER & ICE SYSTEM | 163 |
| Ice & Water Dispenser | Yes |
| Dispenser Type | Integrated Ice & Water Dispenser |
| Measured Fill | Yes |
| Daily Ice Production (lbs) | 3.5 lbs |
| IcePlus™ Production (lbs) | 3.8 lbs |
| Craft Ice™ Daily Ice Production | 0.4 lbs |
| Ice Storage Capacity (Ibs) | 3.0 + 3.3 lbs |
| Ice System | Slim SpacePlus® |
| Dual Ice with Craft Ice™ | Yes |
| Dispenser Light | Yes |
| Water Filter | LT1000P |
| COOLING | |
| Linear Compressor | Yes |
| Smart Cooling Plus™ System | Yes |
| Door Cooling+ | Yes |
| Multi-Air Flow™ System | Yes |
| Temperature Sensors | 9 |
| Fresh Air Filter | Yes |
| Evaporator | 2 |
| Refrigerant | R600a: Low Global Warming Potential, Zero Ozone Depletion Potential and More Energy Efficient Refrigerant than R134a |
| CONVENIENCE | |
| Display Type | Smooth Touch Control / White LED |
| Temperature Controls | Electronic/Digital |
| Door Alarm | Yes |
| Child Lock | Yes |
| Auto Closing Door Hinge | Yes |
| Sabbath Mode | Yes |
| LoDecibel™ Quiet Operation | Yes |
| REFRIGERATOR | |
| No. of Shelves | 4 Split (3 Fixed+1 Folding) |
| Folding Shelf | 1 |
| Cantilevered Shelves | Yes |
| Shelf Construction | Spill Protector™ Tempered Glass |
| Crisper Bins | 2 Humidity Crisper |
| Cool Guard | Yes |
| Refrigerator Light | Micro Surface LED |
| Full-Convert™ Drawer | |
| Dividers | Yes |
| Temperature Range (°F) | -7, 29, 33, 37, 41 |
| Handle Type | SmartPull™ |
| | |
| | |



| Yes |
|---|
| Yes |
| 8 |
| 1 Piece (Clear) |
| |
| Pull Drawer |
| 3- Tier Organization |
| Yes |
| Yes |
| Icemaker & Ice bin in the freezer |
| Premium LED |
| SmartPull™ Handle |
| |
| Yes |
| Yes |
| Google Assistant, Amazon Alexa |
| Yes |
| |
| Yes |
| Yes |
| Smooth |
| Yes |
| Matching Commercial Handles |
| PrintProof™ Stainless Steel PrintProof™ Black Stainless Steel |
| |
| Cyclopentane: Low Global Warming Potential, and Zero Ozone Depletion Potential Blowing Agent |
| |
| |
| Ozone Depletion Potential Blowing Agent |
| Ozone Depletion Potential Blowing Agent 38 1/8" |
| Ozone Depletion Potential Blowing Agent 38 1/8" 35 3/4" |
| Ozone Depletion Potential Blowing Agent 38 1/8" 35 3/4" 31" |
| Ozone Depletion Potential Blowing Agent 38 1/8" 35 3/4" 31" 50" |
| Ozone Depletion Potential Blowing Agent 38 1/8" 35 3/4" 31" 50" 69" |
| Ozone Depletion Potential Blowing Agent 38 1/8" 35 3/4" 31" 50" 69" 70 1/4" |
| Ozone Depletion Potential Blowing Agent 38 1/8" 35 3/4" 31" 50" 69" 70 1/4" 35 3/4" |
| Ozone Depletion Potential Blowing Agent 38 1/8" 35 3/4" 31" 50" 69" 70 1/4" 35 3/4" 45" |
| Ozone Depletion Potential Blowing Agent 38 1/8" 35 3/4" 31" 50" 69" 70 1/4" 35 3/4" 45" |
| Ozone Depletion Potential Blowing Agent 38 1/8" 35 3/4" 31" 50" 69" 70 1/4" 35 3/4" 45" 40" 4 5/8" |
| Ozone Depletion Potential Blowing Agent 38 1/8" 35 3/4" 31" 50" 69" 70 1/4" 35 3/4" 45" 40" 4 5/8" 2 1/4" |
| Ozone Depletion Potential Blowing Agent 38 1/8" 35 3/4" 31" 50" 69" 70 1/4" 33 3/4" 45" 40" 4 5/8" 2 1/4" Sides 1/8", Top 1", Back 2" |
| Ozone Depletion Potential Blowing Agent 38 1/8" 35 3/4" 31" 50" 69" 70 1/4" 35 3/4" 45" 40" 4 5/8" 2 1/4" Sides 1/8", Top 1", Back 2" 357 lbs. / 381 lbs. |
| Ozone Depletion Potential Blowing Agent 38 1/8" 35 3/4" 31" 50" 69" 70 1/4" 35 3/4" 45" 40" 4 5/8" 2 1/4" Sides 1/8", Top 1", Back 2" 357 lbs. / 381 lbs. 38" x 73" x 40" |
| Ozone Depletion Potential Blowing Agent 38 1/8" 35 3/4" 31" 50" 69" 70 1/4" 35 3/4" 45" 40" 4 5/8" 2 1/4" Sides 1/8", Top 1", Back 2" 357 lbs. / 381 lbs. 38" x 73" x 40" |
| Ozone Depletion Potential Blowing Agent 38 1/8" 35 3/4" 31" 50" 69" 70 1/4" 35 3/4" 45" 40" 4 5/8" 2 1/4" Sides 1/8", Top 1", Back 2" 357 lbs. / 381 lbs. 38" x 73" x 40" |
| Ozone Depletion Potential Blowing Agent 38 1/8" 35 3/4" 31" 50" 69" 70 1/4" 35 3/4" 45" 40" 4 5/8" 2 1/4" Sides 1/8", Top 1", Back 2" 357 lbs. / 381 lbs. 38" x 73" x 40" |
| Ozone Depletion Potential Blowing Agent 38 1/8" 35 3/4" 31" 50" 69" 70 1/4" 35 3/4" 45" 40" 4 5/8" 2 1/4" Sides 1/8", Top 1", Back 2" 357 lbs. / 381 lbs. 38" x 73" x 40" |
| Ozone Depletion Potential Blowing Agent 38 1/8" 35 3/4" 31" 50" 69" 70 1/4" 35 3/4" 45" 40" 4 5/8" 2 1/4" Sides 1/8", Top 1", Back 2" 357 lbs. / 381 lbs. 38" x 73" x 40" 1 Year 5 Years 5 Years 6-10 Years |
| 38 1/8" 35 3/4" 31" 50" 69" 70 1/4" 35 3/4" 45" 40" 4 5/8" 2 1/4" Sides 1/8," Top 1," Back 2" 357 lbs. / 381 lbs. 38" x 73" x 40" |
| |