CLASSICO





Variable speed control with last setting memory.



Halogen lamps brilliantly illuminate the cooktop.



Hi-Flow[™] baffle filters utilize a V-mesh & baffle design to increase airflow, lower sound levels and provide excellent ventilation efficiency.



WP28 iQ

Exclusive iQ Blower System[™] with GPS Technology (see page 62) for the quietest, most energy efficient and fastest smoke and odor removal available in a range hood; choice of 13 Internal or

External blower options offered separately.

Bright Halogen lighting floods the cooktop and surrounding area for clear visibility.

Mesh lined Hi-Flow[™] baffle filters provide superior grease capture to ensure a clean, fresh kitchen.

Heat Sentry[™] detects excessive heat and adjusts blower to high automatically.

Works with optional Universal Make-Up Air Dampers.

WP28M30SB	WP28
WP28M36SB	WP28

Hood Sizes Widths

30", 36", 42", 48", 54", 60" 24"

Must purchase blower separately.

Finish

Depth

i inion	
Stocked	Brushed Stainless Steel
Special Order	Not Available
Features	
Lighting Type	Halogen, GU10, MR16, 50-watt
Number of Lamps	2 on 30", 36" 4 on 42", 48", 54", 60"
Lighting Levels	2
Lighting Lamps Included	Yes
Control Type	Variable Speed Rotary with Last Setting Memory
Control Features	Heat Sentry [™]
Remote Control	Not Available
Filter Type	Hi-Flow™ Baffle Filter
Non-ducted Capability	Νο

Hood Blower Options (Must choose one blower sold separately)

					· [· · · · ·),
Internal	iQ6	iQ12	P3	P6	P12
Blower CFM	600	1200	300	600	1200
Sones Low/High	0.3/7.5	0.3/10.5	0.3/3.5	2.0/9.5	2.25/12.0
External In-line	ILB3	ILB6	ILB9	ILB11	
Max CFM	280	600	800	1100	
Sone levels are typically half of comparable CFM internal blowers.					
External Exterior	EB6	EB9	EB12	EB15	
Max CFM	600	900	1200	1500	
Sone levels are typically half of comparable CFM internal blowers.					


Accessories

Decorative Soffit Flue	AEWP28302SB, AEWP28362SB, AEWP28422SB, AEWP28482SB, AEWP28542SB, AEWP28602SB
Backsplashes Universal MUA Damper	RMP3604, RMP4204, RMP6004 MD6TU, MD8TU, MD10TU

Installation Requirements

Amps @ 120V Electrical Duct Size: Internal Blower Duct Size: External Blower Duct Direction Backdraft Damper

8.5 Max Direct Wire 8" (iQ6, P3, P6) 10" (iQ12, P12) 10" (at hood) Vertical and Horizontal Refer to Blower



Installation height above the cooking surface: 24"-36"

For more details see the product specifications sheet found at www.BESTRangeHoods.com

AEWP Decorative Soffit Flue

A soffit flue is available in brushed stainless steel, and attaches to the top of the range hood shell. It is available in all hood widths in 12" height only.

