

Monitor Section

Picture size	6.2 inches(diagonal) wide
W x H	137.5mm x 77.2 mm , 5-7/16 x 3-1/16 inch
Display system	TN LCD panel
Drive system	TFT active matrix system
Number of pixels	1,152,000 800H x 480V x RGB
Effective pixels	99.99%
Pixel arrangement	RGB striped arrangement
Back lighting	LED

DVD Section

D/A Converter	24 / 32Bit	
Audio Decoder	Linear PCM Dolby Audio MP3 / WMA / AAC / WAV / FLAC / Vorbis	
Video Decoder	MPEG1/2,MPEG4 / WMV / H.264 / MKV	
Wow & Flutter	Below Measurable Limit	
Frequency response	96k Sampling	20 - 44,000 Hz
	48k Sampling	20 - 22,000 Hz
	44.1k Sampling	20 - 20,000 Hz
Total harmonic distortion 1kHz	0.010%	
Signal to Noise ratio	90.5dB (DVD-Video 96k)	
Dynamic range	89dB (DVD-Video 96k)	
DISC Format	DVD-Video / VIDEO-CD / CD-DA	
Quantifying bit number	16 / 20 / 24bit	

USB I/F Section

USB Standard	USB2.0 High Speed
File System	FAT 16/32, exFAT, NTFS
Maximum Power Supply Current	DC5V=1.5A
D/A Converter	24/32Bit
Audio Decoder	MP3 / WMA / AAC / WAV / FLAC / Vorbis
Video Decoder	MPEG1/2,MPEG4 / WMV / H.264 / MKV

Bluetooth Section

Technology	Bluetooth Ver4.1
Frequency	2.402 – 2.480 GHz

Monitor Section

Picture size	6.2 inches(diagonal) wide
W x H	137.5mm x 77.2 mm , 5-7/16 x 3-1/16 inch
Display system	TN LCD panel
Drive system	TFT active matrix system
Number of pixels	1,152,000 800H x 480V x RGB
Effective pixels	99.99%
Pixel arrangement	RGB striped arrangement
Back lighting	LED

DVD Section

D/A Converter	24 / 32Bit	
Audio Decoder	Linear PCM Dolby Audio MP3 / WMA / AAC / WAV / FLAC / Vorbis	
Video Decoder	MPEG1/2,MPEG4 / WMV / H.264 / MKV	
Wow & Flutter	Below Measurable Limit	
Frequency response	96k Sampling	20 - 44,000 Hz
	48k Sampling	20 - 22,000 Hz
	44.1k Sampling	20 - 20,000 Hz
Total harmonic distortion 1kHz	0.010%	
Signal to Noise ratio	90.5dB (DVD-Video 96k)	
Dynamic range	89dB (DVD-Video 96k)	
DISC Format	DVD-Video / VIDEO-CD / CD-DA	
Quantifying bit number	16 / 20 / 24bit	

USB I/F Section

USB Standard	USB2.0 High Speed
File System	FAT 16/32, exFAT, NTFS
Maximum Power Supply Current	DC5V=1.5A
D/A Converter	24/32Bit
Audio Decoder	MP3 / WMA / AAC / WAV / FLAC / Vorbis
Video Decoder	MPEG1/2,MPEG4 / WMV / H.264 / MKV

Bluetooth Section

Technology	Bluetooth Ver4.1
Frequency	2.402 – 2.480 GHz

Monitor Section

Picture size	6.2 inches(diagonal) wide
W x H	137.5mm x 77.2 mm , 5-7/16 x 3-1/16 inch
Display system	TN LCD panel
Drive system	TFT active matrix system
Number of pixels	1,152,000 800H x 480V x RGB
Effective pixels	99.99%
Pixel arrangement	RGB striped arrangement
Back lighting	LED

DVD Section

D/A Converter	24 / 32Bit	
Audio Decoder	Linear PCM Dolby Audio MP3 / WMA / AAC / WAV / FLAC / Vorbis	
Video Decoder	MPEG1/2,MPEG4 / WMV / H.264 / MKV	
Wow & Flutter	Below Measurable Limit	
Frequency response	96k Sampling	20 - 44,000 Hz
	48k Sampling	20 - 22,000 Hz
	44.1k Sampling	20 - 20,000 Hz
Total harmonic distortion 1kHz	0.010%	
Signal to Noise ratio	90.5dB (DVD-Video 96k)	
Dynamic range	89dB (DVD-Video 96k)	
DISC Format	DVD-Video / VIDEO-CD / CD-DA	
Quantifying bit number	16 / 20 / 24bit	

USB I/F Section

USB Standard	USB2.0 High Speed
File System	FAT 16/32, exFAT, NTFS
Maximum Power Supply Current	DC5V=1.5A
D/A Converter	24/32Bit
Audio Decoder	MP3 / WMA / AAC / WAV / FLAC / Vorbis
Video Decoder	MPEG1/2,MPEG4 / WMV / H.264 / MKV

Bluetooth Section

Technology	Bluetooth Ver4.1
Frequency	2.402 – 2.480 GHz

Monitor Section

Picture size	6.2 inches(diagonal) wide
W x H	137.5mm x 77.2 mm , 5-7/16 x 3-1/16 inch
Display system	TN LCD panel
Drive system	TFT active matrix system
Number of pixels	1,152,000 800H x 480V x RGB
Effective pixels	99.99%
Pixel arrangement	RGB striped arrangement
Back lighting	LED

DVD Section

D/A Converter	24 / 32Bit	
Audio Decoder	Linear PCM Dolby Audio MP3 / WMA / AAC / WAV / FLAC / Vorbis	
Video Decoder	MPEG1/2,MPEG4 / WMV / H.264 / MKV	
Wow & Flutter	Below Measurable Limit	
Frequency response	96k Sampling	20 - 44,000 Hz
	48k Sampling	20 - 22,000 Hz
	44.1k Sampling	20 - 20,000 Hz
Total harmonic distortion 1kHz	0.010%	
Signal to Noise ratio	90.5dB (DVD-Video 96k)	
Dynamic range	89dB (DVD-Video 96k)	
DISC Format	DVD-Video / VIDEO-CD / CD-DA	
Quantifying bit number	16 / 20 / 24bit	

USB I/F Section

USB Standard	USB2.0 High Speed
File System	FAT 16/32, exFAT, NTFS
Maximum Power Supply Current	DC5V=1.5A
D/A Converter	24/32Bit
Audio Decoder	MP3 / WMA / AAC / WAV / FLAC / Vorbis
Video Decoder	MPEG1/2,MPEG4 / WMV / H.264 / MKV

Bluetooth Section

Technology	Bluetooth Ver4.1
Frequency	2.402 – 2.480 GHz

Monitor Section

Picture size	6.2 inches(diagonal) wide
W x H	137.5mm x 77.2 mm , 5-7/16 x 3-1/16 inch
Display system	TN LCD panel
Drive system	TFT active matrix system
Number of pixels	1,152,000 800H x 480V x RGB
Effective pixels	99.99%
Pixel arrangement	RGB striped arrangement
Back lighting	LED

DVD Section

D/A Converter	24 / 32Bit	
Audio Decoder	Linear PCM Dolby Audio MP3 / WMA / AAC / WAV / FLAC / Vorbis	
Video Decoder	MPEG1/2,MPEG4 / WMV / H.264 / MKV	
Wow & Flutter	Below Measurable Limit	
Frequency response	96k Sampling	20 - 44,000 Hz
	48k Sampling	20 - 22,000 Hz
	44.1k Sampling	20 - 20,000 Hz
Total harmonic distortion 1kHz	0.010%	
Signal to Noise ratio	90.5dB (DVD-Video 96k)	
Dynamic range	89dB (DVD-Video 96k)	
DISC Format	DVD-Video / VIDEO-CD / CD-DA	
Quantifying bit number	16 / 20 / 24bit	

USB I/F Section

USB Standard	USB2.0 High Speed
File System	FAT 16/32, exFAT, NTFS
Maximum Power Supply Current	DC5V=1.5A
D/A Converter	24/32Bit
Audio Decoder	MP3 / WMA / AAC / WAV / FLAC / Vorbis
Video Decoder	MPEG1/2,MPEG4 / WMV / H.264 / MKV

Bluetooth Section

Technology	Bluetooth Ver4.1
Frequency	2.402 – 2.480 GHz

Monitor Section

Picture size	6.2 inches(diagonal) wide
W x H	137.5mm x 77.2 mm , 5-7/16 x 3-1/16 inch
Display system	TN LCD panel
Drive system	TFT active matrix system
Number of pixels	1,152,000 800H x 480V x RGB
Effective pixels	99.99%
Pixel arrangement	RGB striped arrangement
Back lighting	LED

DVD Section

D/A Converter	24 / 32Bit	
Audio Decoder	Linear PCM Dolby Audio MP3 / WMA / AAC / WAV / FLAC / Vorbis	
Video Decoder	MPEG1/2,MPEG4 / WMV / H.264 / MKV	
Wow & Flutter	Below Measurable Limit	
Frequency response	96k Sampling	20 - 44,000 Hz
	48k Sampling	20 - 22,000 Hz
	44.1k Sampling	20 - 20,000 Hz
Total harmonic distortion 1kHz	0.010%	
Signal to Noise ratio	90.5dB (DVD-Video 96k)	
Dynamic range	89dB (DVD-Video 96k)	
DISC Format	DVD-Video / VIDEO-CD / CD-DA	
Quantifying bit number	16 / 20 / 24bit	

USB I/F Section

USB Standard	USB2.0 High Speed
File System	FAT 16/32, exFAT, NTFS
Maximum Power Supply Current	DC5V=1.5A
D/A Converter	24/32Bit
Audio Decoder	MP3 / WMA / AAC / WAV / FLAC / Vorbis
Video Decoder	MPEG1/2,MPEG4 / WMV / H.264 / MKV

Bluetooth Section

Technology	Bluetooth Ver4.1
Frequency	2.402 – 2.480 GHz