



AR413720
400 series blower
Metal housing
Air recirculation.
420 CFM
For toe-kick installation

**Easy and compact installation of
downdrafts without exhaust ducts.
Perfect for cooking islands.
To be combined with 1-2 downdrafts**

Output

Features

Metal housing, zinc-plated.
Pipe connections air intake: 2 x DN 150
cylindrical.
Spare cover to close an air intake
included with the blower.

Planning notes

With a chimney-vented fireplace and
installing AR 413 in another area of
room air (e.g. cellar) the hood's power
supply line needs a suitable safety
switch like with an exhaust mode
ventilation.
Installation in the drawer area with
double height or on the floor with cut-
out in the furniture base. Air intake
with flat duct max. 2x DN 150 behind
the drawers requires worktop depth of
min. 27 1/2". Cabinets without plinth
possible.
For details of the remote fan unit's
effective air output in combination with
downdraft, refer to the table section.

Rating

Fan output NO_FEATURE.
Connecting cable 41 1/3"
Performance output level 3/4:
Air output according to EN 61591.
Sound power and sound pressure
depending on built-in situation.
Air recirculation:
420 CFM
For the characteristics of each output
level with/without intensive mode
please refer to the table with the
respective motorless ventilation
products.

Product Features

Product Description

Product group

Accessory

Brand

Gaggenau

Product name / series name

SKU

AR413720

Internal article number

AR413720

EAN code

4242006207472

Product packaging dimensions

(HxWxD) (in)

Net weight (lbs)

42

Gross weight (lbs)

47

Quantity per packing unit

Standard number of units per pallet

UPC code

825225897750

Name of product image

MCSA045881_AR413120_def.jpg

2017-08-30

Page 1

Color Variants

AR413720

Metal housing

Air recirculation.

AR413720
 400 series blower
 Metal housing
 Air recirculation.
 420 CFM
 For toe-kick installation
 2017-08-30
 Page 2

