



**BSP251610**  
**200 series Combi-steam oven**  
**Full glass door in Gaggenau Metallic**  
**Width 24" (60 cm)**  
**Left-hinged**  
**Controls on top**

**Flush installation**  
**Water tank**  
**Hot air 30 °C to 230 °C can be combined with chosen humidity level of 0%, 30%, 60%, 80% or 100%**  
**TFT touch display**  
**Steaming without pressure**  
**Electronic temperature control from 30 °C to 230 °C**  
**Removable meat probe**  
**Net volume 42 litres**

**Cooking modes**  
 Convection + 100 % humidity.  
 Convection + 80 % humidity.  
 Convection + 60 % humidity.  
 Convection + 30 % humidity.  
 Convection + 0 % humidity.  
 Dough proofing.  
 Defrosting.  
 Regenerating.  
 Low temperature cooking.

**Operation**  
 Rotary knob and TFT touch display operation.  
 Clear text display in 25 languages.  
 Option to save 50 individual recipes (incl. meat probe)  
 Information key with use indicators.  
 Side-opening door opens up to 110° angle.

**Features**  
 Removable 1.3 litre water tank.  
 Water level warning.  
 Meat probe with automatic shut-off function.  
 Actual temperature display.  
 Timer functions: cooking time, switch-off time, short-term timer, stopwatch.  
 Automatic boiling point detection.  
 48 W halogen light on the side.  
 Hygienic stainless steel cooking interior.  
 4 tray levels.

**Safety**  
 Child lock.  
 Safety shut-off.  
 Cooled housing with temperature protection.

**Cleaning**  
 Cleaning program.  
 Drying program.  
 Descaling programme.  
 Grease filter, dishwasher-safe.

**Planning notes**  
 Door hinge not reversible.  
 No other electrical appliances should be installed above the BSP Combi-steam oven.  
 The door panel front of the appliance extends 13/16" from the cabinet front. The outer edge of the door handle extends 2 13/16" from the cabinet front.  
 Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance.  
 When planning a corner solution, pay attention to the 110° door opening angle.  
 To achieve the 2 1/8" (550 mm) installation depth, the connection cable needs to follow the slanted edge on the corner of the housing.  
 The power outlet needs to be planned outside of the niche.

**Rating**  
 Energy efficiency class A.

**Product Features**  
**Cooking mode**  
 Defrost, fermentation, Hot Air, Hot air + steam 100%, Hot air + steam 30%, Hot air + steam 60%, Hot air + steam 80%, low temperature steam, Regeneration  
**Time-setting Options**  
**Start and Stop**  
**Convection Element Wattages primary cavity (W)**  
**Included accessories**  
 1 x STS tray-GN2/3-punched-40 mm deep, 1 x STS tray-GN2/3-unpunched-40 mm deep, 1 x grid, 1 x pluggable meat probe  
**Optional accessories**  
 GN114130, GN114230, GN124130, GN124230, GN144130, GN144230, GN154130, GN154230, GN340230, GN410130, GN410230, GR220046

**Consumption and connection features**  
**UPC code**  
 825225929307

**Product color**  
 Stainless steel

**Alternative colors available**

**Energy source**  
 Electric

**Watts (W)**

**Current (A)**  
 10

**Volts (V)**  
 208/220-240

**Frequency (Hz)**  
 60

**Approval certificates**  
 CSA, ETL, UL

**Power Cord Length**  
 59 1/16

**Plug type**  
 fixed connection

**Overall appliance dimensions (HxWxD) (in)**  
 17 15/16" x 23 1/4" x 21 9/16"

**Required cutout size (HxWxD) (in)**  
 17 3/4" x 22 1/16" x 21 11/16"

**Product packaging dimensions (HxWxD) (in)**  
 22 5/8" x 26" x 27 3/16"

**Net weight (lbs)**  
 80

**Gross weight (lbs)**  
 85

**2019-07-10**  
 Page 1

Total rating 2.2 kW.  
 Total Amps: 10 A.  
 120 V / 60 Hz  
 Plan for a 4' long connecting cable without plug (hardwire required).

**Color Variants**

**BSP251610**  
**Full glass door in Gaggenau Metallic**  
**Width 24" (60 cm)**

**Included accessories**

1 x STS tray-GN2/3-punched-40 mm deep.  
 1 x STS tray-GN2/3-unpunched-40 mm deep.  
 1 x grid.  
 1 x pluggable meat probe.

**Optional accessories**

**GN114130**  
**Stainless steel cooking insert**  
**GN114230**  
**Stainless steel cooking insert**  
**GN124130**  
**Stainless steel cooking insert**  
**GN124230**  
**Stainless steel cooking insert**  
**GN144130**  
**Gastronorm pan, non-stick, GN 1/3**  
**GN144230**  
**Gastronorm pan, non-stick, GN 2/3**  
**GN154130**  
**Gastronorm pan, non-stick, GN 1/3**  
**GN154230**  
**Gastronorm pan, non-stick, GN 2/3**  
**GN340230**  
**Non-stick aluminum cast-iron roaster**  
**GN410130**  
**Stainless steel lid**  
**GN410230**  
**Stainless steel lid**  
**GR220046**  
**Wire rack, chromium-plated**

**Product Variants**

**BSP250610**  
**200 series Combi-steam oven**  
**Full glass door in Gaggenau Metallic**  
**Width 24" (60 cm)**  
**Right-hinged**  
**Controls on top**

BSP251610  
200 series Combi-steam oven  
Full glass door in Gaggenau Metallic  
Width 24" (60 cm)  
Left-hinged  
Controls on top  
2019-07-10  
Page 2