

WS463710

400 series warming drawer Stainless steel-backed glass front Width 24" (60 cm), Height 8 1/4" (21 cm)

For side-by-side combination of 30" (76 cm) oven and 24" (60 cm) Combi-steam oven or Coffee machine Handleless warming drawer Bright interior lighting Soft-closing system Hygienic stainless steel interior with glass bottom 4 power levels in the temperature range 104 °F to 175 °F (glass surface) Keeps food and drinks warm, also for

preparing and cooking meals

Cooking modes

Defrosting of meals/proofing of yeast dough. Preheating of small beverages. Keeping meals warm/slow cooking. Warming of dishes.

Operation

Rotary knob operation. Recessed grip at the front bottom center of drawer.

Features

Usable interior dimensions W 18 11/16 " x H 5 3/16 " x D 18 1/16 " (W 475 mm x H 132 mm x D 458 mm). Net volume 1 cu. ft (29 litres). Volume capacity: Dinner service for 8 people including a 9 1/2 " (24 cm) plates and soup bowls, additional bowls and a serving dish depending on size. Integrated base glass plate for easy cleaning. Convection fan for even heat distribution to quickly warm serving dishes. Status display, visible in the glass front.

Base plate made of safety glass. Max. load 33 lbs.

Planning notes

The front of the appliance 1 7/8" extends from the cabinet front. Always use an intermediate shelf - at least 3/4" thick - when mounting a 400 series single oven or Combi-steam oven above the drawer. Installation of BS/CM above WS in 23 3/16 " (66,5 cm) cut-out with intermediate floor (gap of 7 mm between WS and BS). The power outlet can be planned behind the appliance.

Rating

Total rating: 0.81 kW. Total Amps: 10 A. 120 V / 60 Hz Connection cable 71 ", with plug. Product Features
Power output heating
0.810
Power Level
high, low, medium, plate
Type of control
Rotary knob
Temperature control
electronic
Time control
No

Consumption and connection features

UPC code 825225910589 Product color Stainless steel Alternative colors available Watts (W) 810 Current (A)

10 Volts (V)

120 Frequency (Hz)

60 Approval certificates CSA

Power Cord Length

Plug type 120V-3 prong

Required cutout size (HxWxD) (in) 8 " x 22 1/16 " x 21 11/16 " Overall appliance dimensions (HxWxD) (in)

8 3/16 " x 23 3/8 " x 21 1/16 Product packaging dimensions

(HxWxD) (in) 8 1/4 x 26 x 29 1/8 Net weight (lbs)

44

Gross weight (lbs) 50

2017-09-19 Page 1



Color Variants WS463710 Stainless steel-backed glass front Width 24" (60 cm), Height 8 1/4" (21 cm)

WS463710 400 series warming drawer Stainless steel-backed glass front Width 24" (60 cm), Height 8 1/4" (21 cm)

2017-09-19 Page 2

Side view WS 463 under BS, BM, CM





