QUICK REFERENCE GUIDE > RDV3-488-L

Dual Fuel Range, 48", 8 Burners, Self-cleaning, LPG

Series 9 | Professional

Stainless Steel with Black Glass | LPG




With intuitive touchscreen and specialized cooking functions across two ovens, this range is a stand-out addition to your kitchen.

- Guided cooking using your touchscreen makes it simple to cook by food, function or recipe.
- Top burner heat of 19,000 BTU, for seriously fast boiling
- 6.9 cu ft total oven capacity across two oven cavities
- Beautiful LED halo-illuminated dials provide information at a glance

DIMENSIONS

Height	35 ³ / ₄ - 36 ³ / ₄ "
Width	47 ⁷ / ₈ "
Depth	29 ¹ / ₈ "



FEATURES & BENEFITS

Cook with confidence

Our touchscreen interface provides an intuitive guided cooking experience that helps deliver perfect results, whether you've been cooking all your life or just starting out. Cook with a favorite method, a hero ingredient, or a go-to cooking function or recipe. The screen tilts for improved ergonomics and optimal visibility while cooking.

SPECIFICATIONS

Accessories	AH-R48
Square handle option	
Capacity	
Total capacity	6.9cu ft
Cleaning	
Dishwasher proof trivets	•
Pyrolytic self-clean	•
Controls	
High resolution display	•
Metal illuminated dials	•
Sabbath mode	•
Gas requirements	
Fitting and pipe	½ NPT, min. ⅝" Ø flex
Supply Pressure (LPG)	11" to 14" W.C
Main oven features	
Bake	•
Clean	•
Convection Bake	•
Convection Broil	•
Large broil pan	•
Main oven- Self cleaning	•

15

Main oven- True convection

Number of main oven functions

QUICK REFERENCE GUIDE > RDV3-488-L Date: 21.11.2019 > 2

Concealed element	•
Electronic oven control	
Full extension telescopic	2
Internal light	
Pyrolytic self-clean	•
Oven functions	
Pyrolytic self-clean	•
Oven performance	
Main Oven Shelf Positions	5
Main Oven Total Capacity	4.8cu ft
Main Oven Usable Capacity	3.8cu ft
Main oven- Bake	4600W
Main oven- Broil	4000W
Main oven- True convection	2500W
Secondary Oven- Bake	2450W
Secondary Oven- Broil	3600W
Secondary Oven- Capacity	2.1cu ft
Secondary Oven- Capacity	1.8cu ft
Secondary Oven- Shelf	5
Power requirements	
Electric circuit	4 wire
Rated current	50A
Supply frequency	60Hz
Supply voltage	120 - 240V

5 · · ·	1/ "
Depth	29 1/8"
Depth (Excluding handles)	29 1/8 "
Height	35 ³ / ₄ - 36 ³ / ₄ "
Height (excluding vent trim)	35 ³ / ₄ - 36 ³ / ₄ "
Width	47 ⁷ / ₈ "
Rangetop features	
Sealed Dual Flow Burners™	8
Sealed range top	•
Simmer on all burners	140°F
Vent trim included	Flat vent trim
Rangetop Performance	
Max burner power	19000BTU
Power back centre	13000BTU
Power back centre (2)	13000BTU
Power back left	13000BTU
Power back right	13000BTU
Power front centre	15000BTU
Power front centre (2)	15000BTU
Power front left	19000BTU
Power front right	19000BTU
Total cooktop power	120000BTU
Secondary Oven features	
Bake	•
Convection Bake	
Convection Broil	•

Warranty	
Parts and labor	Limted 2 Years Parts & Labor
0.44	04007
SKU	81897

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ® Fisher & Paykel Appliances Ltd 2019.

11

Secondary oven functions

QUICK REFERENCE GUIDE > RDV3-488-L Date: 21.11.2019 > 3

