



Color Variants

AR401740
Stainless steel
665 CFM

Installation Accessories

AD702052
Telescopic wall-duct
ø 8" round

AR401740
400 series blower
Stainless steel
665 CFM
Outside wall mounting
Air extraction

Maximum output for downdraft ventilation and motorless hoods
Outside installation allows lower noise level in the kitchen
To be combined with motorless hoods or downdrafts.

Output
665 CFM

Features
Complete stainless steel housing.
Duct connections air intake: 1 x Ø 8" round.

Planning notes
When installing a ventilation hood with air extraction mode and a chimney-vented fireplace, the hood's power supply line needs a suitable safety switch.
Roof installation with roof installation set AD 401 910 and telescopic wall duct AD 702 052 in slanted roofs with angle of minimal 10 °.
For maximum duct lengths use Gaggenau flat rectangular ducts AD 8... or Naber-System Compair flow. Other flat ducts are not permitted!
For noise optimisation, use the silencer SD 011 050.

Rating
Fan output NO_FEATURE.
Connecting cable 41 1/3"
Performance output level 3/4:
Air output according to EN 61591.
Sound power and sound pressure depending on built-in situation.
For the characteristics of each output level with/without intensive mode please refer to the table with the respective motorless ventilation products.

| |
|---|
| Product Features |
| Product Description |
| Product group |
| Accessory |
| Brand |
| Gaggenau |
| Product name / series name |
| SKU |
| AR401740 |
| Internal article number |
| AR401740 |
| EAN code |
| 4242006207397 |
| Product packaging dimensions (HxWxD) (in) |
| Net weight (lbs) |
| 34 |
| Gross weight (lbs) |
| 38 |
| Quantity per packing unit |
| Standard number of units per pallet |
| UPC code |
| 825225897866 |
| Name of product image |
| MCSA043418_AR401130_def.jpg |

