



Color Variants

EB333610
Stainless steel
Width 36"

Included accessories

1 x enamel baking tray.
suit. pyrolitic clean.
1 x rotary spit.
1 x grill shelf.
1 x grill tub with grid.
1 x pluggable meat probe.

Optional accessories

BA028115
Baking tray, enameled
BA058115
Heating element for baking stone and
cast-iron roaster
BA058133
Baking stone
BA090100
Black control knobs for EB 333, set of 2
BS020002
Pizza peel, additional set of 2
GN340230
Non-stick aluminum cast-iron roaster

EB333610

Single oven

Stainless steel

Width 36"

One-piece front-hinged door with 3 mm precision crafted stainless steel front door panel
Soft door opening and closing system
Diagonally positioned light sources for optimal interior lighting
Pyrolytic self-cleaning
Universal heating system with 17 heating modes, with meat probe, rotisserie spit and baking stone operation
Convection fan rotates in both directions for ideal heat distribution
TFT touch display
Panel-free appliance with control module behind glass
Electronic precision temperature control from 85° F - 550° F
3.6 cu.ft. net volume

Cooking modes

Convection.
Economy convection.
Top + bottom heat.
Top + 1/3 bottom heat.
Top heat.
1/3 top + bottom heat.
Bottom heat.
Convection + bottom heat.
Convection + 1/3 bottom heat.
Convection broiling.
Broiling.
Compact grill.
Baking stone operation.
Roaster function.
Dough proofing.
Defrosting.
Keeping warm.

Operation

Rotary knobs and TFT touch display operation.
Clear text display in 25 languages.
Option to save individual recipes (incl. meat probe)
Information key with use indicators.
Front-hinged door with 90° door opening angle.

Features

Meat probe with automatic shut-off function.
Rotisserie spit.
Baking stone outlet.
Actual temperature display.
Super-quick preheating.
Timer functions: cooking time, switch-off time, short-term timer, stopwatch, Sabbath mode.
60 W halogen light on top.
2 x 10 W halogen light on the side.
Enamelled side shelf supports with 3 rack levels, pyrolytic-safe.

Safety

Thermally insulated door with quintuple glazing.
Child lock.
Safety lock.
Cooled door housing with temperature protection.

Cleaning

Pyrolytic self-cleaning.
Gaggenau Clean-Enamel.
Heated air cleaning catalyst.

Planning notes

The door panel surface of the appliance extends 1 9/16" (40 mm) from the furniture cavity.

Product Features

Cooking mode

Baking stone function, Bottom heat, Bottom heating, 1/3 top heat., Conventional heat, Defrost, Dough proving setting, Full width broil, Half width broil, Hot Air, Hot air and 1/1 bottom heating, Hot air and 1/3 bottom heating, Hot air broiling, Hot Air-Eco, Roasting function, Top heat, Top heating, 1/3 bottom heat., warming

Integrated Cleaning system

Self Clean

Interior Lights - primary cavity

3

Pull-out system

Accessory

Timer settings

Alarm, Off, On, timer

Included accessories

1 x enamel baking tray,suit. pyrolitic clean, 1 x rotary spit, 1 x grill shelf, 1 x grill tub with grid, 1 x pluggable meat probe

Bake Element Wattages primary cavity (W)

1700

Broil Element Wattages primary cavity (W)

4250

Convection Element Wattages primary cavity (W)

2070

Microwave Wattages (W)

Drawer wattage (W)

Consumption and connection features

UPC code

825225922544

Product color

Stainless steel

Alternative colors available

Energy source

Electric

Watts (W)

5860

Current (A)

25

Volts (V)

208/220-240

Frequency (Hz)

60

Approval certificates

ETL

Power Cord Length

47 1/4

Plug type

fixed connection

Required cutout size (HxWxD) (in)

18 11/16 x 33 7/8 x 22 1/16

Product packaging dimensions (HxWxD) (in)

27 9/16 x 39 3/4 x 28 15/16

Net weight (lbs)

182

Gross weight (lbs)

206

2017-09-19

Page 1

The outer edge of the door handle extends 3 9/16" (90 mm) from the furniture cavity.
For installation underneath cooktops: Distance between the underside of the cooktop and the top edge of the oven cavity: min. 19/32" (15 mm).
The planning notes for the cooktops (particularly regarding ventilation, gas/ electric connection) must be taken into account.

To achieve the 21 5/8" (550 mm) installation depth, the connection cable needs to follow the slanted edge on the corner of the housing.

Plan a power outlet outside of the cut-out niche.

Rating

Total rating 5.9 kW.

Total Amps: 25 A.

208 / 220 - 240 V / 60 Hz

Connection cable 47 1/4 without plug (hardwire required).

