



Color Variants

**BX481611**  
**Stainless steel-backed full glass door**  
**Width 30" (76 cm)**

Included accessories

2 x enamel baking tray.  
suit. pyrolytic clean.  
1 x rotary spit.  
2 x grill shelf.  
2 x grill tub with grid.  
1 x pluggable meat probe.

Optional accessories

**BA028115**  
**Baking tray, enameled**  
**BA058115**  
**Heating element for baking stone and cast-iron roaster**  
**BA058133**  
**Baking stone**  
**BS020002**  
**Pizza peel, additional set of 2**  
**GN340230**  
**Non-stick aluminum cast-iron roaster**

Product Variants

**BX480611**  
**400 double oven**  
**Stainless steel-backed full glass door**  
**Width 30" (76 cm)**  
**Right-hinged**  
**Controls centered**

**BX481611**  
**400 double oven**  
**Stainless steel-backed full glass door**  
**Width 30" (76 cm)**  
**Left-hinged**  
**Controls centered**

**Pyrolytic self-cleaning**  
**Universal heating system with 17 heating modes, with meat probe, rotisserie spit and baking stone operation**  
**TFT touch display**  
**Electronic precision temperature control from 85° F - 550° F.**  
**2x 2.8 cu. ft. net volume**

Cooking modes

Convection.  
Economy convection.  
Top + bottom heat.  
Top + 1/3 bottom heat.  
Top heat.  
1/3 top + bottom heat.  
Bottom heat.  
Convection + bottom heat.  
Convection + 1/3 bottom heat.  
Convection broiling.  
Broiling.  
Compact grill.  
Baking stone operation.  
Roaster function.  
Dough proofing.  
Defrosting.  
Keeping warm.

Operation

Rotary knobs and TFT touch display operation.  
Clear text display in 25 languages.  
Information key with use indicators.  
Side-opening door opens up to 180° angle.

Features

Meat probe with automatic shut off (lower oven).  
Rotisserie spit (lower oven).  
Baking stone outlet.  
Actual temperature display.  
Super-quick preheating.  
Timer functions: cooking time, switch-off time, short-term timer, stopwatch, Sabbath mode.  
60 W halogen top light.  
10 W halogen light on the side.  
Enamel wire racks on the sidewalls with 5 rack levels, pyrolytic-safe.

Safety

Thermally insulated door with quadruple glazing.  
Child lock.  
Safety lock.  
Cooled door housing with temperature protection.

Cleaning

Pyrolytic self-cleaning.  
Gaggenau Clean-Enamel.  
Heated air cleaning catalyst.

Planning notes

Door hinge not reversible.  
The front of the appliance extends 1 7/8" from the cabinet front.  
The outer edge of the door handle extends 3 11/16" (94 mm) from the furniture cavity.  
Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance.  
When planning a corner solution, pay attention to the 90° door opening angle.  
To achieve the 21 5/8" installation depth, the connecting cable needs to follow the slanted edge on the lower right hand corner of the housing.  
The electrical outlet needs to be planned outside the cut-out niche.

Product Features

**Cooking mode**  
Baking stone function, Bottom heat, Bottom heating, 1/3 top heat., Conventional heat, Defrost, Dough proving setting, Full width broil, Half width broil, Hot Air, Hot air and 1/1 bottom heating, Hot air and 1/3 bottom heating, Hot air broiling, Hot Air-Eco, Roasting function, Top heat, Top heating, 1/3 bottom heat., warming

**Cooking method secondary cavity**  
Baking stone function, Bottom heating, Bottom heating, 1/3 top heat., Defrosting, Dough proving setting, Hot air, Hot air and 1/1 bottom heating, Hot air and 1/3 bottom heating, Hot Air-Eco, Hot air grill, Large-area grill, Roaster function, Small area grill, Top/bottom heating, Top heating, Top heating, 1/3 bottom heat., Warming

Integrated Cleaning system

Self Clean

Number of interior lights

2

Timer

Yes

Included accessories

2 x enamel baking tray,suit. pyrolytic clean, 1 x rotary spit, 2 x grill shelf, 2 x grill tub with grid, 1 x pluggable meat probe

Bake Element Wattages primary cavity (W)

1700

Broil Element Wattages primary cavity (W)

3900

Convection Element Wattages primary cavity (W)

Microwave Wattages (W)

Consumption and connection features

UPC code

825225911159

Product color

Stainless steel

Alternative colors available

Energy source

Electric

Watts (W)

9200

Current (A)

40

Volts (V)

208/220-240

Frequency (Hz)

60

Approval certificates

ETL

Power Cord Length

70 7/8"

Plug type

fixed connection

Required cutout size (HxWxD) (in)

56 1/8 " x 28 1/2 " x 21 11/16 "

Overall appliance dimensions (HxWxD) (in)

56 1/4 " x 29 5/8 " x 21 9/16 "

Product packaging dimensions (HxWxD) (in)

69.09 x 33.46 x 29.72

Net weight (lbs)

356

Gross weight (lbs)

380

2017-09-19

Page 1

Rating

Total rating 9.2 kW.  
Total Amps: 40 A.  
208 / 220 - 240 V / 60 Hz  
Connecting cable 70 7/8" without plug (hardwire required).

BX481611  
400 double oven  
Stainless steel-backed full glass door  
Width 30" (76 cm)  
Left-hinged  
Controls centered  
2017-09-19  
Page 2

