



#### Color Variants

**BX480611**  
**Stainless steel-backed full glass door**  
**Width 30" (76 cm)**

#### Included accessories

2 x enamel baking tray, suit. pyrolytic clean.  
 1 x rotary spit.  
 2 x grill shelf.  
 2 x grill tub with grid.  
 1 x pluggable meat probe.

#### Optional accessories

**BA028115**  
**Baking tray, enameled**  
**BA058115**  
**Heating element for baking stone and cast-iron roaster**  
**BA058133**  
**Baking stone**  
**BS020002**  
**Pizza peel, additional set of 2**  
**GN340230**  
**Non-stick aluminum cast-iron roaster**

#### Product Variants

**BX481611**  
**400 double oven**  
**Stainless steel-backed full glass door**  
**Width 30" (76 cm)**  
**Left-hinged**  
**Controls centered**

**BX480611**  
**400 double oven**  
**Stainless steel-backed full glass door**  
**Width 30" (76 cm)**  
**Right-hinged**  
**Controls centered**

**Pyrolytic self-cleaning**  
**Universal heating system with 17 heating modes, with meat probe, rotisserie spit and baking stone operation**  
**TFT touch display**  
**Electronic precision temperature control from 85° F - 550° F.**  
**2x 2.8 cu. ft. net volume**

#### Cooking modes

Convection.  
 Economy convection.  
 Top + bottom heat.  
 Top + 1/3 bottom heat.  
 Top heat.  
 1/3 top + bottom heat.  
 Bottom heat.  
 Convection + bottom heat.  
 Convection + 1/3 bottom heat.  
 Convection broiling.  
 Broiling.  
 Compact grill.  
 Baking stone operation.  
 Roaster function.  
 Dough proofing.  
 Defrosting.  
 Keeping warm.

#### Operation

Rotary knobs and TFT touch display operation.  
 Clear text display in 25 languages.  
 Information key with use indicators.  
 Side-opening door opens up to 180° angle.

#### Features

Meat probe with automatic shut off (lower oven).  
 Rotisserie spit (lower oven).  
 Baking stone outlet.  
 Actual temperature display.  
 Super-quick preheating.  
 Timer functions: cooking time, switch-off time, short-term timer, stopwatch, Sabbath mode.  
 60 W halogen top light.  
 10 W halogen light on the side.  
 Enamel wire racks on the sidewalls with 5 rack levels, pyrolytic-safe.

#### Safety

Thermally insulated door with quadruple glazing.  
 Child lock.  
 Safety lock.  
 Cooled door housing with temperature protection.

#### Cleaning

Pyrolytic self-cleaning.  
 Gaggenau Clean-Enamel.  
 Heated air cleaning catalyst.

#### Planning notes

Door hinge not reversible.  
 The front of the appliance extends 1 7/8" from the cabinet front.  
 The outer edge of the door handle extends 3 11/16" (94 mm) from the furniture cavity.  
 Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance.  
 When planning a corner solution, pay attention to the 90° door opening angle.  
 To achieve the 21 5/8" installation depth, the connecting cable needs to follow the slanted edge on the lower right hand corner of the housing.  
 The electrical outlet needs to be planned outside the cut-out niche.

#### Product Features

**Cooking mode**  
 Baking stone function, Bottom heat, Bottom heating, 1/3 top heat., Conventional heat, Defrost, Dough proving setting, Full width broil, Half width broil, Hot Air, Hot air and 1/1 bottom heating, Hot air and 1/3 bottom heating, Hot air broiling, Hot Air-Eco, Roasting function, Top heat, Top heating, 1/3 bottom heat., warming

#### Cooking method secondary cavity

Baking stone function, Bottom heating, Bottom heating, 1/3 top heat., Defrosting, Dough proving setting, Hot air, Hot air and 1/1 bottom heating, Hot air and 1/3 bottom heating, Hot Air-Eco, Hot air grill, Large-area grill, Roaster function, Small area grill, Top/bottom heating, Top heating, Top heating, 1/3 bottom heat., Warming

#### Integrated Cleaning system

Self Clean

#### Number of interior lights

2

#### Timer

Yes

#### Included accessories

2 x enamel baking tray, suit. pyrolytic clean, 1 x rotary spit, 2 x grill shelf, 2 x grill tub with grid, 1 x pluggable meat probe

#### Bake Element Wattages primary cavity (W)

1700

#### Broil Element Wattages primary cavity (W)

3900

#### Convection Element Wattages primary cavity (W)

1900

#### Microwave Wattages (W)

#### Consumption and connection features

##### UPC code

825225911142

##### Product color

Stainless steel

##### Alternative colors available

##### Energy source

Electric

##### Watts (W)

9200

##### Current (A)

40

##### Volts (V)

208/220-240

##### Frequency (Hz)

60

##### Approval certificates

ETL

##### Power Cord Length

70 7/8"

##### Plug type

fixed connection

##### Required cutout size (HxWxD) (in)

56 1/8 " x 28 1/2 " x 21 11/16 "

##### Overall appliance dimensions (HxWxD) (in)

56 1/4 " x 29 5/8 " x 21 9/16 "

##### Product packaging dimensions (HxWxD) (in)

69.48 x 33.07 x 29.72

##### Net weight (lbs)

329

##### Gross weight (lbs)

353

##### 2017-09-19

##### Page 1

## Rating

Total rating 9.2 kW.

Total Amps: 40 A.

208 / 220 - 240 V / 60 Hz

Connecting cable 70 7/8" without plug (hardwire required).

BX480611  
400 double oven  
Stainless steel-backed full glass door  
Width 30" (76 cm)  
Right-hinged  
Controls centered  
2017-09-19  
Page 2

