



BO480611
400 series single oven
Stainless steel-backed full glass door
Width 30" (76 cm)
Right-hinged
controls on top

Handleless door / automatic door opening
Pyrolytic self-cleaning
Universal heating system with 17 heating modes, with meat probe, rotisserie spit and baking stone operation
TFT touch display
Electronic precision temperature control from 85° F - 550° F.
4.5 cu.ft. net volume

Cooking modes

Convection.
 Economy convection.
 Top + bottom heat.
 Top + 1/3 bottom heat.
 Top heat.
 1/3 top + bottom heat.
 Bottom heat.
 Convection + bottom heat.
 Convection + 1/3 bottom heat.
 Convection broiling.
 Broiling.
 Compact grill.
 Baking stone operation.
 Roaster function.
 Dough proofing.
 Defrosting.
 Keeping warm.

Operation

Automatic door opening.
 Rotary knobs and TFT touch display operation.
 Clear text display in 25 languages.
 Option to save individual recipes (incl. meat probe)
 Information key with use indicators.
 Side-opening door opens up to 180° angle.

Features

Meat probe with automatic shut-off.
 Rotisserie spit.
 Baking stone outlet.
 Actual temperature display.
 Super-quick preheating.
 Timer functions: cooking time, switch-off time, short-term timer, stopwatch, Sabbath mode.
 60 W halogen top light.
 2 x 10 W halogen light on the side.
 Enamel wire racks on the sidewalls with 5 rack levels, pyrolytic-safe.

Safety

Thermally insulated door with quadruple glazing.
 Child lock.
 Safety lock.
 Cooled door housing with temperature protection.

Cleaning

Pyrolytic self-cleaning.
 Gaggenau Clean-Enamel.
 Heated air cleaning catalyst.

Planning notes

Door hinge not reversible.
 The front of the appliance extends 1 7/8" from the cabinet front.
 When handle (optional accessory) is installed, the outer edge of the door handle extends 3 11/16" (94mm) from the cabinet front.
 Consider the overhang, incl. the door handle where applicable, when planning to open drawers next to the appliance. Plan a gap of at least 3/16" between the appliance and adjacent cabinets.

Product Features

Cooking mode
 Baking stone function, Bottom heat, Bottom heating, 1/3 top heat., Conventional heat, Defrost, Dough proving setting, Full width broil, Half width broil, Hot Air, Hot air and 1/1 bottom heating, Hot air and 1/3 bottom heating, Hot air broiling, Hot Air-Eco, Roasting function, Top heat, Top heating, 1/3 bottom heat., warming

Integrated Cleaning system

Self Clean

Interior Lights - primary cavity

3

Pull-out system

Accessory

Timer settings

Alarm, Off, On, timer

Included accessories

1 x enamel baking tray, suit. pyrolytic clean, 1 x rotary spit, 1 x grill shelf, 1 x grill tub with grid, 1 x pluggable meat probe

Bake Element Wattages primary cavity (W)

1700

Broil Element Wattages primary cavity (W)

3900

Convection Element Wattages primary cavity (W)

1900

Microwave Wattages (W)

Drawer wattage (W)

Consumption and connection features

UPC code

825225911166

Product color

Stainless steel

Alternative colors available

Energy source

Electric

Watts (W)

5520

Current (A)

25

Volts (V)

208/220-240

Frequency (Hz)

60

Approval certificates

ETL

Power Cord Length

47 1/4

Plug type

fixed connection

Required cutout size (HxWxD) (in)

26 3/16 " x 28 1/2 " x 21 11/16 "

Product packaging dimensions (HxWxD) (in)

33 7/8 x 33 7/16 x 29 15/16

Net weight (lbs)

175

Gross weight (lbs)

189

2017-09-19

Page 1

When planning a corner solution, pay attention to the 90° door opening angle.

To achieve the 21 5/8" installation depth, the connecting cable needs to follow the slanted edge on the lower right hand corner of the housing. The electrical outlet needs to be planned outside the cut-out niche.

Rating

Total rating 5.5 kW.

Total Amps: 25 A.

208 / 220 - 240 V / 60 Hz

Connecting cable 47 1/4 without plug (hardwire required).

Color Variants

BO480611
Stainless steel-backed full glass door
Width 30" (76 cm)

Included accessories

1 x enamel baking tray, suit. pyrolytic clean.
 1 x rotary spit.
 1 x grill shelf.
 1 x grill tub with grid.
 1 x pluggable meat probe.

Optional accessories

BA028115
Baking tray, enameled
BA058115
Heating element for baking stone and cast-iron roaster
BA058133
Baking stone
BS020002
Pizza peel, additional set of 2
GN340230
Non-stick aluminum cast-iron roaster

Installation Accessories

BA478110
Handle bar, stainless steel

Product Variants

BO481611
400 series single oven
Stainless steel-backed full glass door
Width 30" (76 cm)
Left-hinged
controls on top