

**Color Variants** 

BOP250611

Full glass door in Gaggenau Metallic Width 24" (60 cm)

### Included accessories

1 x enamel baking trav. suit. pyrolitic clean.

1 x grill shelf.

1 x grill tub with grid.

1 x pluggable meat probe

#### Optional accessories

BA016165

Pull-out system BA026115

Baking tray, enameled

BA036165

Wire rack, chromium-plated

BA056115

Heating element for baking stone and cast-iron roaster

BA056133

Baking stone

BA226105

Broil pan, enameled

BS020002

Pizza peel, additional set of 2

GN340230

Non-stick aluminum cast-iron roaster

**Product Variants** 

BOP251611 200 series single oven Full glass door in Gaggenau Metallic Width 24" (60 cm) Left-hinged

BOP250611 200 series single oven

Full glass door in Gaggenau Metallic

Width 24" (60 cm)

Right-hinged

Flush installation Pyrolytic self-cleaning system Universal heating system with 13 heating modes, with meat probe and baking stone operation TFT touch display Electronic temperature control from 30 °C to 300 °C Net volume 76 litres

## Cooking modes

Convection.

Economy convection.

Top + bottom heat.

Top heat.

Bottom heat.

Convection + bottom heat.

Convection broiling.

Broiling.

Economy broiling.

Baking stone operation.

Roaster operation.

Dough proofing.

Defrosting.

#### Operation

Rotary knob and TFT touch display

Clear text display in 25 languages. Option to save 50 individual recipes (incl. meat probe)

Information key with use indicators. Side-opening door opens up to 110° angle.

#### **Features**

Meat probe with automatic shut-off function.

Baking stone outlet. Actual temperature display. Super-quick preheating.

Timer functions: cooking time. switch-off time, short-term timer. stopwatch.

60 W halogen light on the top. Enameled side rack supports with 4 rack levels, pyrolytic-safe.

## Safety

Thermally insulated door with quintuple alazina.

Child lock

Safety shut-off. Cooled housing with temperature protection.

# Cleaning

Pyrolytic self-cleaning. Gaggenau Clean-Enamel. Heated air cleaning catalyst.

## Planning notes

Door hinge not reversible. The door panel front of the appliance extends 13/16" from the cabinet front. The outer edge of the door handle extends 2 13/16" from the cabinet front.

Necessary lateral gap between appliance door and cabinet front of min. 3/16".

Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance.

When planning a corner solution, pay attention to the 110° door opening

For installation underneath cooktops: Distance between the underside of the cooktop and the top edge of the oven cavity: min. 9/16". The

planning notes for the cooktops (particularly regarding ventilation, gas/ electric connection) must be taken into

#### **Product Features**

#### Cooking mode

Baking stone function, Bottom heat, Conventional heat, Defrost, Dough proving setting, Full width broil, Half width broil, Hot Air, Hot air and 1/1 bottom heating, Hot air broiling, Hot Air-Eco. Roasting function, Top heat

Integrated Cleaning system

Self Clean

Interior Lights - primary cavity

Pull-out system

Accessor

Timer settings

Alarm, Off, On, timer

# Included accessories

1 x enamel baking tray, suit. pyrolitic clean, 1 x grill shelf, 1 x grill tub with grid, 1 x pluggable meat probe

Bake Element Wattages primary cavity

**Broil Element Wattages primary cavity** 

3000

Convection Element Wattages primary cavity (W)

2100

Microwave Wattages (W)

Drawer wattage (W)

### Consumption and connection features

UPC code

825225929116

Product color

Stainless steel

Alternative colors available

**Energy source** Electric

Watts (W)

Current (A)

Volts (V)

208/220-240

Frequency (Hz)

Approval certificates CSA, ETL, UL

Power Cord Length

Plug type fixed connection

Required cutout size (HxWxD) (in)

23 1/4" x 22 1/16" x 21 11/16

Product packaging dimensions (HxWxD) (in)

30 11/16" x 26 3/4" x 29 15/16"

Net weight (lbs)

Gross weight (lbs)

2019-07-10 Page 1

To achieve the 21 5/8" (550 mm) installation depth, the connection cable needs to follow the slanted edge on the corner of the housing. Plan a power outlet outside of the cut-out niche.

#### Rating

Energy efficiency class A. Total rating 4.0 kW. Total Amps: 17 A. 120 V / 60 Hz

Plan for a 4' long connecting cable without plug (hardwire required).



BOP250611 200 series single oven Full glass door in Gaggenau Metallic Width 24" (60 cm) Right-hinged

2019-07-10 Page 2

