



Color Variants

BOP251611
Full glass door in Gaggenau Metallic
Width 24" (60 cm)

Included accessories

- 1 x enamel baking tray.
- suit. pyrolytic clean.
- 1 x grill shelf.
- 1 x grill tub with grid.
- 1 x pluggable meat probe.

Optional accessories

- BA016165
- Pull-out system
- BA026115
- Baking tray, enameled
- BA036165
- Wire rack, chromium-plated
- BA056115
- Heating element for baking stone and cast-iron roaster
- BA056133
- Baking stone
- BA226105
- Broil pan, enameled
- BS020002
- Pizza peel, additional set of 2
- GN340230
- Non-stick aluminum cast-iron roaster

Product Variants

BOP250611
200 series single oven
Full glass door in Gaggenau Metallic
Width 24" (60 cm)
Right-hinged

BOP251611
200 series single oven
Full glass door in Gaggenau Metallic
Width 24" (60 cm)
Left-hinged

Flush installation
Pyrolytic self-cleaning system
Universal heating system with 13 heating modes, with meat probe and baking stone operation
TFT touch display
Electronic temperature control from 30 °C to 300 °C
Net volume 76 litres

Cooking modes

- Convection.
- Economy convection.
- Top + bottom heat.
- Top heat.
- Bottom heat.
- Convection + bottom heat.
- Convection broiling.
- Broiling.
- Economy broiling.
- Baking stone operation.
- Roaster operation.
- Dough proofing.
- Defrosting.

Operation

- Rotary knob and TFT touch display operation.
- Clear text display in 25 languages.
- Option to save 50 individual recipes (incl. meat probe)
- Information key with use indicators.
- Side-opening door opens up to 110° angle.

Features

- Meat probe with automatic shut-off function.
- Baking stone outlet.
- Actual temperature display.
- Super-quick preheating.
- Timer functions: cooking time, switch-off time, short-term timer, stopwatch.
- 60 W halogen light on the top.
- Enameled side rack supports with 4 rack levels, pyrolytic-safe.

Safety

- Thermally insulated door with quintuple glazing.
- Child lock.
- Safety shut-off.
- Cooled housing with temperature protection.

Cleaning

- Pyrolytic self-cleaning.
- Gaggenau Clean-Enamel.
- Heated air cleaning catalyst.

Planning notes

- Door hinge not reversible.
- The door panel front of the appliance extends 13/16" from the cabinet front.
- The outer edge of the door handle extends 2 13/16" from the cabinet front.
- Necessary lateral gap between appliance door and cabinet front of min. 3/16".
- Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance.
- When planning a corner solution, pay attention to the 110° door opening angle.
- For installation underneath cooktops: Distance between the underside of the cooktop and the top edge of the oven cavity: min. 9/16". The planning notes for the cooktops (particularly regarding ventilation, gas/ electric connection) must be taken into

Product Features

- Cooking mode
- Baking stone function, Bottom heat, Conventional heat, Defrost, Dough proving setting, Full width broil, Half width broil, Hot Air, Hot air and 1/1 bottom heating, Hot air broiling, Hot Air-Eco, Roasting function, Top heat
- Integrated Cleaning system
- Self Clean
- Interior Lights - primary cavity
- 1
- Pull-out system
- Accessory
- Timer settings
- Alarm, Off, On, timer
- Included accessories
- 1 x enamel baking tray,suit. pyrolytic clean, 1 x grill shelf, 1 x grill tub with grid, 1 x pluggable meat probe
- Bake Element Wattages primary cavity (W)
- 1300
- Broil Element Wattages primary cavity (W)
- 3000
- Convection Element Wattages primary cavity (W)
- 2100
- Microwave Wattages (W)
- Drawer wattage (W)

Consumption and connection features

- UPC code
- 825225929123
- Product color
- Stainless steel
- Alternative colors available
- Energy source
- Electric
- Watts (W)
- 4030
- Current (A)
- 17
- Volts (V)
- 208/220-240
- Frequency (Hz)
- 60
- Approval certificates
- CSA, ETL, UL
- Power Cord Length
- 39 3/8
- Plug type
- fixed connection
- Required cutout size (HxWxD) (in)
- 23 1/4" x 22 1/16" x 21 11/16"
- Product packaging dimensions (HxWxD) (in)
- 30 11/16" x 26 3/4" x 29 15/16"
- Net weight (lbs)
- 123
- Gross weight (lbs)
- 132
- 2019-07-10
- Page 1

To achieve the 21 5/8" (550 mm) installation depth, the connection cable needs to follow the slanted edge on the corner of the housing. Plan a power outlet outside of the cut-out niche.

Rating

- Energy efficiency class A.
- Total rating 4.0 kW.
- Total Amps: 17 A.
- 120 V / 60 Hz
- Plan for a 4' long connecting cable without plug (hardwire required).

