

FULGOR

MILANO

700 Series 30" Self Cleaning Double Wall Oven

F7DP30W1



Series		700	
Type		PYRO	
Size		30"x30"	
Colour		WHITE	
Stainless Steel Aesthetics		Embossed window profile with bended edges	
Oven Type		Multifunction 2 Fans (True Euro Convection)	
Temperature Regulation		Full Electronic	
Key	Functions		
LIGHT	LIGHT		Upper/Lower
DEHIDR	DEFROST		Upper/Lower
	DEHYDRATE		Upper/Lower
KEEP WARM	WARM		Upper/Lower
	WARM +		Upper/Lower
BAKE	BAKE		Upper/Lower
	ROAST		Upper/Lower
	TRUE CONVECTION BAKE		Upper/Lower
CONV.	CONVECTION ROAST		Upper/Lower
	CONVECTION BAKE		Upper/Lower
	CONVECTION GRILL		Upper/Lower
	CONVECTION BROIL		Upper/Lower
PIZZA	PIZZA		Upper/Lower
BROIL	BROIL LEVELS		Upper/Lower
SELF C.	SELF CLEAN		Upper/Lower
Control Panel		MODULAR - Electronic	
Control type		TFT 3,5"	
Display		●	
Menu Recipes			

FULGOR

MILANO

Commands	Full Touch
Language	11
Special Features	
Demo Mode	•
Brightness setting (ON condition)	•
Brightness setting (OFF condition)	•
Beeper volume setting	•
Date format	•
Automatic Fast Preheat	•
Classic PIZZA function 310°C	•
Child Door Lock	•
Commands Lock	•
Sabbath mode	•
12/24 hours clock format	•
°C/°F degree unit	•
Door micro switch	•
Event logs (for Service)	•
Oven Door(s)	
Oven Glass Window	Large See Through Glass
Door Cooling System	4 Pane Heat Resistant Glass
Door Hinges	Heavy Duty Steady Tilt
Oven Cavity	
Gross Capacity (cbft)	4.4
Net Capacity (cbft)	4.1
Cavity Enameling Colour	Black
Rack Positions	6
Oven Lights	3 or 2 x 20W Halogen
Broil Upper Heating Element	3500 W (240V)
Upper Auxiliary Element Wattage	1032W (240V)
Concealed Bake Lower Heating Element	3000 W (240V)
Convection Element Wattage	2x1300W (240V)
Oven Accessories	
Chromed racks	•
Enameled Grill set (basin + anti splash)	•
Telescopic chromed rack	•
Meat probe	• Upper Oven Only
Dimensions/Weight - (In or Lbs)	
Overall dim - width	29 11/16" (754mm)
Overall dim - height	50 13/16" (1290mm)
Overall dim - depth	24" (610mm)
Cutout - width	28 7/16" (722mm)
Cutout - height (min)	50" (1270mm)
Cutout - depth (min)	23 1/4" (590mm)
Power / Ratings (208/240 V, 60 Hz)	
KW/Amps rating at 240V, 60Hz	7.50kW - 31.2A
KW/Amps rating at 208V, 60Hz	6.30kW - 30.3A
Cable + Conduit	•
INSTRUCTIONS FOR USE	
Use & Care Manual	EN, SP, FR
Installation Manual	EN, SP, FR