

# RGPC 600 S

Parallel Power Delivery for  
Load Impedance matching

## New and Improved! Parallel Power Delivery Model

The RGPC 600 S (available in black or silver) with its beautiful award winning Art Deco design, switchable backlit logo (blue, orange or off) is available as a stand alone or rack mounted. With three duplex outlets the 600 S is large enough to power most midsize home theater and two channel systems.

To receive the maximum performances install the RGPC 600S as close as possible to the AV equipment. The RGPC 600 S, utilizes Balanced Surge Protection Design (SPD) to ensure Bidirectional Protection and Reduced Ground Interference.

### Features & Benefits

- High Current on Demand
- Balanced AC Surge Protection
- Resettable Circuit Breaker
- Rack mountable with optional self kit.
- Compatible with UL1449 3rd edition for Type 3 locations
- Orange or Blue Illuminated Front – rear switch

### Applications

- All AV equipment
- Midsize Home Theaters
- Installations with Multiple Circuits
- For Crisp and Flawless AV Experience



### Specifications

Dimensions (WHD)

Net weight

Mounting

Rack Mountable

Power Cord (Detachable)

Outlets

Input Voltage

Output Voltage

Frequency

Output Power

Technology

AC Surge Protection (type 3 locations)

Efficiency

Cooling

Storage Temperature

Operating Temperature

### 600 S 120/120

8.75 x 5.25(w/feet 6.2) x 11

30 lbs

Stand alone Floor / Shelf

w/ mounting kits

6 ft, 12 AWG, NEMA 5-15P

6 (NEMA 5-20R)

120 VAC

120 VAC

60 HZ

12 A (1,440 Watts)

Parallel Power Delivery

Balanced

>99%

Convectional

-40° C to 85° C

-40° C to 65° C

### 600 S 240/240

8.75 x 5.25(w/feet 6.2) x 11

30 lbs

Stand alone Floor / Shelf

w/ mounting kits

6 ft, 12 AWG, Euro Schuko Plug

4 Euro Shuko

240 VAC

240 VAC

50 HZ

12 A (2,880 Watts)

Parallel Power Delivery

Balanced

>99%

Convectional

-40° C to 85° C

-40° C to 65° C

