

DÔME

Product sheet



- Focal sound in compact and sophisticated design
- True 2 way acoustic loudspeaker
- Integration versatility on table, on wall, on ceiling, on optional stand
- High gloss laquered aluminum cabinet
- Made in France
- Available in 2.0, 2.1 and 5.1 systems
- Optional color grilles red, blue and yellow

	Dôme speaker	Dôme subwoofer
Type	2-way compact sealed speaker	Active bass-reflex subwoofer
Drivers	4" (10cm) Polyglass mid-bass, 1" (25mm) Al/Mg inverted dome tweeter	8" (21cm) Polyflex woofer
Frequency response (±3dB)	80Hz - 28 kHz	42Hz - 200Hz
Low frequency point (-6dB)	72Hz	35Hz
Sensitivity [2.83V/1m]	88dB	Variable crossover 50Hz to 200Hz, Phase inverter 0°/180°, Autopower, LFE input
Nominal impedance	8 ohms	
Minimum impedance	4 ohms	
Crossover frequency	2500Hz	
Recommended amplifier power	25 - 100W	100W BASH® amplifier
Dimensions (HxWxD)	6 ^{3/4} x 5 ^{11/16} x 5 ^{5/8} " (172x144x143mm)	15 ^{3/4} x 10 ^{7/8} x 10 ^{7/8} " (400x276x276mm)
Net weight	4.2lbs (1.9kg)	18lbs (8.2kg)



FOCAL
the Spirit of Sound