

Variable-speed rotary control designed to resist the effects of heat and moisture.

Model Numbers:



Large, easy-to-remove baffle filter and grease rail.



Bright halogen lighting.



A variable-speed rotary control enables infinite blower speed adjustment.

Hood Sizes	
Widths	36", 42", 48"
Depths	28-3/8"
Finish	
Stocked	Corrosion Resistant Stainless Steel (Grade 304)
Special Order	Not Available
Features	
Lighting Type	Halogen, MR16, GU10-50W
Number of Lamps	2
Lighting Levels	1
Lighting Lamps Included	Yes
Control Type	Infinite Speed Rotary, Illuminated ON/OFF with Last Memory Setting
Control Features	Heat Sentry [™]
Remote Control	Not Available
Filter Type	Baffle
Non-ducted Capability	No

Hood Blower Options (Blower sold separately)

Prover sold separately,		
Internal Modular	P12NA	
Max Blower CFM*	1300	
Sones Normal Setting**	2.0	


*MAX Blower CFM indicates the performance of the hood blower in open air.
**Normal setting corresponds to speed 1.

Installation Requirements

Amps @ 120V	7.0
Electrical Connection	Direct Wire
Duct Size: Internal Blower	10"
Duct Direction	Vertical
Backdraft Damper	Not Included

Accessories

None



Installation height above the cooking surface: 36"

For more details or HVI rated performance for this model see the product specifications sheet found at www.BESTRangeHoods.com





Performance is a beautiful thing.

It can be subtle or bold. It can take months or years to hone. Then impress you in an instant.

A great performance gives the audience exactly what they want and more than they ever imagined. And it inspires everyone and everything around it to be better.

At **BEST**, we make high performance range hoods that perform beautifully. Astonishingly quiet. Impressively effective. Remarkably efficient. And perfectly suited for the most distinguished kitchens.

Whether it's the centerpiece of the room or letting its surroundings shine, **BEST** is where high-end performance inspires.

