

Power packs for custom application—cabinet mount.

Electronic push button controls with LED.

Four ventilation speeds.

Two-intensity exclusive PURLED™ lighting: two 5.5 watt LED modules (included).

5-minute delay function.

Dishwasher-safe low-profile baffle filters.

Filter maintenance indicator.

Heat Sentry™ detects excessive heat and adjusts speed to high automatically.

Model Numbers

CC65I28SB


CC67128SE




PURLED™ light system boosts light output, distributes light better and improves energy-efficiency.



Backlit electronic push button controls.



Easy-to-install low-profile baffle filters.



Protect cabinetry from steam and grease with stainless steel liners that provide a custom fit.

| Hood Sizes | | | |
|-------------------------|---|--|--|
| Widths | 28-1/8" | | |
| Depth | 14-3/4" | | |
| Finish | | | |
| Stocked | Brushed Stainless Steel (Grade 430) | | |
| Special Order | Not Available | | |
| Features | | | |
| Lighting Type | PURLED™ 5.5 watt, 1100 Lumens, 3000K | | |
| Number of Lamps | 2 | | |
| Lighting Levels | 2 | | |
| Lighting Lamps Included | Yes | | |
| Control Type | 4-speed Electronic Push Button | | |
| Control Features | Heat Sentry™, Delay-off | | |
| Remote Control | Not Available | | |
| Filter Type | Mini Baffle | | |
| Non-ducted Capability | No | | |

Hood Blower Included

| Internal | CC65 | CC67 | |
|------------------------|------|------|--|
| Max Blower CFM* | 650 | 1300 | |
| Sones Normal Setting** | 1.1 | 1.5 | |

^{*}MAX Blower CFM indicates the performance of the hood blower in open air.
**Normal setting corresponds to speed 1.

Accessories

Custom Liners 30"-ALCC630SB, 36"-ALCC636SB, 42"-ALCC642SB

CFM Reducer Kit ARP310 (for use with CC65)


Installation Requirements

Amps @ 120V 6.0/9.5

Electrical Connection Direct Wire

Duct Size: Internal Blower 3-1/4" x 10" V or H
10" round / Vertical only

Backdraft Damper Included



Installation height above the cooking surface: 24"-30"

For more details or HVI rated performance for this model see the product specifications sheet found at www.BESTRangeHoods.com

Liners for CC6

- Brushed Standard Stainless Steel finish
- 28-1/2", 34-1/2" and 40-1/2" widths
- Adjustable depths with backboard 16" to 17-13/16"
- Adjustable depths without backboard 16-3/8" to 18"





Performance is a beautiful thing.

It can be subtle or bold. It can take months or years to hone. Then impress you in an instant.

A great performance gives the audience exactly what they want and more than they ever imagined. And it inspires everyone and everything around it to be better.

At **BEST**, we make high performance range hoods that perform beautifully. Astonishingly quiet. Impressively effective. Remarkably efficient. And perfectly suited for the most distinguished kitchens.

Whether it's the centerpiece of the room or letting its surroundings shine, **BEST** is where high-end performance inspires.

