

G 7106 SCU

Built-under dishwasher
with 3D MultiFlex Tray for maximum convenience.



- Perfect results in less than one hour – QuickIntense Wash
- Everything completely dry – AutoOpen drying
- Very easy door opening and closing – ComfortClose
- Versatile and secure – ExtraComfort basket design

EAN: 4002516261445 / Material number: 11387580 / Old Material Number: 21710637USA

Construction type	
Pre-finished	•
Design	
Fascia color	Clean Touch Steel
Fascia panel version	Straight fascia
Control type	Programme selector button
Control panel	1-line text display
Display color	White
MultiLingua	•
Convenience	
Door closing aid	ComfortClose
Operating noise dB(A) re 1 pW	43
Countdown indicator	•
Delay start up to 24 hours	•
In-operation indication	Display
Display language selection	•
Efficiency and sustainability	
EcoFeedback	•
EcoPower Technology	•
Proven hygiene	•
Hot water connection	•
Half load	•
ENERGY STAR® Most Efficient	•
Gentle on dishware/glass	
Fresh water dishwasher	•
AutoOpen drying	•
SensorDry	•
Active condensation drying	•
Perfect GlassCare	•
Dishwashing programs	
QuickIntenseWash	•
Normal	•
Pots & Pans	•
IntenseWash	•
China & Crystal	•
SaniWash	•
Rinse & Hold	•
Rinse options	
IntenseZone	•
Express	•
Extra Clean	•
Extra dry	•
Basket design	
Cutlery loading	3D MultiFlex tray
FlexCare glass holder	2
FlexCare cup rack	2
Basket design	ExtraComfort
Safety	
Waterproof system	•
Check filter saturation indicator	•

G 7106 SCU

Built-under dishwasher

with 3D MultiFlex Tray for maximum convenience.



EAN: 4002516261445 / Material number: 11387580 / Old Material Number: 21710637USA

Child Safety lock

•

Technical data

Niche width min in in.(mm)	23 5/8 (600)
Niche width max in in.(mm)	23 5/8 (600)
Niche height min in in.(mm)	33 3/4 (855)
Niche height max in in.(mm)	36 1/4 (920)
Niche depth in in.(mm)	22 1/2 (570)
Appliance width in in.(mm)	23 5/8 (598)
Appliance height in in.(mm)	33 3/4 (855)
Appliance depth in in.(mm)	22 1/2 (570)
Appliance depth with door open in in.(cm)	47 1/2 (120.5)
Net weight in lbs. (kg)	107 (48.5)
Total connected load in kW	1.40
Voltage in V	120
Fuse rating in A	15
Number of phases	1
Electrical frequency standard	60
Length of water inlet hose in ft (m)	5 (1.50)
Length of water drain hose in ft (m)	5 (1.50)
Length of electrical wire in ft (m)	4 (1.20)

Available display languages

Available display languages via MultiLingua

deutsch, english, español,
français, português,