

PDR 908 HP [EL]

Professional heat-pump dryer

With very low energy consumption and short cycle times. Load capacity 18 (8.0) US pound.



- Drum volume 4.59 (130) Cubic ft, load capacity 18 (8.0) US pound
- Tested for intensive use – unique Miele quality
- Top convenience with full-touch color display – M Touch Flex
- Precision drying of all fabrics – PerfectDry

EAN: 4002516195924 / material number: 11204490

Model and design	
Design	Front-loader, stackable
Linie	Performance Plus
Front	Stainless steel
Load in lbs. (kg)	18 (8.0)
Drum volume in gal (l)	4.59 (130)
Drying system	Heat pump
Door opening [Ø] in inches (mm)	14 5/8 (370)
Door opening angle in degrees	167
Door hinging	left
Stainless steel honeycomb drum	•
Application	
Suitable for the hotel and catering industry	•
Suitable for retirement and care homes	•
Suitable for facility management	•
Suitable for laundrettes	•
Suitable for residential homes and apartments	•
Suitable for dry cleaners	•
Suitable for commercial laundries	•
Suitable for small businesses	•
Suitable for universities, nurseries and schools	•
Suitable for hospitals	•
Suitable for camp sites	•
Suitable for sports clubs	•
Suitable for beauty salons, spas and fitness centers	•
Suitable for doctors' and dentists' practices	•
Suitable for the petrochemical industry	•
Suitable for the food-processing industry	•
Suitable for amusement parks and holiday complexes	•
Suitable for public/community care facilities	•
Performance data	
Maximum evaporation capacity in l/hour and gal. qts./hour	2.6
Specific energy consumption for cottons/Normal drying, residual moisture 48% in kWh/kg	0.20
Specific energy consumption for mixed fabric/Normal drying, residual moisture 40% in kWh/kg	0.17
Program cycle in min.	88
Program cycle time for cottons/Normal drying, residual moisture 48% in min.	88
Program duration for mixed fabrics/Normal drying program with residual moisture at 40 % in minutes	76
Controls	
Control system	M Touch Flex
Programmability	programmable
Program controls	Residual moisture controlled
Max. delay start in h	24
Countdown indicator	•
Program sequence indicator	•
Language can be selected easily at any time	•

PDR 908 HP [EL]

Professional heat-pump dryer

With very low energy consumption and short cycle times. Load capacity 18 (8.0) US pound.



Standard electrical connection	
Type of heating	Heat pump
Electrical connection	2 AC 208-240V 60HZ
Total connected load in kW	1.20
Fuse rating in A	30
NEMA plug: Twist Lock L6-30	•
Dimensions and weight	
External dimensions, net height in inches	33 1/2 (850)
External dimensions, net width in inches	23 7/8 (605)
External dimensions, net depth in inches	30 5/8 (777)
External dimensions, gross height in inches	37 1/8 (940)
External dimensions, gross width in inches	26 (660)
External dimensions, gross depth in inches	32 3/8 (820)
Net weight in lbs. (kg)	159 (72)
Gross weight in lbs.	172 (78)
Maximum floor loading in p/force	920
Emission levels	
Emissions - sound pressure at workplace	<70 dB(A) re 20 µPa
Heat dissipation into the room in btu/h (MJ/h)	3.60
Features	
Intelligent drum reversal	•
Axial airflow	•
Fluff filter in the door	•
Low-maintenance heat exchanger filter system	•
PerfectDry	•
SoftLift drum ribs	•
Gentle tumble function	•
Condensed water drainage	•
Communication slot	•
Drying basket (optional)	•
Drum lighting	•
Appliance-independent accessories	•
Efficiency and sustainability	
Recycling rate in %	95
Connection options	
Payment system (optional)	•
Optical interface for service access	•
Test certificates and symbols	
WEEE	•
c ETL US	•
Contains fluorinated greenhouse gases	•
Hermetically sealed system	•
Coolant	R134a
Refrigerant quantity in lbs	1
Refrigerant global warming potential in lbs CO ₂ e	1,430
Appliance global warming potential in lbs CO ₂ e	844