

## PG 8056 U [208V]

Built-under fresh water dishwasher

ADA compliant, with baskets for hotels, restaurants and catering companies.



- Max. cleaning performance\*: 380 plates/h or 20 baskets/h
- Flexible processing of two wire or plastic baskets per cycle
- Simple to operate thanks to clear fascia panel design
- Always the right program - item-specific solutions
- First-class results thanks to fresh water system

EAN: 4002515460887 / material number: 09862620

<b>Model and design</b>	
Design	Built-under dishwasher
Line	Professional
Wash system	Fresh water
Number of levels	2
Front	Stainless steel
Lid	Stainless steel
Side walls	Stainless steel
Convertible to a freestanding appliance	Stand 1-80, stainless steel
Drying	without
<b>Application</b>	
Suitable for small restaurants/bars	•
Suitable for hospitality industry	•
Suitable for Bed & Breakfast	•
Suitable for canteens	•
Suitable for small businesses	•
Suitable for fast food restaurants	•
Suitable for sports clubs	•
Suitable for fire brigades and rescue services	•
<b>Performance data</b>	
Circulation pump, Qmax in gal/min (l/min)	0.0 (390)
Shortest program duration in min.	6
Maximum final rinse temperature in °F (°C)	159 (70)
Cleaning performance, plates/h	380
Cleaning performance, baskets/h	20
Possible to wash plastic baskets on two levels	•
Tested operating hours	15,000
<b>Controls</b>	
Control system	TouchControl
Program selection	Touch on Metal
Max. delay start in h	24
Countdown indicator	•
Program sequence indicator	•
Choice of display language	•
Language-neutral operation	•
<b>Standard electrical connection</b>	
Electrical connection	2 PH. 208V 60HZ
Heater rating in kW	5.40
Total connected load in kW	5.80
Fuse rating in A	30
Length of connection wire in ft (m)	5 (1.70)
<b>Possible voltage variant 1</b>	
Electrical connection	3 PH. 208V 60HZ
Heater rating in kW	5.4
Total connected load in kW	5.80
Fuse rating in A	20

PG 8056 U [208V]

Built-under fresh water dishwasher

ADA compliant, with baskets for hotels, restaurants and catering companies.



<b>Water connection/drainage</b>	
Cold water [number]	1
Hot water [number]	1
Required flow pressure in bar	0,40-10,00
Drain hose [DN]	22
Maximum delivery head for drain pump in inches (cm)	39 3/8 (100)
Integrated water softener	•
Maximum water hardness in gpg (mmol/l)	0.000 (10.70)
Water consumption per wash cycle in gal (l)	2.1 (8.00)
<b>Dimensions and weight</b>	
External dimensions, net height in inches	32 3/8 (820)
External dimensions, net width in inches	23 5/8 (598)
External dimensions, net depth in inches	22 7/8 (580)
External dimensions, gross height in inches	37 1/8 (940)
External dimensions, gross width in inches	26 5/8 (675)
External dimensions, gross depth in inches	29 3/8 (745)
Usable space in wash cabinet, width in inches (mm)	20 7/8 (530)
Usable space in wash cabinet, height in inches (mm)	22 1/8 (559)
Usable space in wash cabinet, depth of upper basket in inches (mm)	18 3/4 (474)
Usable space in wash cabinet, depth of lower basket in inches (mm)	20 (505)
In-feed height above floor in inches (mm)	8 5/8 (216)
Net weight in lbs.	139 (63)
Gross weight in lbs.	153 (69)
Maximum floor loading in p/force	1,200
<b>Emission levels</b>	
Emission sound pressure level in workplace (LpA)	47 dB(A) re 20 µPa
Sound power (LwA) in dB(A) re 1 pW	59.0
Heat dissipation into the room in btu/h (MJ/h)	1.08
<b>Basket design</b>	
1 x O 891 upper basket for cups	•
1 x U 890 lower basket for inserts	•
1 x E 810 insert for dessert plates	•
2 x E 816 inserts for plates	•
2 x E 165 inserts for cutlery	•
Height-adjustable upper basket	•
<b>Features</b>	
1 Combi dispenser/door for powder and liquid media	•
Wash cabinet made from high-quality stainless steel.	•
In-door salt container	•
Perfect GlassCare	•
Adjustable final rinse temperature	•
Adjustable wash temperature	•
Adjustable rinse time	•
Optical interface	•
A wide range of accessories (optional)	•
<b>Connection options</b>	
External dispensing module for liquid cleaning agent	•

PG 8056 U [208V]

Built-under fresh water dishwasher

ADA compliant, with baskets for hotels, restaurants and catering companies.



Test certificates and symbols	
CE	•
VDE	•
Interference suppression	•
DIN 10512	•
EN 1717	•
EMC	•
ADA compliant	•
Complies with Machinery Directive 2006/4 2/EC	•