

## PG 8056 U [240V]

Built-under fresh water dishwasher

ADA compliant, with baskets for hotels, restaurants and catering companies.



- Max. cleaning performance<sup>\*</sup>: 380 plates/h or 20 baskets/h
- Flexible processing of two wire or plastic baskets per cycle
- Simple to operate thanks to clear fascia panel design
- Always the right program itemspecific solutions
- First-class results thanks to fresh water system

EAN: 4002515460870 / material number: 09862610

| Model and design                                    |                             |
|---|-----------------------------|
| Design  | Built-under dishwasher      |
| Line  | Professional                |
| Wash system   | Fresh water                 |
| Number of levels                                    | 2                           |
| Front   | Stainless steel             |
| Lid   | Stainless steel             |
| - <del> </del>                                      |                             |
| Side walls  Convertible to a freestanding appliance | Stainless steel             |
| Convertible to a freestanding appliance             | Stand 1-80, stainless steel |
| Drying  | without                     |
| Application   | •                           |
| Suitable for small restaurants/bars                 | - <del>-</del>              |
| Suitable for hospitality industry                   | - <del>•</del>              |
| Suitable for Bed & Breakfast                        |                             |
| Suitable for canteens                               | - <del>•</del>              |
| Suitable for small businesses                       | <u>•</u>                    |
| Suitable for fast food restaurants                  | <u>•</u>                    |
| Suitable for sports clubs                           | · <u>·</u>                  |
| Suitable for fire brigades and rescue services      | •                           |
| Performance data                                    | 0.0 (000)                   |
| Circulation pump, Qmax in gal/min (l/min)           | 0.0 (390)                   |
| Shortest program duration in min.                   | 6                           |
| Maximum final rinse temperature in °F (°C)          | 159 (70)                    |
| Cleaning performance, plates/h                      | 380                         |
| Cleaning performance, baskets/h                     |                             |
| Possible to wash plastic baskets on two levels      |                             |
| Tested operating hours                              | 15,000                      |
| Controls  |                             |
| Control system                                      | TouchControl                |
| Program selection                                   | Touch on Metal              |
| Max. delay start in h                               |                             |
| Countdown indicator                                 | •                           |
| Program sequence indicator                          | •                           |
| Choice of display language                          | <u>•</u>                    |
| Language-neutral operation                          | •                           |
| Standard electrical connection                      |                             |
| Electrical connection                               | 2 PH. 240V 60HZ             |
| Heater rating in kW                                 | 5.40                        |
| Total connected load in kW                          | 5.80                        |
| Fuse rating in A                                    | 30                          |
| Length of connection wire in ft (m)                 | 7 (2.20)                    |
| Possible voltage variant 1                          | 0.511.04014.051.55          |
| Electrical connection                               | 3 PH. 240V 60HZ             |
| Heater rating in kW                                 | 5.4                         |
| Total connected load in kW                          | 5.80                        |
| Fuse rating in A                                    | 20                          |



## PG 8056 U [240V]

Built-under fresh water dishwasher ADA compliant, with baskets for hotels, restaurants and catering companies.



| Water connection/drainage   |   |
|---|---|
| Cold water [number]   | _ 1   |
| Hot water [number]  | 1   |
| Required flow pressure in bar   | 0,40-10,00  |
| Drain hose [DN]   | 22  |
| Maximum delivery head for drain pump in inches (cm)   | 39 3/8 (100)  |
| Integrated water softener   | •   |
| Maximum water hardness in gpg (mmol/l)  | 0.000 (10.70)   |
| Water consumption per wash cycle in gal (I)   | 2.1 (8.00)  |
| Dimensions and weight   |   |
| External dimensions, net height in inches   | 32 3/8 (820)  |
| External dimensions, net width in inches  | 23 5/8 (598)  |
| External dimensions, net depth in inches  | 22 7/8 (580)  |
| External dimensions, gross height in inches   | 37 1/8 (940)  |
| External dimensions, gross width in inches  | 26 5/8 (675)  |
| External dimensions, gross depth in inches  | 29 3/8 (745)  |
| Usable space in wash cabinet, width in inches (mm)  | 20 7/8 (530)  |
| Usable space in wash cabinet, height in inches (mm)   | 22 1/8 (559)  |
| Usable space in wash cabinet, depth of upper basket in inches (mm)  | 18 3/4 (474)  |
| Usable space in wash cabinet, depth of lower basket in inches (mm)  | 20 (505)  |
| In-feed height above floor in inches (mm)   | 8 5/8 (216)   |
| Net weight in lbs.  | 139 (63)  |
| Gross weight in lbs.  | 153 (69)  |
| Maximum floor loading in p/force  | 1,200   |
| Maximum iloor loading in phorce   | 1,200   |
| Emission levels   | 1,200   |
|   | 47 dB(A) re 20 μPa  |
| Emission levels   |   |
| Emission levels Emission sound pressure level in workplace (LpA)  | 47 dB(A) re 20 μPa  |
| Emission levels Emission sound pressure level in workplace (LpA) Sound power (LwA) in dB(A) re 1 pW   | 47 dB(A) re 20 μPa<br>59.0                                |
| Emission levels Emission sound pressure level in workplace (LpA) Sound power (LwA) in dB(A) re 1 pW Heat dissipation into the room in btu/h (MJ/h)  | 47 dB(A) re 20 μPa<br>59.0                                |
| Emission levels Emission sound pressure level in workplace (LpA) Sound power (LwA) in dB(A) re 1 pW Heat dissipation into the room in btu/h (MJ/h) Basket design  | 47 dB(A) re 20 μPa<br>59.0                                |
| Emission levels Emission sound pressure level in workplace (LpA) Sound power (LwA) in dB(A) re 1 pW Heat dissipation into the room in btu/h (MJ/h) Basket design 1 x O 891 upper basket for cups  | 47 dB(A) re 20 μPa<br>59.0                                |
| Emission levels Emission sound pressure level in workplace (LpA) Sound power (LwA) in dB(A) re 1 pW Heat dissipation into the room in btu/h (MJ/h) Basket design 1 x O 891 upper basket for cups 1 x U 890 lower basket for inserts   | 47 dB(A) re 20 μPa<br>59.0                                |
| Emission levels Emission sound pressure level in workplace (LpA) Sound power (LwA) in dB(A) re 1 pW Heat dissipation into the room in btu/h (MJ/h) Basket design 1 x O 891 upper basket for cups 1 x U 890 lower basket for inserts 1 x E 810 insert for dessert plates   | 47 dB(A) re 20 μPa<br>59.0                                |
| Emission levels Emission sound pressure level in workplace (LpA) Sound power (LwA) in dB(A) re 1 pW Heat dissipation into the room in btu/h (MJ/h) Basket design 1 x O 891 upper basket for cups 1 x U 890 lower basket for inserts 1 x E 810 insert for dessert plates 2 x E 816 inserts for plates  | 47 dB(A) re 20 μPa<br>59.0<br>1.08                        |
| Emission levels Emission sound pressure level in workplace (LpA) Sound power (LwA) in dB(A) re 1 pW Heat dissipation into the room in btu/h (MJ/h) Basket design 1 x 0 891 upper basket for cups 1 x U 890 lower basket for inserts 1 x E 810 insert for dessert plates 2 x E 816 inserts for plates 2 x E 165 inserts for cutlery  | 47 dB(A) re 20 μPa<br>59.0<br>1.08                        |
| Emission levels  Emission sound pressure level in workplace (LpA)  Sound power (LwA) in dB(A) re 1 pW  Heat dissipation into the room in btu/h (MJ/h)  Basket design  1 x 0 891 upper basket for cups  1 x U 890 lower basket for inserts  1 x E 810 insert for dessert plates  2 x E 816 inserts for plates  2 x E 165 inserts for cutlery  Height-adjustable upper basket   | 47 dB(A) re 20 μPa<br>59.0<br>1.08                        |
| Emission levels  Emission sound pressure level in workplace (LpA)  Sound power (LwA) in dB(A) re 1 pW  Heat dissipation into the room in btu/h (MJ/h)  Basket design  1 x 0 891 upper basket for cups  1 x U 890 lower basket for inserts  1 x E 810 insert for dessert plates  2 x E 816 inserts for plates  2 x E 165 inserts for cutlery  Height-adjustable upper basket  Features   | 47 dB(A) re 20 μPa<br>59.0<br>1.08                        |
| Emission levels  Emission sound pressure level in workplace (LpA)  Sound power (LwA) in dB(A) re 1 pW  Heat dissipation into the room in btu/h (MJ/h)  Basket design  1 x 0 891 upper basket for cups  1 x U 890 lower basket for inserts  1 x E 810 insert for dessert plates  2 x E 816 inserts for plates  2 x E 165 inserts for cutlery  Height-adjustable upper basket  Features  1 Combi dispenser/door for powder and liquid media   | 47 dB(A) re 20 μPa<br>59.0<br>1.08                        |
| Emission levels  Emission sound pressure level in workplace (LpA)  Sound power (LwA) in dB(A) re 1 pW  Heat dissipation into the room in btu/h (MJ/h)  Basket design  1 x O 891 upper basket for cups  1 x U 890 lower basket for inserts  1 x E 810 insert for dessert plates  2 x E 816 inserts for plates  2 x E 165 inserts for cutlery  Height-adjustable upper basket  Features  1 Combi dispenser/door for powder and liquid media  Wash cabinet made from high-quality stainless steel.   | 47 dB(A) re 20 μPa 59.0 1.08  • • • • • • • • •           |
| Emission levels  Emission sound pressure level in workplace (LpA)  Sound power (LwA) in dB(A) re 1 pW  Heat dissipation into the room in btu/h (MJ/h)  Basket design  1 x O 891 upper basket for cups  1 x U 890 lower basket for inserts  1 x E 810 insert for dessert plates  2 x E 816 inserts for plates  2 x E 165 inserts for cutlery  Height-adjustable upper basket  Features  1 Combi dispenser/door for powder and liquid media  Wash cabinet made from high-quality stainless steel.  In-door salt container   | 47 dB(A) re 20 μPa 59.0 1.08  • • • • • • • • • • • • • • |
| Emission levels  Emission sound pressure level in workplace (LpA)  Sound power (LwA) in dB(A) re 1 pW  Heat dissipation into the room in btu/h (MJ/h)  Basket design  1 x O 891 upper basket for cups  1 x U 890 lower basket for inserts  1 x E 810 insert for dessert plates  2 x E 816 inserts for plates  2 x E 165 inserts for cutlery  Height-adjustable upper basket  Features  1 Combi dispenser/door for powder and liquid media  Wash cabinet made from high-quality stainless steel.  In-door salt container  Perfect GlassCare  | 47 dB(A) re 20 μPa 59.0 1.08  • • • • • • • • • • • • • • |
| Emission levels  Emission sound pressure level in workplace (LpA)  Sound power (LwA) in dB(A) re 1 pW  Heat dissipation into the room in btu/h (MJ/h)  Basket design  1 x O 891 upper basket for cups  1 x U 890 lower basket for inserts  1 x E 810 insert for dessert plates  2 x E 816 inserts for plates  2 x E 165 inserts for cutlery  Height-adjustable upper basket  Features  1 Combi dispenser/door for powder and liquid media  Wash cabinet made from high-quality stainless steel.  In-door salt container  Perfect GlassCare  Adjustable final rinse temperature  | 47 dB(A) re 20 μPa 59.0 1.08  • • • • • • • • • • • • • • |
| Emission levels  Emission sound pressure level in workplace (LpA)  Sound power (LwA) in dB(A) re 1 pW  Heat dissipation into the room in btu/h (MJ/h)  Basket design  1 x O 891 upper basket for cups  1 x U 890 lower basket for inserts  1 x E 810 insert for dessert plates  2 x E 816 inserts for plates  2 x E 165 inserts for cutlery  Height-adjustable upper basket  Features  1 Combi dispenser/door for powder and liquid media  Wash cabinet made from high-quality stainless steel.  In-door salt container  Perfect GlassCare  Adjustable mash temperature  Adjustable wash temperature  | 47 dB(A) re 20 μPa 59.0 1.08  • • • • • • • • • • • • • • |
| Emission levels  Emission sound pressure level in workplace (LpA)  Sound power (LwA) in dB(A) re 1 pW  Heat dissipation into the room in btu/h (MJ/h)  Basket design  1 x O 891 upper basket for cups  1 x U 890 lower basket for inserts  1 x E 810 insert for dessert plates  2 x E 816 inserts for plates  2 x E 165 inserts for cutlery  Height-adjustable upper basket  Features  1 Combi dispenser/door for powder and liquid media  Wash cabinet made from high-quality stainless steel.  In-door salt container  Perfect GlassCare  Adjustable mash temperature  Adjustable rinse time  | 47 dB(A) re 20 μPa 59.0 1.08  • • • • • • • • • • • • • • |
| Emission levels  Emission sound pressure level in workplace (LpA)  Sound power (LwA) in dB(A) re 1 pW  Heat dissipation into the room in btu/h (MJ/h)  Basket design  1 x O 891 upper basket for cups  1 x U 890 lower basket for inserts  1 x E 810 insert for dessert plates  2 x E 816 inserts for plates  2 x E 165 inserts for cutlery  Height-adjustable upper basket  Features  1 Combi dispenser/door for powder and liquid media  Wash cabinet made from high-quality stainless steel.  In-door salt container  Perfect GlassCare  Adjustable final rinse temperature  Adjustable vash temperature  Adjustable rinse time  Optical interface | 47 dB(A) re 20 μPa 59.0 1.08  • • • • • • • • • • • • • • |



## PG 8056 U [240V]

Built-under fresh water dishwasher

ADA compliant, with baskets for hotels, restaurants and catering companies.



| Test certificates and symbols                 |   |
|---|---|
| CE  | • |
| VDE   | • |
| Interference suppression                      | • |
| DIN 10512                                     | • |
| EN 1717                                       | • |
| EMC   | • |
| ADA compliant                                 | • |
| Complies with Machinery Directive 2006/4 2/EC | • |