

FRIGIDAIRE

FFAD3533W1

Frigidaire Moderate Humidity 35 Pint Capacity Dehumidifier



AVAILABLE COLORS

MORE EASY-TO-USE FEATURES

Front Loading Bucket with Carrying Handle and Splash Guard

A water bucket is conveniently located in the front of the unit for easy access, while the carry handle and splash guard make emptying your bucket hassle-free.

Portable Design

Easily move from room to room with caster wheels and side handles, dehumidifying your room when and where you need it.

Low Temperature Operation

This unit is designed to operate at low temperatures down to 41°F.

Multi-Speed Fan

Enjoy more cooling flexibility with three different fan speeds.

ENERGY STAR® Certified

Use less energy, reduce your energy usage and ultimately lower your utility bills.

SIGNATURE FEATURES

Easy-to-Clean Washable Filter

Capture dust from the air and keep your dehumidifier working efficiently with our easy-to-clean washable filter.

Custom Humidity Control

Maximize your comfort with customized control over the amount of humidity in your room.

Continuous Drain Option

Skip emptying the water bucket -- this unit continuously drains your dehumidifier so that you don't have to lift a finger.

Automatic Shut Off

Unit shuts off automatically when the water bucket is full.

CERTIFICATIONS

ENERGY STAR®



FFAD3533W1Frigidaire Moderate Humidity
35 Pint Capacity Dehumidifier**General Specifications**

Product Weight	41.19 lbs
Prop 65 Label	Yes
Warranty - Labor	1 Year
Warranty - Parts	1 Year
Power Type	Electric
Size	None
Installation Type	Free-Standing
Collection	Frigidaire

Performance

Dehumidification - Pints per Day	35.23
----------------------------------	-------

Safety Certifications & Approvals

UL Listed	Yes
cUL Listed	Yes
Energy Efficiency Verification (Canada)	Yes
ENERGY STAR Certified	Yes

Dimensions and Volume

Height	24 1/4"
Width	15 31/32"
Depth	12 3/16"

Dehumidifier

Air CFM (Low)	167 CFM
Air CFM (High)	229 CFM
Air CFM (Med)	194 CFM
Fan Speeds - Fan	3
Noise Level dB (Low)	45 dB
Noise Level dB (Med)	48 dB
Noise Level dB (High)	51 dB
Motor RPM (Low)	880 RPM
Motor RPM (Med)	980 RPM
Motor RPM (High)	1,160 RPM
Container Capacity	16.9 pints
Container Full Indication	Yes
Digital Humidity Readout	Yes
Filter Access	Yes
Filter Check Indicator	Yes
Filter Type	Easy-to-Clean Washable Filter
Low Temperature Operation	Yes

Installation

Power Cord Length	72"
-------------------	-----

Controls

Control Type	Electronic
--------------	------------

Functions

24-Hour On/Off Timer	Yes
Auto Restart	Yes
Auto Shut-Off	Yes
Continuous Drain Operation	Yes

Electrical Specifications

Plug Type	LCDI 515P
Voltage Rating	115 V

Note: For planning purposes only. Always consult local and national electric, gas and plumbing codes. Refer to Product Installation Guide for detailed installation instructions on the web at frigidaire.com / frigidaire.ca.

Specifications subject to change. Accessories information available on the web at frigidaire.com / frigidaire.ca

FRIGIDAIRE

USA • 10200 David Taylor Drive • Charlotte, NC 28262 • 1-800-FRIGIDAIRE • frigidaire.com
 CANADA • 5855 Terry Fox Way • Mississauga, ON L5V 3E4 • 1-800-265-8352 • frigidaire.ca

FFAD3533W1
 ©2017 Electrolux Home Products, Inc.