



**15" SIGNATURE SERIES**  
*Wine Reserve*



**eco friendly**  
R600a Refrigerant



JOB	
AREA	
ITEM NO.	
MODEL NO.	



Glass Door Model



Solid Door Model

MODELS	DESCRIPTION
<b>HP15WS-4-1R/L</b>	Indoor Signature Series Wine Reserve Solid Stainless Steel Door
<b>HP15WS-4-2R/L</b>	Indoor Signature Series Wine Reserve Solid Panel Ready Door
<b>HP15WS-4-3R/L</b>	Indoor Signature Series Wine Reserve Stainless Steel Glass Door
<b>HP15WS-4-4R/L</b>	Indoor Signature Series Wine Reserve Panel Ready Glass Door
<b>HP15WO-4-1R/L</b>	Outdoor Signature Series Wine Reserve Solid Stainless Steel Door
<b>HP15WO-4-2R/L</b>	Outdoor Signature Series Wine Reserve Solid Panel Ready Door
<b>HP15WO-4-3R/L</b>	Outdoor Signature Series Wine Reserve Stainless Steel Glass Door
<b>HP15WO-4-4R/L</b>	Outdoor Signature Series Wine Reserve Panel Ready Glass Door

**KEY PRODUCT FEATURES AND BENEFITS**

- 1000 BTU/hr capacity delivers industry's most energy efficient cool down, indoors or outdoors
- Up to 70% faster cooling speeds than leading competitor
- Variable speed compressor minimizes sound; up to 30% quieter than competitors
- Commercial-grade all stainless steel interior and exterior provide superior durability and easy cleaning
- Perlick Anti-Condensation System™ eliminates condensation from forming on the cabinet (outdoor models only)

**Quick Features:**

- Wine shelves fully extend on vibration dampened, stainless steel ball-bearing glides; stainless steel wine shelves will not absorb odors over time
- Industry's best full 6 year warranty for owner ease of mind
- Available with stainless steel or panel ready doors to match your design style
- Audible door alarm warns user if door is held open
- Selectable blue or white LED lighting
- R600a Natural Refrigerant offers maximum energy efficiency with zero global warming potential
- Storage for up to 20 bottles of wine



**15" SIGNATURE SERIES**  
*Wine Reserve*

MODEL NUMBERS		HP15WS	HP15WO
MODEL DESCRIPTION		15" Indoor Wine Reserve	15" Outdoor Wine Reserve
ATTRIBUTES			
Perlick Anti-Condensation System		NO	YES
OVERALL DIMENSIONS	Width - in. (mm)	14-7/8" (378 mm.)	14-7/8" (378 mm.)
	Depth - in. (mm)	24" (610 mm.)	24" (610 mm.)
	Height - in. (mm)	34-1/4" (870 mm.)	34-1/4" (870 mm.)
OPENING DIMENSIONS	Width - in. (mm)	15" (381 mm.)	15" (381 mm.)
	Depth - in. (mm)	24-7/8" (632 mm.)	24-7/8" (632 mm.)
	Height - in. (mm)	34-1/2" (876 mm.)	34-1/2" (876 mm.)
INTERNAL VOLUME Net. Cu. Ft.		2.8 cu. ft	2.8 cu. ft
SHIPPING WEIGHT Lbs. (kg.)		175 lbs (79.38 kg)	175 lbs (79.38 kg)
ELECTRICAL SPECIFICATIONS	Electrical Supply	115 VAC/60 Hz/1 Ph	115 VAC/60 Hz/1 Ph
	Running Load Amps	2.1 amps	2.1 amps
	Electrical Connection	Cord connected	Cord connected
	Cord Plug Type	NEMA 3 Prong 5-15P	NEMA 3 Prong 5-15P
	Cord Length	6'	6'
	Defrost Initiation	Automatic	Automatic
	Defrost Type	Off cycle	Off cycle
	Thermostat	Digital	Digital
REFRIGERATION SPECIFICATIONS	Lighting Type	LED	LED
	Refrigerant	R600a (38g)	R600a (38g)
	Expansion Device	Capillary Tube	Capillary Tube
	Temperature Settings F°(C°)	45° (7.2°) - 65° (18.33°) Factory Set Point 36° (2.2°)	45° (7.2°) - 65° (18.33°) Factory Set Point 36° (2.2°)
	Heat Rejection (at 75°F)	300 BTU/hr	300 BTU/hr
	Pull Down Capacity	1000 BTU/hr	1000 BTU/hr
Front Vented	Yes	Yes	
PLUMBING		None Required	None Required

Installation Notes: To achieve 24" install depth, place electrical connection adjacent to the installation cavity.

**ACCESSORIES**

MODEL NOS.	DESCRIPTION
(L)	Factory Installed Lock
67990-L/R	Stacking Kit for HP15 models
66736-15	Caster Kit for HP15 models
67115-15	Wood Faces for Wine Shelves (5/pk)

Perlick accessories are available for purchase through an authorized Perlick dealer. For a full list of accessories and to find a dealer near you, visit [perlick.com](http://perlick.com).




**15" SIGNATURE SERIES**  
*Wine Reserve*

CUSTOMER MODEL NUMBER	REGULATORY MODEL NUMBER	Hinge Side	Lock
HP15WS-4-1L	HP15WS4F-00-SLF0W	Left	No
HP15WS-4-1R	HP15WS4F-00-SRF0W	Right	No
HP15WS-4-2L	HP15WS4F-00-PL00W	Left	No
HP15WS-4-2R	HP15WS4F-00-PR00W	Right	No
HP15WS-4-3L	HP15WS4F-00-TLF0W	Left	No
HP15WS-4-3R	HP15WS4F-00-TRF0W	Right	No
HP15WS-4-4L	HP15WS4F-00-RL00W	Left	No
HP15WS-4-4R	HP15WS4F-00-RR00W	Right	No
HP15WS-4-1LL	HP15WS4F-00-SLFLW	Left	Yes
HP15WS-4-1RL	HP15WS4F-00-SRFLW	Right	Yes
HP15WS-4-2LL	HP15WS4F-00-PL0LW	Left	Yes
HP15WS-4-2RL	HP15WS4F-00-PR0LW	Right	Yes
HP15WS-4-3LL	HP15WS4F-00-TLFLW	Left	Yes
HP15WS-4-3RL	HP15WS4F-00-TRFLW	Right	Yes
HP15WS-4-4LL	HP15WS4F-00-RL0LW	Left	Yes
HP15WS-4-4RL	HP15WS4F-00-RR0LW	Right	Yes
HP15WO-4-1L	HP15WO4F-00-SLF0W	Left	No
HP15WO-4-1R	HP15WO4F-00-SRF0W	Right	No
HP15WO-4-2L	HP15WO4F-00-PL00W	Left	No
HP15WO-4-2R	HP15WO4F-00-PR00W	Right	No
HP15WO-4-3L	HP15WO4F-00-TLF0W	Left	No
HP15WO-4-3R	HP15WO4F-00-TRF0W	Right	No
HP15WO-4-4L	HP15WO4F-00-RL00W	Left	No
HP15WO-4-4R	HP15WO4F-00-RR00W	Right	No
HP15WO-4-1LL	HP15WO4F-00-SLFLW	Left	Yes
HP15WO-4-1RL	HP15WO4F-00-SRFLW	Right	Yes
HP15WO-4-2LL	HP15WO4F-00-PL0LW	Left	Yes
HP15WO-4-2RL	HP15WO4F-00-PR0LW	Right	Yes
HP15WO-4-3LL	HP15WO4F-00-TLFLW	Left	Yes
HP15WO-4-3RL	HP15WO4F-00-TRFLW	Right	Yes
HP15WO-4-4LL	HP15WO4F-00-RL0LW	Left	Yes
HP15WO-4-4RL	HP15WO4F-00-RR0LW	Right	Yes



**15" SIGNATURE SERIES**  
*Wine Reserve*



\* - Leg leveler can add  $3\frac{1}{4}"$  [19] to these dimensions when fully extended.

