

H 6560 B AM

24 Inch Convection Oven with PerfectClean for very easy cleaning at an attractive entry level price.



- TFT clear text display with touch operation SensorTronic
- Achieve perfect results with ease Automatic programs
- Particularly easy to clean -PerfectClean finish
- Precise temperature roasting Roast probe
- Lots of room and versatility

EAN: 4002515430705 / material number: 09769400	
Construction type	
Built-in wall oven	•
Design	
ContourLine	•
Appliance color	Clean Touch Steel
Control panel	SensorTronic
Convenience features	
Precise temperature control	75 – 575 °F
Roast probe	•
Operating modes	
Defrost	•
MasterChef automatic programs	More than 100
Auto roast	•
Gentle bake	•
Broil	•
Convection Bake	•
ntensive bake	•
Slow roast	<u> </u>
Surround	-
	<u> </u>
Browning Balka	`
Bake	
Convection Broil	-
Special modes	•
Control panel	
MultiLingua	•
Time of day display	<u> </u>
Date display	<u> </u>
Minute minder	<u> </u>
Time buffer in h	200
Start-stop programming	<u> </u>
Automatic switch-off	<u> </u>
Programmable cooking time	<u> </u>
Entry via number keypad	<u> </u>
Actual temperature display	•
Default temperatures	•
Acoustic signal when desired temperature is reached	•
Sabbath program	•
ndividual settings	•
Door	
CleanGlass door	•
Door contact switch	•
Door hinge side	Bottom
Cavity	
Cavity volume in cu.ft(I)	2.97 (84)
No. of rack levels	5
Labeling of rack levels	
No. of halogen lamps	double
Cleaning convenience	
Stainless steel front with Clean Touch Steel surface	•
Foldable broil heater element	

More information at www.MieleUSA.com



H 6560 B AM

24 Inch Convection Oven with PerfectClean for very easy cleaning at an attractive entry level price.




Efficiency and sustainability	
Energy-saving lighting circuit	•
Residual heat utilization	•
Rapid PreHeat	•
Safety	
Appliance cooling system with cool touch front	•
Safety cut-out	•
System lock	•
Door contact switch	•
Technical data	
Niche depth in in. (mm)	21 3/4 (550)
Appliance width in in.(mm)	21 13/16 (554)
Appliance height in in.(mm)	22 7/8 (579)
Weight in lbs. (kg)	92.59 (42.0)
Total connected load in kW	4.2
Voltage in V	240/208
Fuse rating in A	30
Number of phases	1
Standard accessories	
Universal baking tray with PerfectClean	1
Baking tray with PerfectClean	1
PerfectClean baking and roasting rack	1
Side racks with PerfectClean	1 pair
Connection wire	•
Connection wire with plug	•




H 6560 B AM

24 Inch Convection Oven with PerfectClean for very easy cleaning at an attractive entry level price.







H 6000 E/B, 60 cm (Installation drawing) - USA

A= Cut-out (4"x22" / 100 mm x 560 mm) in the bottom of the cabinet for power cord and Ventilation B= Power cord with plug * Oven with glass front ** Oven with metal front

H 6000 E/B, 60 cm (Installation drawing) - USA

A= Cut-out (4"x22" / 100 mm x 560 mm) in the bottom of the cabinet for power cord and Ventilation B= Power cord with plug * Oven with glass front ** Oven with metal front