## SUMMIT

# SBC15NKIF



34.25" x 15" x 22.5" (H x W x D)

15" wide, built-in, commercially listed kegerator, auto defrost with digital thermostat, panel-ready door, front lock, sealed back, and black cabinet

### **Highlights:**

Designed for built-in installation under the counter

Listed to NSF-7 standards and meets UL 471 for commercial use

15" wide design makes it ideal for smaller residential and commercial settings

#### **Product Features:**

15" wide design	Slim-fit design complements smaller commercial and residential spaces	
Commercially approved	ETL-S listed to NSF-7 standard and meets UL-471 for use in commercial settings	
Built-in capability	Make the best use of space by installing your appliance under the counter; NOTE: if installing flush with wall or cabinets, unit will require an extra ¼" of space due to the door design. For more information, see the user manual	
Versatile kegerator	2.9 cu.ft. interior can accept a 1/6 (sixtel) barrel keg or a pony keg; compatible with beer, wine, coffee, or kombucha tap systems	
Panel-ready door	Integrated stainless steel door frame accepts full overlay panels, allowing you to customize the refrigerator door or blend it into your cabinetry design	
Automatic defrost	Reduced user maintenance with auto defrost operation	
Digital thermostat	Electronic controls ensure easy temperature management, with an external readout in Celsius or Fahrenheit	
Tap cool system	Keeps cold air flowing to the tower for consistently cold beer	
Stainless steel floor cover	Interior includes steel cover to protect the floor when loading kegs	
-		



### **SBC15NKIF Specifications:**

Overview		
Height of Cabinet	34.25" (87 cm)	
Width	15.0" (38 cm)	
Width with Door Open	15.25" (39 cm)	
Depth	22.5" (57 cm)	
Depth with Handle	24.5" (62 cm)	
Depth with door at 90°	36.5" (93 cm)	
Capacity	2.9 cu.ft. (82 L)	
Defrost Type	Automatic	
Door	Panel-Ready	
Cabinet	Black	
US Electrical Safety	ETL	
Canadian Electrical Safety	ETL-C	
Sanitation	ETL-S	
Energy Usage/Year	280.0kWh/year	
Amps	1.25	
Voltage/Frequency	115 V AC/60 Hz	
Weight	74.0 lbs. (34 kg)	
Shipping Weight	80.0 lbs. (36 kg)	
Parts & Labor Warranty	1 Year	
Compressor Warranty	5 Years	
UPC	761101067872	
Kegerator		
Door Swing	RHD	
Reversible	Factory Reversible	
Adjustable Shelves	Yes	
Shelf Type	Chrome	
Shelf Qty	2	
Thermostat Type	Digital	
Fan Type	Exterior	
Refrigerant	R600a	
Refrigerant Amount	1.06 oz.	
High Side PSI	150.0	
Low Side PSI	50.0	
Inter Height	26.75" (68 cm)	
Interior Width	11.75" (30 cm)	
Interior Depth	17.5" (44 cm)	
Compressor Step Height	3.75" (10 cm)	

Compressor Step Width	11.75" (30 cm)
Compressor Step Depth	5.0" (13 cm)
Level Legs Qty	4
Wheel Qty	4
Temperature Range	34º to 50º F

