



Special Notes: LED GU10 lighting. M600 and M1200 blowers are sold separately. Features stainless steel baffle filters.

WIDTH:	48"			
DEPTH:	24"			
HEIGHT:	18"			
CFM:	See Chart			
SONES:	N/A			
AMPS:	See Chart			
# LIGHTS:	3			




CONNECTION DIAGRAM


Wall Side 5 6" Round Centerline of Hood



M600 & M1200 Connection Diagrams

VP566 Transition Details (Included with M1200)





Optional Duct Cover

REC. MOUNTING HEIGHT*

* Exceeding recommended mounting height may compromise performance.

(CHART B)

(CHART B)								
SPEED	CFM @ 0.1" S.P.							
SPEED	M600	WHM300 *	M1200					
1	240	240	420					
2	300	300	645					
3	500	-	865					
1	625		1015					

* The WHM300 is a wiring harness that when used with the M600 blower (sold separately) will disable blower speeds exceeding 300 CFM.

(CHART A) ELECTRICAL/MECHANICAL SPECIFICATIONS FOR BLOWER UNIT

MODEL	VOLTS	AMPS+	HZ	CFM SP@0.0"	CFM SP@0.1"	CFM SP@0.25"	CFM SP@0.5"	CFM SP@0.75"	MIN. ROUND DUCT SIZE
M600 Single	115	5.0	60	630	625	615	600	580	6" (28in.^2)
M600 w/WHM300 Harness	115	5.0	60	302	300	295	288	278	6" (28in.^2)
M1200 Dual	115	10.0	60	1035	1015	1000	995	915	10" (79in.^2)

⁺Add 0.5 amp for each halogen light. Hoods are available with halogen lights (2 lights: 30" - 41", 3 lights: 42" - 53", 4 lights: 54" - 66").

