



Get the Custom Look Without the Custom Price

With a profile of just 2", Millenia LP Trio delivers a custom, tailored look when paired with <u>any</u> flat panel TV. Its 48" length makes it an ideal match for most 55" TV's.



Millenia LP Trio 48" Left/Center/Right Soundbar

Hallmark Paradigm sound. Ultra-thin 2" profile. Single speaker convenience. When space is a premium or aesthetics dictate that a single speaker with left, center and right capability is preferred, then Millenia LP Trio is the perfect choice.

Like other speakers in the Millenia series the "Trio" tackles the high-end audio spectrum expected from Paradigm in a design that's also discreet for its size. Ideally suited to wall mounting, Millenia LP Trio is perfectly at home on a credenza too using the supplied table top stands. Brushed black aluminium faceplate and polished black accents give Millenia LP Trio an understated look that belies the science held within.

Advanced Technology Includes:

- Patented Perforated Phase Alignment (PPA[™]) Lens: smooths extended high frequency response for incredible detail (US Patent: 10, 003, 869).
- **S-PAL Aluminum Cones:** Aluminum yields less distortion than polypropylene by moving resonance out the driver's pass band. The result is clean and clear sound in just 1-3/4" profile.
- **7 Driver, 2-way design:** ensures clear, vibrant sound from the small enclosure.





Millenia LP Trio mounts with the terminal cup positioned at the top or bottom for easy wire management.







Seismic 110

MilleniaSUB

Round out Performance with a Paradigm Subwoofer

While Millenia LP Trio sounds great right out-of-the-box, there's a subwoofer to accompany the Millenia LP Trio. Consider the **MilleniaSUB** or **Seismic 110**. Or if you prefer a sub that is as discreet as Millenia LP Trio itself, try our **RVC-12SQ** or **PCS-82SQ** in-wall subwoofers.



RVC-12SQ



PCS-82SQ

Specifications

DESIGN

9-driver, 3-channel, 2-way acoustic suspension, on-wall / shelf-mounted

FREQUENCY RESPONSE ON-AXIS

+/-3dB from 150-20kHz

HIGH FREQUENCY DRIVER

Three 25mm (1") S-Pal dome, ferro-fluid damped and cooled

MIDRANGE FREQUENCY DRIVER

Two 114mm (4.5") anodized unibody cones, 37mm (1.5") high temperature aluminum voice coils, Nomex spider, Nitrile rubber surround, neodymium magnet, basket intergrated motor heat dissipation system, tempered steel heatfin basket

SENSITIVITY ROOM / ANECHOIC 92dB/89dB

IMPEDANCE Compatible with 8 ohms

FINISH

Black gloss with brushed aluminum accents

WEIGHT

5.9kg (13 lbs)

DIMENSIONS (h x w x d) 122cm x 16.2cm x 5.1cm (48" x 6.4" x 2"), <u>With stands:</u> 122cm x 16.2cm x 9.7cm (48" x 6.4" x 3.8")

LOW FREQUENCY EXTENSION 125Hz (DIN)

CROSSOVER

2nd-order electro-acoustic at 2.8kHz for the center channel and 2.7kHz for the left and right channels

FREQUENCY RESPONSE 30° OFF-AXIS

+/-3dB from 150-17kHz

SUITABLE AMPLIFIER POWER RANGE 15-130W

MAXIMUM INPUT POWER 65W

INPUTS

Low profile push terminals



