

STYLE#: 22543

WARNING: TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER BEFORE INSTALLING OR SERVICING THIS FIXTURE.

Carefully unpack all lamp parts from carton. We suggest a licensed electrician for all fixture installations.

- 1. Take the lamp carefully out of the Carton, and place on a flat surface.
- 2.Be sure the power to the installation point is off.
- 3. Pass the supply wires through the Universal Bar. Attach the Universal Bar to Outlet Box with the head of Green Ground Screw facing you. Secure it with Outlet Box Screws. Tighten until snug
- 4. Connect the wire as shown.
 - a. Connect the House Ground Wire to the Fixture Ground Wire, secure with wire nut.
 - b.Connect the House White (or Ribbed) Wire to the Fixture Supply Wire (White or Ribbed Side), secure with wire nut.
 - c. Connect the House Black (or Red) Wire to the Fixture Supply Wire (Black or Smooth Side), secure with wire nut.
 - d.Carefully stuff all of the connected wires into the Outlet Box.
- 5. Attach the Fixture Body over the Universal Bar and secure with Screws. Tighten until snug with screwdrivers.
- 6. Place the Fabric Shade carefully onto the Socket.
- 7. Install the Bulb referring to fixture markings and/or labels for maximun wattage on the Socket(No Included)

Your installation is completed now. Restore electricity.





