## YIM15-PR | 15" Clear Ice Machine Individual Cube: Pump Model



- Produces up to 68 lbs of 1<sup>1</sup>/<sub>6</sub>" x 1<sup>1</sup>/<sub>6</sub>" x 1<sup>1</sup>/<sub>4</sub>" clear individual cubes per day
- Bin stores up to 25 lbs of clear ice
- Integrated water filter system removes any impurities producing the clearest ice
- Clear ice scoop and storage hook included
- Blue interior light
- Fully wrapped stainless-steel exterior
- Arti culati ng, concealed self-closing hinges with built-in door stop
- Multi functi on capacitati ve touch electronic control
- Auto shut-off when ice bin is full
- Alert noti fi es when ti me to initi ate easy cleaning process
- Quiet Mode Feature can be set to suspend ice-making producti on during specifi c ti mes of the day
- Full LED theater lighting
- Unit ships right hinged with fi eld-reversible doors
- Stainless model includes a 1" diameter stainless steel handle with faceted standoff s (26" length)
- Panel Ready model requires ¾" custom door panel and handle
- Precise Zero Clearance Design allows for unmatched integrati on into any built-in setti ng
- 4 independent adaptable leveling legs
- Black steel grille accepts an integrated toe kick
- Adaptable grille design allows alignment with adjacent cabinetry and toe kick/plinth
- Installati on requires a customer-supplied water line and includes a 10 ft factory-installed drain line
- Gravity drain and factory-installed pump models available





## **Model Details**

Model	Pump	Finish	Description	Shipping Weight
YIM15-PR	Yes	Panel Ready	15" Indoor Clear Ice Machine Individual Cube	120 lbs

Dimensions/Weight	Detail
Product Depth	23 ¼"
Product Height	34" - 35"
Product Width	14%"
Product Weight	100 lbs
Shipping Dimensions	17 ¾" x 27 ½" x 36 ¾"
Shipping Weight	120 lbs

Integration/Panel Information*	Detail
Panel Height	30" - 31"
Panel Thickness	¾" – 20 mm
Panel Width	14 %"

\*Refer to manual for all panel dimensions and installation instructions

## 

Model	Details	
Control Type	Electronic Capacitative Touch with OLED Screen	
Indoor or Outdoor	Indoor	
Built-in Installation	Inset, Frameless / Overlay and Framed Cabinet Styles	
Ice Size	1½" x 1½" x 1¼"	
lce Weight (g) per unit	22 g / 0.0485 lbs	
Ice Quantity per cycle	24 Individual Cubes (1¼ lbs)	
Ice Production Capacity	68 lbs	
Ice Storage Capacity	25 lbs	
Refrigerant Type	R290	

Plumbing Water	Details	
Water Inlet Adapter	1/4" OD Compression Fitting*	
Water Pressure Operating Range (psi)	20 psi – 80 psi	
Integrated Water Filter System	Yes	
Water Usage	16½ gallons per 100 lbs of ice	
Factory Installed Drain Line	10 feet	
Drain Required	Yes (See manual for details)	
*Water line not included		

Electrical	Details
Electrical Requirements	115 V / 60 Hz
Volt Range	104 V ~ 127 V
Maximum Amp Fuse	15 amp
Amps Running	2.4 amps

Approvals - Certifications	Details
Energy Star	Yes
ETL Sanitation	Yes
UL Commercial	Yes



NOTE: For Gravity drain models, the drain hole cannot exceed 7 inches above the floor. For Pump models, the drain hole should be no lower than 7 inches and no higher than 4 feet above the floor



\*Dimensions are the same for Panel Ready unit when  $\ensuremath{\ensuremath{\mathbb{N}}}$  " panel applied



Back View