

Danby Medical Fridges

NIST Digital Data Logger

Danby Health is the medical division of Danby, producing freezers and fridges for medical, clinical, and scientific use. Whether in a lab, pharmacy, retirement home, or for personal use - you can trust the brand with over 70 years of quality refrigeration experience.



1.6 Cubic Foot Refrigerator

FEATURES

- Temperature Range: 36°F to 46°F (2°C to 8°C)
- Purpose-built to meet the recommendations of the CDC and VFC for reliable vaccine storage
- Separate ISO 17025:2017 Certified NIST thermometer with data logging and temperature alarm functions

SPECIFICATIONS

| | | |
|---------------|----------|-----------|
| Width | 44.93 cm | 17 11/16" |
| Depth | 49.21 cm | 19 6/16" |
| Height | 53.02 cm | 20 14/16" |

DH016A1W-D
Digital Data Logger
UPC 67638028028



3.2 Cubic Foot Refrigerator

FEATURES

- Temperature Range: 36°F to 46°F (2°C to 8°C)
- Purpose-built to meet the recommendations of the CDC and VFC for reliable vaccine storage
- Separate ISO 17025:2017 Certified NIST thermometer with data logging and temperature alarm functions

SPECIFICATIONS

| | | |
|---------------|----------|-----------|
| Width | 44.93 cm | 17 11/16" |
| Depth | 49.21 cm | 19 6/16" |
| Height | 87.47 cm | 34 7/16" |

DH032A1W-D
Digital Data Logger
UPC 67638028042



Danby Health 1.6 Cubic Foot Medical Refrigerator - White

DH016A1W



FEATURES

- ▶ **Temperature Stability:** Engineered to maintain a steady temperature range (2°C - 8°C)(36°F - 46°F)
- ▶ **Internal Forced Air Fan:** Ensures even cooling from top to bottom
- ▶ **Integrated Temperature Logger:** Tracks refrigerator readings, a simple and definitive solution to accurate air temperature monitoring.
- ▶ **High/Low Alarm:** Alarm sounds when fridge air temperature rises or falls of set range.
- ▶ **Keyed Door Lock:** Ensures ultimate temperature control and product safety.
- ▶ **Hospital Grade Power Cord:** This unit features a durable hospital grade green dot power cord.
- ▶ **Compact Design:** Danby Health is made for fitting in, this unit is the perfect counter size for pharmacies, labs, clinics, research centers, beauty counters, senior homes and medical offices.
- ▶ **UL 471 Compliant**
- ▶ **Includes Silver Coated Handle**

SPECIFICATIONS & DESCRIPTION

Dimensions

| | | |
|----------------|----------|-----------|
| Product Width | 44.93 cm | 17 11/16" |
| Product Depth | 49.21 cm | 19 6/16" |
| Product Height | 53.02 cm | 20 7/16" |

Shipping Details

| | | |
|--------|----------|---------|
| Weight | 20.80 kg | 45.86lb |
|--------|----------|---------|

Capacity

| | |
|------------------|-------------|
| Loading Capacity | 1.6 cu. ft. |
|------------------|-------------|

UPC: 067638013826

Warranty

24 months parts and labor coverage with carry-in service. Installation and/or yearly maintenance (cleaning) are not covered under warranty.

Traceable Excursion-Trac™ Data Logging Thermometer with Calibration: 1 Bottle Probe



FEATURES

- ▶ Includes NIST-Traceable certificate from our A2LA accredited (1750.01) calibration laboratory.
- ▶ Memory can be cleared after downloading data & alarm events.
- ▶ Set limits for and store up to 10 unique events.
- ▶ Smart-Alarm™ with visual/audible alarm continues to alert even if conditions return to normal range.
- ▶ Triple-display: shows high, low, and current temperature simultaneously.

INCLUDES

- ▶ Glass bottle probe with 10-ft cable, flip-open stand, hook and loop strips, magnetic strips, wall-mount receptacle, batteries, and NIST-traceable calibration certificate with data.

SPECIFICATIONS & DESCRIPTION

| | |
|--------------------------|--------------------------|
| Meter Measurement Type | Digital Indicator |
| Number of Probe Channels | 1 |
| Min Temperature (°F) | -58 |
| Max Temperature (°F) | 158 |
| Min Temperature (°C) | -50 |
| Max Temperature (°C) | 70 |
| Accuracy | ±0.25°C |
| Resolution | 0.01° |
| Data Logging | Yes |
| Memory Capacity | 525,600 (rolling memory) |
| Alarm | Yes |